







EVOLVE 30II

# Engineered for flexible connectivity and great sound for calls and music.

-  Great calls and music
-  Plug-and-play connectivity
-  Manage calls easily
-  Flexible connectivity via 3.5 mm jack, USB-A or USB-C



## TECHNICAL SPECIFICATIONS

<b>General info</b>	Box content	Evolve 30 II headset, pouch, foam inlay (only available for duo), layer card, poly bag, documentation	
	Packaging dimensions LxWxH	Mono: 149.6x59.5x170.1 mm/5.88x2.3x6.7 inch Stereo: 151.2x59.5x170.4 mm/5.9x2.3x6.7 inch Multipack: 358x198x214 mm/14.9x7.79x8.42 inch	
	Main unit dimension	Stereo with cable 138.2 mm/without cable 103.6 mm Stereo with cable 5.44 inch/without cable 4.08 inch Mono with cable 107.8 mm/without cable 72.8 mm Mono with cable 4.24 inch/without cable 2.87 inch	
	Weight including main wearing style	<b>Evolve 30II USB-C</b> Stereo with cable: 138.2 g/4.87 oz Stereo without cable: 93.2 g/3.28 oz Mono with cable: 107.9 g/3.80 oz Mono without cable: 62.9 g/2.21 oz	<b>Evolve 30II USB-A</b> Stereo with cable: 146.1 g/5.15 oz Stereo without cable: 93.2 g/3.28 oz Mono with cable: 117.4 g/4.14 oz Mono without cable: 62.9 g/2.21 oz
	Material used	Soft headband and comfortable on-the-ear foam ear pads	
	Warranty	2 years	
	Jabra Direct/Jabra Xpress	Yes	
	Jabra Sound+	No	
	LED features and functions	Busylight, incoming calls, Microsoft Teams notifications*	
	<b>Audio</b>	Headset bandwidth	Wideband
Speaker size		ø28x3.9mm	
Speaker sensitivity		93.6dB SPL @ 1kHz	
Speaker impedance		32+/-4.8Ω, @ 1.0kHz	
Speaker max input power		Rated Input 5mW @ 0.4V, max input 10mW @ 0.56V	
Speaker frequency range		150Hz~7kHz, @ Output S.P.L -10dB	
Speaker bandwidth Speak mode		150Hz~7kHz, @ Output S.P.L -10dB	
Microphone type		Electret condenser (ECM)	
Microphone sensitivity		F=1kHz, pin=1Pa, 0dB=1V/Pa, Min=-48dB, Max=-44dB	
Microphone frequency range		100Hz ~ 10kHz @ 6dB	
Microphone bandwidth		Wideband	
User hearing protection		Jabra SafeTone™**	
Certifications		Leading UC vendors; Microsoft Teams-certified*	
<b>Fit &amp; Comfort</b>	Headset form factor	On-ear headband	
<b>Connectivity</b>	Connection (computer and mobile devices)	3.5 mm jack, USB-A/USB-C	
	Cord length	Control cable: 95 cm/37.4 in, HS cable: 120 cm/47.24 in	
	AC power supply	USB power supply by PC	
<b>Extended Info</b>	Power consumption speaker	Rated Input 5mW @ 0.4V, max input 10mW @ 0.56V	
	Operating temperature	-10°C to +50°C, 14°F to 122°F	
	Storage temperature	-30°C to +80°C Storage temperature range: (-20°C to +35°C 6 months), (+35°C to +45°C 3 months), (+45°C to +45°C 1 month), (+60°C to +70°C 1 hour with no degradation), (+70°C to +85°C max. 1 hour < 20% degradation)	

\*Microsoft Teams variants only \*\*Supports Peakstop and Intellitone G616

PRODUCT TYPE	SKU	DESCRIPTION	EAN CODE
Stereo	5399-823-309	Jabra Evolve 30 II MS Stereo, USB-A	5706991019964
	5399-823-389	Jabra Evolve 30 II MS Stereo, USB-C	5706991023879
	5399-829-309	Jabra Evolve 30 II UC Stereo, USB-A	5706991019971
	5399-829-389	Jabra Evolve 30 II UC Stereo, USB-C	5706991023886
Mono	5393-823-309	Jabra Evolve 30 II MS Mono, USB-A	5706991019940
	5393-823-389	Jabra Evolve 30 II MS Mono, USB-C	5706991023893
	5393-829-309	Jabra Evolve 30 II UC Mono, USB-A	5706991019957
	5393-829-389	Jabra Evolve 30 II UC Mono, USB-C	5706991023909
Accessory	14208-35	Jabra Evolve 30 II LINK MS Controller, USB-C	5706991023923
	14208-36	Jabra Evolve 30 II LINK UC Controller, USB-C	5706991023930
Multipack	14401-40	Jabra Evolve 30 II Stereo 3.5mm Jack, Multipack (10 units)	5706991027716