



Each WSU wire wrapping tool wraps, unwraps and even strips the appropriate wire diameter with a unique built-in stripper blade. Ideal for bench use or tool kit in all service and repair applications. In addition to versatility, convenience, and reliability, the WSU Series offers exceptional value.

SPECIFICATIONS	WSU-24M	WSU-26M	WSU-30	WSU-30M	WSU-2224
<b>WRAP TYPE</b>	Modified	Modified	Regular	Modified	Regular
<b>WIRE GAUGE</b>	24 AWG (0.5 mm)	26 AWG (0.40 mm)	30 AWG (0.25 mm)	30 AWG (0.25 mm)	22-24 AWG (0.65-0.50 mm)
<b>TERMINAL HOLE DIA.</b>	0.075" (1.9 mm)	0.075" (1.9 mm)	0.036" (0.91 mm)	0.036" (0.91 mm)	0.075" (1.9 mm)
<b>TERMINAL HOLE DEPTH</b>	1.50" (38.1 mm)	1.50" (38.1 mm)	1.50" (38.1 mm)	1.50" (38.1 mm)	1.50" (38.1 mm)
<b>OUTSIDE DIAMETER</b>	.213" (5.4mm)	.213" (5.4mm)	.125" (3.2mm)	.125" (3.2mm)	.213" (5.4mm)
<b>WRAP POST SIZE</b>	0.045" (1.14 mm)	0.045" (1.14 mm)	0.025" (0.63 mm)	0.025" (0.63 mm)	0.045" (1.14 mm)
<b>FUNCTIONS</b>	Wrap, Unwrap, and Strip	Wrap, Unwrap, and Strip	Wrap, Unwrap, and Strip	Wrap, Unwrap, and Strip	Wrap, Unwrap, and Strip
<b>WEIGHT</b>	0.106 lbs (48.08g)	0.104 lbs (47.17g)	0.076 lbs (34.47g)	0.076 lbs (34.47g)	0.086 lbs (39.01g)
<b>UPC #</b>	811490013667	811490013100	811490012172	811490011335	811490010291

