

DYNEO DD Heating Immersion Circulator

New temperature control technology for demanding applications

DYNEO DD heating circulators for internal and external applications are equipped with closed bath tanks. The tanks are well insulated and include a coil for counter-cooling. An integrated drain tap makes emptying the tank safe and clean. The multilingual 3.5-inch color display and unique rotary knob provide for straightforward and intuitive operation.

Your advantages

- Flexible installation options
- For internal and external applications
- Powerful and infinitely adjustable pressure pump
- Flow rate 23 l/min, pressure 0.6 bar
- Easy switching between internal and external circulation
- Large color TFT display, multilingual interface
- Central rotary knob (controller) simplifies operation
- Integrated programmer for 8 x 60 program steps
- Integrated external Pt100 connection
- USB port
- RS232 interface or analog interfaces (optional)



Technical Data

Order No.	9021000
Order No. with RS232 Option	9021000.D
Order No. with analog Option	9021000.A
Model series	DYNEO
Category	Heating Immersion Circulators
Working temperature range (°C)	+20 ... +200
Temperature stability (°C)	±0.01
Setting / display resolution	0.01 °C
Temperature Display	3.5" TFT Display
Heating capacity (kW)	2
Pump capacity flow rate (l/min)	8 ... 23
Pump capacity flow pressure (bar)	0.1 ... 0.6
Viscosity max. (cSt)	50
Ambient temperature	5...40 °C
Dimensions W x L x H (cm)	13.2 x 16 x 35.5
Weight (kg)	2.5
Cooling coil	optional
Usable immersion depth (cm)	16
Available voltage versions	100-115V/50-60Hz 200-230V/50-60Hz

Characteristics