

## CORIO CP-1001F Refrigerated/Heating Circulator

with an enhanced pump performance and a temperature range up to +200°C

Refrigerated Circulators from the CORIO CP range are suitable for applications with a temperature range up to +200°C. The enhanced pump performance ensures they are suitable for easy temperature control tasks in combination with external applications.

### Your advantages

- Models for internal and external applications
- Bright, white, easy-to-read display
- Very quiet
- Easy change-over from internal to external circulation and vice versa
- External pump connections (M16x1)
- USB interface
- R232 interface
- Space-saving cooling coil design provides more usable space in the bath tank
- Bath lid and drain tap included
- Removable ventilation grid
- Refrigeration unit without side vents
- System for low liquid level
- Class III (FL) according to DIN 12876-1



Made in Germany

### Technical Data

Order No.	9013708
Model series	CORIO
Category	Refrigerated - Heating Circulators
Working temperature range (°C)	-38 ... +100
Temperature control	PID
Temperature stability (°C)	±0.03
Setting / display resolution	0.01 – 0.1 °C
Temperature Display	LED
Heating capacity (kW)	1
Pump capacity flow rate (l/min)	8 ... 27
Pump capacity flow pressure (psi)	1.5 ... 10.2
Bath opening / bath depth (W x L / D inch)	13.8 x 16.1 x 11.8
Pump connections	M16x1
Barbed fittings diameter (inner dia. / mm)	8 / 12
Filling volume liters	42 ... 56
Refrigerant stage 1	R452A
Filling volume refrigerant stage 1 (g)	170
Global Warming Potential for	2140
Carbon dioxide equivalent stage 1 (t)	0.364

Ambient temperature	5...40 °C
Dimensions W x L x H (inch)	17.7 x 25.2 x 37.4
Weight (LBS)	162.5
Included with each unit	2 each barbed fitting for tubing 8 and 12 mm inner dia. (pump connections M16x1 male)
Bath tank	Stainless steel
Bath cover	integrated
Cooling of compressor	Air
Available voltage versions	230 V / 50 - 60 Hz

### Characteristics



**100% Checked.**

100% testing. 100% quality. Each CORIO undergoes thorough quality testing before leaving the factory.



**More bath.**

Designed for more comfort. Thanks to the recessed cooling coil, the internal bath provides more space.



**ATC.**

Absolute Temperature Calibration, 1-point calibration (CD).



**Powerful. Adjustable.**

Strong pressure pump, continuously adjustable.



**Brilliant.**

Bright display with strong illumination can be viewed easily from a long distance.



**Quick start.**

Individual JULABO consultation and comprehensive manuals at your disposal.



**Condensation protection.**

Superb design solution. Integrated ventilation directs air over the bath lid and minimizes condensation.



**Safety.**

CORIO complies with Class III (FL) according to DIN 12876-1 and switches off automatically in case of high temperature or low liquid level alarm.



**Connection. Easy.**

Inclined pump connections (M16x1) facilitate the connection of applications. Each unit includes 2 barbed fittings of 8/12 mm diameter each.



**Satisfied customers.**

11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



**Connectivity.**

Remote control made easy. CORIO CP circulators feature a USB connection.




**Services 24/7.**

Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at [www.julabo.com](http://www.julabo.com).



**Early warning system for low liquid level.**  
Maximum safety for your application. Optical and audible alarm allows user to refill bath fluid in time.



**Solid.**  
Minimized energy loss through high-quality insulation.



**Everything at the front.**  
All operating controls and safety functions are accessed easily and comfortably from the front.



**Space saving. Free up space.**  
Place your JULABO Circulator right next to an application, another unit, or wall. That saves space. This is made possible by eliminating vents and connections on the sides.



**Exact.**  
You can rely on it. PID1 control and 'Active Cooling Control' make the new CORIO precise and perfect.



**Stable.**  
Rubber feet allow for a secured footing of your CORIO to prevent damage to your laboratory equipment.



**Green technology.**  
Development consistently applied environmentally friendly materials and technologies.



**Switch on. And off you go.**  
Intelligent operating concept. Ready for operation with just a few quick and easy steps.



**Handle with ease.**  
Makes day-to-day work easy. Comfortably move your CORIO around by using the ergonomic handles (front and rear).



**Click.**  
One for all. Control the circulator and the refrigeration unit with only one power switch.



**Internal. External.**  
The pump is controlled via a lever located directly below the display. Easily change between internal and external circulation.



**Tidy.**  
The special drain tap for easy draining of bath fluids without tools.



**JULABO. Quality.**  
Highest standards of quality for a long product life.



**Timer. Integrated.**  
CORIO circulators include an integrated timer function. When the set time has elapsed, a signal sounds and the device switches off. Setting range: 0 ... 999 minutes



**Locked in.**  
The lockable power plug guarantees safe connection. More process safety.



**Touching permitted.**  
Optimum safety. The ergonomic plastic handle protects your fingers from hot surfaces.




**Mobile.**

Extra easy handling. Integrated castors for easy repositioning of refrigerated circulators. (CD-600F, CD-601F, CD-900F, CD-1000F, CD-1001F)



**Unique.**

Specially designed pyramids ensure that the condensed liquid drips directly back into the bath.



**Modern. Reliable.**

Every JULABO Circulator is equipped with high-grade components like i.e. platinum sensors, proven motor technology, CAN-Bus communication and much more.



**USB.**

Remote control made easy. CORIO CD circulators feature a USB connection.