

diamond

product data sheet



Technical Data

Name	<i>Diamond</i>
Order number	9FT2000
Temperature range	68 °F ... 203 °F (20 °C ... 95 °C)
Temperature stability	±0.018 °F (±0.01 °C)
Temperature setting	digital
Temperature display (0.01 display resolution)	VFD display
Connections	
Computer interface	RS232
Internal temperature sensor	Pt100
Mains/power connection	115 V / 60 Hz
Current draw	11.1 A
Heating capacity	1.2 kW @115 V, 2 kW @230 V
Circulating pump	
Voltage options	230 V / 50-60 Hz 115 V / 60 Hz
Overall dimensions (W*D*H) behind actual dimensions	5.24 x 8.35 x 13 inches (133 x 212 x 330 mm)
Weight	11 lbs (5 kg)
Standards	NRTL certified / RoHs compliant
Warning and safety equipment	
Low-level protection	float switch
Vapor barrier protection	YES
Alarm notification	optical / audible
Permissible ambient temperature	+41 °F ... +104 °F (+5 °C ... +40 °C)

Description

Diamond has all of the features that make *Pearl* so special plus additional innovative functions like pre-programmed memory keys for meat, fish, and vegetables, straightforward HACCP data logging, and calibration functions.

When used in conjunction with the core temperature sensor, *Diamond* emits an alarm to indicate that your selected core temperature has been reached. The *Easy fusionchef* software gives you the ability to control, visualize, and log HACCP-relevant data for up to 24 *Diamond* units simultaneously.

The timers can be started separately from each other so you always stay in control, even during hectic situations. The timer that will expire next is shown continuously. A visual and acoustic signal informs the chef when the desired time has passed. The timer then goes into the minus range so you always know the total time that the food has been cooking.

Each of the pre-programmed memory keys (fish, meat, and vegetables) is set by default to five practical temperature values. Of course, you can edit these values at any time. It doesn't get any easier than that!



Technical changes reserved. Image may differ from original.

diamond

product data sheet



At a glance:

- Temperature stability of $\pm 0.018^{\circ}\text{F}$ ($\pm 0.01^{\circ}\text{C}$)
- Splash-proof operating keypad
- Bright VFD temperature display
- Hygienic anti-fingerprint stainless hood
- Low-water alarm
- Three timers
- Pre-programmed temperature memory keys (fish, meat, vegetables)
- Core temperature alarm (acoustic and visual)
- Straightforward HACCP-compliant data storage
- Guided-user auto calibration
- Simultaneous display of target and actual temperatures, core temperature, and timer
- PC control and recording
- High-capacity pump 3.7 gal/min (14 l / min)
- For container volumes up to 15.32 gal (58 l)
- Easy to install and clean
- Stainless steel protection grid (included)
- Vapor barrier protection
- Temperature display switchable between $^{\circ}\text{C}$ and $^{\circ}\text{F}$

How much food can be cooked in the different bath sizes?

To make sure the bath will maintain a uniform temperature please notice that the bath is not fully packed with food and that the water should always circulate. The weight in lbs/kg refer to beef tenderloin.

XS Bath Tank: 3.4 gal (13 l)	up to 13.2 lbs (up to 6 kg)
S Bath Tank: 5 gal (19 l)	up to 19.8 lbs (up to 9 kg)
M Bath Tank: 7.1 gal (27 l)	up to 28.7 lbs (up to 13 kg)
L Bath Tank: 11.6 gal (44 l)	up to 46.3 lbs (up to 21 kg)
XL Bath Tank: 15.3 gal (58 l)	up to 63.9 lbs (up to 29 kg)

Technical changes reserved. Image may differ from original.