Thermal P90

Version: 2.2

Reviewed on 12.11.2015 Print date: 12.11.15



SECTION 1. Identification of the substance/mixture and of the company

Product identifier

Name Used on Label Thermal P90 Order-No. (5 Liter) 8891415 Order-No. (10 Liter) 8891414 Order-No. (55 Gal Drum): 8891307

Company JULABO U.S.A., INC Manufactured for:

884 Marcon Blvd

ALLENTOWN,PA 18109 / U.S.A.

[+1] 610-231-0250 Phone Fax [+1] 610-231-0260 E-mail info@julabo.com Internet www.julabo.com

Emergency Information : CHEMTREC 1-800-424-9300

:Polydimethylsiloxane Trade name

Recommended use : JULABO PRESTO® Highly Dynamic Temperature Control Systems Only

: temperature control liquid Application

: PRESTO® working temperature range: -90 °C - +170 °C

SECTION 2. Hazards identification

GHS Classification

Flammable liquids Category 4

GHS Label Element

Signal Word Warning

H227 Combustible liquid **Hazard Statements**

Precautionary Statements Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking

P280 Wear protective gloves/eye protection/face protection

Storage

P403+P235 Store in a well-ventilated place. Keep cool

Disposal

P501 Dispose of contents/container to an approved waste disposal

Facility.

HMIS Ratings: Health: 0 Flammability: 2 Physical hazard: 0

SECTION 3. Composition / information on ingredients

Substances

Substances/Mixture Mixture Chemical nature Silicone

Chemical Name	CAS number	%
Dodecamethylpentasiloxane	141-63-9	90-100
Polydiimethylsiloxane	63148-62-9	1-5
Dodecamethyl cyclohexasiloxane	540-97-6	1-5

Dangerous components Not applicable

SECTION 4. First aid measures

Description of first aid measures

JULABO USA, Inc. www.julabo.com Page 1 of 7

Thermal P90

Version: 2.2

Reviewed on 12.11.2015 Print date: 12.11.15

General information: No special measures required

Inhalation Supply fresh air; consult doctor in case of complaints.

Skin contact Wash skin with soap and water; consult doctor if symptoms occur.

Eye contact Rinse immediately with plenty of water for at least 15 minutes. Get medical

attention if irritation develops and persists.

Ingestion Rinse mouth. DO NOT induce vomiting. Get medical attention immediately.

Most important symptoms/effects, acute and delayed None known No special precautions are necessary for first aid responders. Protection of first-aidersB Indication of immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5. Firefighting measures

167 °F / 75 °C (Closed Cup) Flash point:

Boiling point: 442 °F / 229 °C **Autoignition temperature:** 430 °C

Not determined Flammability Limits in Air:

Suitable extinguishing media Dry foam, alcohol-resistant foam. Carbon dioxide (CO₂), water.

Unsuitable extinguishing media Water with full jet.

Specific hazards arising from

the chemical

Do not use a solid water stream as it may scatter and spread fire.

Flash back possible over considerable distance. Vapors may form explosive mixture with air. Fire burns more vigorously than would be expected.

Exposure to combustion products may be a hazard to health.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet, gloves, rubber boots, and self-contained breathing apparatus.

Fire-fighting equipment /

Instructions

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Cool containers/tanks with water spray. Remove

containers from fire area if it is safe to do so. Evacuate area.

SECTION 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear appropriate personal protective equipment. Particular danger of slipping on leaked / spilled product. Remove all ignition sources.

Environmental precautions

Do not allow product to reach sewage system or any water course. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Non-sparking tools should be used. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.

Suppress gases/vapors/mists with a water spray jet.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. Handling and storage

Technical measures

See engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation

Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation.

Conditions for safe storage, including any incompatibilities

JULABO USA, Inc. www.julabo.com Page 2 of 7

Thermal P90

Version: 2.2

Reviewed on 12.11.2015 Print date: 12.11.15



Store in a cool, dry place out of direct sunlight. Keep in original, properly labeled container. Keep away from heat and sources of ignition.

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practices. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment.

Materials to avoid

Do not store with the following product types: strong oxidizing agents, explosives, gases.

SECTION 8. Exposure controls / personal protection

Occupational exposure limits No exposure limits noted for ingredient(s).

Biological limit valuesNo biological exposure limits noted for the ingredient(s).

Appropriate engineering controls Provide eyewash station

Engineering measuresProcessing may form hazardous compounds (Section 10)
Ensure adequate ventilation, especially in confined areas

Use only in an area equipped with explosion proof exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face protection Use proper protection – safety glasses as a minimum

Skin protection

Hand protection Wear flame retardant protective gloves

Other Wear flame retardant antistatic protective clothing. Skin contact must

be avoided by using impervious protective clothing (gloves, aprons,

boots, etc.)

Respiratory protection General and local exhaust ventilation is recommended to maintain

vapor exposures below recommended limits. Where concentrations

are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator

regulations (29 CFR 1910.134) and NIOSH/MSHA approved

respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide adequate protection.

Thermal hazards Not available

General hygiene considerations

Wash hands before breaks and immediately after handling product. Handle in accordance with good industrial hygiene and safety practice. This product can generate formaldehyde at approximately 150 °C (300 °F) and above in the presence of air. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant and potential cancer hazard. Safe handling conditions may be maintained by keeping vapor concentrations within the OSHA Permissible Exposure Limit for formaldehyde.

SECTION 9. Physical and chemical properties

Physical Form Liquid Color Colorless Odor Odorless **Density** 0.872 (@ 25 °C) Viscosity 2 cSt (@ 25 °C) Not available pН Freezing / melting point Not available Initial boiling point / boiling range >205 °C

 $\begin{array}{ll} \textbf{Flash point} & 87 \ ^{\circ}\text{C (Closed Cup)} \\ \textbf{Auto-ignition temperature} & >752 \ ^{\circ}\text{F} \, / \, 430 \ ^{\circ}\text{C} \\ \end{array}$

Self-igniting Product is not self-igniting

Danger of explosion Product does not present an explosion hazard

Decomposition temperature Not available

JULABO USA, Inc. www.julabo.com Page 3 of 7

Thermal P90

Version: 2.2

Reviewed on 12.11.2015 Print date: 12.11.15

Evaporation rate Not available

Volatile content 0%

Flammability (solid, gas) Not applicable

Upper / lower flammability or explosive limits

Flammability limit – lower (%)

Flammability limit – upper (%)

Explosive limit – lower (%)

Explosive limit – upper (%)

Not available

Not available

Not available

Vapor pressureNot availableVapor densityNot availableSolubility in waterInsoluble

Oxidizing properties Not classified as oxidizing

Molecular weight Not available

Above information is not intended for use in preparing product specifications.

SECTION 10. Stability and reactivity

Reactivity Product stable and non-reactive under normal conditions of use,

storage and transport. Not a reactive hazard.

Chemical stability Stable at normal conditions

Possibility of hazardous reactions Hazardous polymerization does not occur. Combustible liquid. Vapors

may form explosive mixture with air. Can react with strong oxidizing agents. When heated to temperatures above 150 °C (300 °F) in the presence of air, trace quantities of formaldehyde may be released. Adequate ventilation is required. See OSHS formaldehyde standard

29 CFR 1910.1048 Heat, flames, sparks. Strong oxidizing agents

Hazardous decomposition products Hazardous decomposition products will be formed at elevated

Temperatures.

SECTION 11. Toxicological information

Information on likely routes of exposure

Conditions to avoid

Incompatible materials

IngestionNot availableInhalationNot availableSkin contactNot available

Eye contact Contact of the product with the human eye may result in a harmless

and reversible clouding of sight which is of short duration, caused by

formation of an oil film on the cornea.

Symptoms related to the physical, chemical and toxicological characteristics

Information on toxicological effects

Acute oral toxicity LD50 (rat): >2,000 mg/kg

No acute oral toxicity based on data from similar results.

Acute dermal toxicity LD50 (rabbit): >2,000 mg/kg

No acute dermal toxicity based on data from similar results.

Skin corrosion / irritation Not classified based on available information.

Species Rabbit

Result No skin irritation

Remarks Based on data from similar results

Serious eye damage / eye irritation Not classified based on available information.

Species Rabbit

Result No eve irritation

Remarks Based on data from similar materials

Respiratory or skin sensitization

Respiratory sensitizationNot classified based on available informationSkin sensitizationNot classified based on available informationGerm cell mutagenicityNot classified based on available information

JULABO USA, Inc. www.julabo.com Page 4 of 7

Thermal P90

Version: 2.2

Reviewed on 12.11.2015 Print date: 12.11.15

Germ cell mutagenicity
Not classified based on available information
Genotoxicity in vitro
Test type: Bacterial reverse mutation assay (AMES)

Result Negative; based on test data

Carcinogenicity

IARC No ingredient of this product present at levels greater than

or equal to 0.1% is identified as probable, possible or

confirmed human carcinogen by IARC

ACGIH No ingredient of this product present at levels greater than

or equal to 0.1% is identified as probable, possible or

confirmed human carcinogen by ACGIH.

OSHA No ingredient of this product present at levels greater than

or equal to 0.1% is identified as probable, possible or

confirmed human carcinogen by OSHA.

NTP No ingredient of this product present at levels greater than

or equal to 0.1% is identified as probable, possible or

confirmed human carcinogen by NTP.

Reproductive toxicity

Specific target organ toxicity – single exposure Specific target organ toxicity – repeated exposure Not classified based on available information Not classified based on available information Not classified based on available information

Further information This material contains dodecamethylcyclohexasiloxane (D6). D6 was administered to rats by whole body inhalation to 0, 1, 10 and 30 ppm for a period of 13-14 weeks. An increased incidence and severity of inflammation and hyperplasia was observed in the nasal region in the 10 and 30 ppm dose groups. These observations are consistent with a mucosal irritant, however there was little or incomplete recovery after the 28-day recovery period. The relevance of these findings to humans is unknown.

SECTION 12. Ecological information

EcotoxicityNot availablePersistence and degradabilityNot availableBioaccumulative potentialNot availableMobility in soilNot availableOther adverse effectsNot available

SECTION 13. Disposal considerations

Disposal methods Follow applicable Federal, State and Local regulations

Resource Conservation and Th

Recovery Act(RCRA)

This product has been evaluated for RCRA characteristics and does not meet

the criteria of hazardous waste if discarded in its purchased form.

Waste from residues Dispose of in accordance with local regulations

Contaminated packaging Dispose of as unused product. Empty containers should be taken to an

Approved waste handling site for recycling or disposal. Do not burn or use

cutting torch on the empty drum.

SECTION 14. Transport information

UNRTDG Not regulated as dangerous goods.
IATA-DGR Not regulated as dangerous goods.
IMDG-Code Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

Domestic regulation 49 CFR

UN/ID/NA number NA1993

Proper shipping name COMBUSTIBLE LIQUID, N.O.S.

(Dodecamethylpentasiloxane, Dodecamethyl cyclohexasiloxane)

Class CBL Packing Group III

JULABO USA, Inc. www.julabo.com Page 5 of 7

Thermal P90

Version: 2.2

Reviewed on 12.11.2015 Print date: 12.11.15

Labels None
ERG Code 128
Marine pollutant No

Remarks Above applies only to containers over 119 gallons or 450 liters. Not regulated

if shipped in packages less than or equal to 119 gallons (450 liters).

SECTION 15. Regulatory information

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity This material does not contain any components with a CERCLA RQ.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards Fire Hazard

Sara 302 No chemicals in this material are subject to the reporting requirements of SARA Title

III, Section 302.

SARA 313 (TRI reporting)

None present or not present in regulated quantities.

DOT Road Shipment Information (49 CFR 172.101)

Not subject to DOT.

Ocean Shipment (IMDG)

Not subject to IMDG code.

Air Shipment (IATA)

Not subject to IATA regulations

US state regulations

Massachusetts RTK – Substance List

Not regulated

New Jersey Worker and Community Right-to-Know Law

CAS Number [141-63-9] 90-100 wt% Dodecamethylpentasiloxane

CAS Number [63148-62-9] 1-5 wt% Dimethyl Siloxane, trimethylsiloxy-terminated

CAS Number [540-97-6] 1-5 wt% Dodecamethyl cyclohexasiloxane

Pennsylvania Worker and Community Right-to-Know Law

CAS Number [141-63-9] 90-100 wt% Dodecamethylpentasiloxane

CAS Number [63148-62-9] 1-5 wt% Dimethyl Siloxane, trimethylsiloxy-terminated

CAS Number [63148-62-9] >60 wt% Polydimethylsiloxane

Rhode Island RTK Not regulated

California Proposition 65 This product does not contain any chemicals known to the

State of California to cause cancer, birth or any other

reproductive defects.

International Inventories

Ingredients of this product are reported in the following inventories

Listed, exempt or notified on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed or exempted on the Japanese ENCS (Existing * New Chemical Substances) inventory

Listed or exempt on the Canadian Domestic Substances List (DSL)

Listed, exempt or notified on KECI (Korean Existing Chemicals Inventory)

Included or exempted on USA Toxic Substances Control Act (TSCA)

Listed or exempt on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed or exempt on NZloC (New Zealand Inventory of Chemicals)

Listed on the AICS (Australian Inventory of Chemical Substances)

SECTION 16. Other information

This document was created on 5 May 2015.

NFPA ratings Health: 0 – Exposure under fire conditions would offer no hazard beyond that

of ordinary combustible materials.

Flammability: 2 – Must be moderately heated or exposed to relatively high ambient

temperature before ignition can occur and multiple finely

JULABO USA, Inc. www.julabo.com Page 6 of 7

Safety Data Sheet / Product Details Thermal P90

Version: 2.2


Reviewed on 12.11.2015 Print date: 12.11.15



divided suspended solids that do not require heating before ignition can occur.

Instability:

0 - Normally stable, even under fire exposure conditions, and not reactive with water.



HMIS III

HEALTH	0
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

DISCLAIMER

Information presented herein has been compiled from information provided to us by our suppliers and other sources considered to be dependable and are accurate and reliable to the best of our knowledge and belief but are not guaranteed to be so. We make no warranty as to the results to be obtained in using any material and since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of any material supplied by us.

All chemicals may pose unknown hazards and should be used with caution. This Safety Data Sheet (SDS) applies only to the material as packaged. If this product is combined with other materials, deteriorates, or becomes contaminated, it may pose hazards not mentioned in this SDS. It shall be the user's responsibility to develop proper methods of handling and personal protection based on the actual conditions of use. While this SDS is based on technical data judged to be reliable, JULABO USA, Inc. assumes no responsibility for the completeness or accuracy of the information contained herein.