



Comprehensive Scope 2 Monocular Head

Model # TU-19011C / TU-19011C-230

Detailed Specifications (January 2014)

Head	Eyepieces	1 – WF10x 19mm eyepiece with built-in coating for humidity and poor climate; 1 with pointer; all fixed to avoid loss and damage	
	Eyepiece Tubes	1 – Variable adjustment $\pm 0.20x$ for varied eye strengths.	
	Monocular View with 45° incline	1 -- 45° Angle 360° rotation attached eyepieces comfortable student or teacher viewing	
Frame	Aluminum Single Cast	“Y” shape base for ideal research application	
	Integrated Stow and Go Handle™	Retractable Handle for transport are integrated into the body of the unit.	
	Integrated storage	Storage compartment with built-in receptacle for the external power supply	
	“Table Guard” protection base	Base outlined with resilient polymer to avoid daily damage to the Microscope or the surrounding surfaces	
	Illumination	Ken-A-Vision LED cool lighting source with very long life (12,000+ hours), on/off switch, and dimmer rheostat. On/off switch and dimmer are separate, dimmer rheostat is low position light control	
	Power	USB compliant / IEC 62684:2011 charging system standardized on external USB to AC adapter 5V--1A DC operation included or USB 2.0 computer port or backward compliant for legacy power supply 5.5V--500mA; 7.5V--800mA	
Optics	Nose Piece	Reversed 4 hole nose piece with 4 position ball bearing action stop, 360 full rotation	
	Objectives	3 – lead free, humidity and climate protected by special coating; manufactured according to DIN: Achromat 4x N.A. 0.10, Achromat 10x N.A. 0.25, Achromat 40x(S) N.A. 0.65 (with built-in spring action tip to avoid crushing of specimen)	
Stage	Fixed Plain Stage w/Side Clips	12cm x 12cm x 0.7cm modular attachment to frame 2 spring loaded clips for slides	
	Focus	Low position coaxial focus with left or right hand low drive control; with rotating mechanism and torque adjustment 1 coarse rotation from minimum to maximum stage height. Fine 0.002mm per unit scale mechanism, rubber grips on both fine and coarse focus knobs; Fine focusing scale value 0.002mm	
Optional upgrades	Viewing Head	Dual View with 30° incline opposing view (SC12DH) Compensation Free Binocular Head (SC12BH) Compensation Free Trinocular Head (SC12TH) Compensation Free Digital Monocular Head (SC12CMH2) Compensation Free Digital Binocular Head (SC12CBH2)	
	Eyepiece	WF 16x, WF 20x	
	Achromatic Objective	20x, 60x(S), 100x(S) Oil	
	Plan Objective	4x, 10x, 20x, 40x(S), 60x(S), 100x(S) Oil	
	Semi-Plan Objective	4x, 10x, 20x, 40x(S), 60x(S), 100x(S) Oil	
	Illumination	Halogen bulb 6v/20W, Adjustable Brightness	
	Packing	Boxing	Two inner cartons in one outer carton
		Protective Cover	Durable Clear Dust cover with Ken-A-Vision logo
	Weights and Dims	14lbs/6.4kgs - 20" X 16" X 13"/50.8cm X 40.64cm X 33.02cm	
Certificates	Patents	Multiple Patents Pending	
	Quality Certificates	ISO:9001--2000	
	Local Certificates	CE, CSA, RoHS	
	Warranty Guarantee	10 Years against manufacturing faults	