

SAFETY DATA SHEET (SDS)

According to 1907/2006/EC, Article 31

Printing Date 11/01/2016

Version number 4

Reviewed on 11/01/2016

1 PRODUCT AND COMPANY IDENTIFICATION**Trade name: 245 CORE Sn63Pb37****Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

Application of the substance / the preparation: Flux cored solder**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

Kester Inc.

800 West Thorndale Avenue

Itasca, IL 60143 USA

Tel (630) 616-4000

Tel International 00 1 630 616-4000

ITW Specialty Materials (Suzhou) Co., Ltd.

Heng Qiao Road

Wujiang Economic Development Zone

Suzhou, Jiangsu 215200 China

Tel +86 512 82060808

Kester GmbH

Ganghofer Strasse 45

D-82216 Gernlinden Germany

Tel +49 (0) 8142 4785 0

Information department: Product Compliance: EHS_Kester@kester.com**1.4 Emergency telephone number:**

CHEMTREC 24-Hour Emergency Response Telephone Number : (800) 424-9300

CHEMTREC 24-Hour Emergency Response (Outside US & Canada) Telephone Number : (703) 527-3887

2 HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 1 H360 May damage fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labeled according to the CLP regulation.

(Contd. on page 2)

US

SAFETY DATA SHEET (SDS)

According to 1907/2006/EC, Article 31

Printing Date 11/01/2016

Version number 4

Reviewed on 11/01/2016

Trade name: 245 CORE Sn63Pb37

(Contd. of page 1)

Hazard pictograms



GHS07 GHS08

Signal word Danger

Hazard-determining components of labeling:

LEAD (Pb)

Hazard statements

H302 Harmful if swallowed.

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P330 Rinse mouth.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard description:

WHMIS Symbols



Classification system:

NFPA ratings (scale 0 - 4)



Health = 1

Fire = 1

Reactivity = 0

HMIS-ratings (scale 0 - 4)



Health = *1

Fire = 1

Reactivity = 0

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

(Contd. on page 3)

SAFETY DATA SHEET (SDS)

According to 1907/2006/EC, Article 31

Printing Date 11/01/2016

Version number 4

Reviewed on 11/01/2016

Trade name: 245 CORE Sn63Pb37

(Contd. of page 2)

3 COMPOSITION OF MIXTURE

Description: Mixture of the substances listed below with nonhazardous additions.

CAS No.	Description	% Range
CAS: 7440-31-5 EINECS: 231-141-8	TIN (Sn)	55-70%
CAS: 7439-92-1 EINECS: 231-100-4	LEAD (Pb)	25-40%

⚠ Carc. 2, H351; Repr. 1B, H360; STOT RE 2, H373
⚠ Acute Tox. 4, H302; Acute Tox. 4, H332

Additional information:

^ Composition and weight percent of solder alloys varies widely and can be determined by product label.

4 FIRST AID MEASURES

4.1 Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Follow general first aid procedures.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO₂)

Aliphatic aldehydes

5.3 Advice for firefighters

Protective equipment: No special measures required.

6 ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Melted solder will solidify on cooling and can be scraped up. Use caution to avoid breathing fumes if a gas torch is used to cut up large pieces.

6.4 Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 4)

SAFETY DATA SHEET (SDS)

According to 1907/2006/EC, Article 31

Printing Date 11/01/2016

Version number 4

Reviewed on 11/01/2016

Trade name: 245 CORE Sn63Pb37

(Contd. of page 3)

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:

7440-31-5	TIN (Sn)	6 mg/m3
7439-92-1	LEAD (Pb)	0.15 mg/m3
106-65-0	Methyl succinate	2.5 ppm
50-01-1	guanidinium chloride	1.4 mg/m3

PAC-2:

7440-31-5	TIN (Sn)	67 mg/m3
7439-92-1	LEAD (Pb)	120 mg/m3
106-65-0	Methyl succinate	28 ppm
50-01-1	guanidinium chloride	16 mg/m3

PAC-3:

7440-31-5	TIN (Sn)	400 mg/m3
7439-92-1	LEAD (Pb)	700 mg/m3
106-65-0	Methyl succinate	170 ppm
50-01-1	guanidinium chloride	94 mg/m3

7 HANDLING AND STORAGE

7.1 Precautions for safe handling Prevent formation of aerosols.

Information about protection against explosions and fires: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Keep receptacle tightly sealed.

Store in dry conditions.

Exposure to sulfur or to high humidity will tarnish solder surface.

7.3 Specific end use(s) No further relevant information available.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Additional information about design of technical systems: No further data; see item 7.

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

7440-31-5 TIN (Sn)

PEL	Long-term value: 2 mg/m ³ metal
REL	Long-term value: 2 mg/m ³
TLV	Long-term value: 2 mg/m ³ metal

(Contd. on page 5)

US

SAFETY DATA SHEET (SDS)

According to 1907/2006/EC, Article 31

Printing Date 11/01/2016

Version number 4

Reviewed on 11/01/2016

Trade name: 245 CORE Sn63Pb37

(Contd. of page 4)

7439-92-1 LEAD (Pb)

PEL	Long-term value: 0.05* mg/m ³ *see 29 CFR 1910.1025
REL	Long-term value: 0.05* mg/m ³ *8-hr TWA ;See PocketGuide App.C
TLV	Long-term value: 0.05* mg/m ³ *and inorganic compounds, as Pb; BEI

Additional information:

PEL = Permissible Exposure Limit (OSHA)

TLV= Threshold Limit Value (ACGIH)

OSHA= Occupational Safety and Health Administration

ACGIH= American Conference of Governmental Industrial Hygienists

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Breathing equipment:

When ventilation is not sufficient to remove fumes from the breathing zone, a safety approved respirator or self-contained breathing apparatus should be worn.

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:



Protective gloves

Material of gloves:

Cloth gloves

Nitrile rubber, NBR

Natural rubber, NR

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Safety glasses



Face Shield with Safety Glasses when refilling.

9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Solid material
Color:	Silver grey
Odor:	Mild

(Contd. on page 6)

US

SAFETY DATA SHEET (SDS)

According to 1907/2006/EC, Article 31

Printing Date 11/01/2016

Version number 4

Reviewed on 11/01/2016

Trade name: 245 CORE Sn63Pb37

(Contd. of page 5)

pH-value: Not determined.

Change in condition
Melting point/Melting range: 183-184 °C (361-363 °F)
Undetermined.
Boiling point/Boiling range: 1740 °C (3164 °F)

Flash point: >93 °C (>199 °F)

Auto igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Density: Not determined.

Solubility in / Miscibility with Water: Not miscible or difficult to mix.

Solvent content:
Organic solvents: 0.1 %
Solids content: 99.9 %

10 STABILITY AND REACTIVITY

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: Strong acids, strong oxidizers.

10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

When heated to soldering temperatures, the solvents are evaporated and rosin may be thermally degraded to liberate aliphatic aldehydes and acids.

11 TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity:

Harmful if swallowed.

LD/LC50 values that are relevant for classification:

7439-92-1 LEAD (Pb)

Oral	LD50	500 mg/kg (ATE)
Inhalative	LC50/4 h	11 mg/l (ATE)

Rosin

Oral	LD50	> 4000 mg/kg (Rat)
Dermal	LD50	>2500 mg/kg (rabbit)

Primary irritant effect:

on the skin: Possible local irritation by contact with flux or fumes.

on the eye: Smoke during soldering can cause eye irritation.

through inhalation:

Flux fumes during soldering may cause irritation and damage of mucous membranes and respiratory system.

(Contd. on page 7)

SAFETY DATA SHEET (SDS)

According to 1907/2006/EC, Article 31

Printing Date 11/01/2016

Version number 4

Reviewed on 11/01/2016

Trade name: 245 CORE Sn63Pb37

(Contd. of page 6)

through ingestion: May be harmful if swallowed.

Sensitization: Based on available data, the classification criteria are not met.

Additional toxicological information:

Carcinogenic categories

IARC (International Agency for Research on Cancer)

7439-92-1 | LEAD (Pb)

2B

NTP (National Toxicology Program)

7439-92-1 | LEAD (Pb)

R

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 ECOLOGICAL INFORMATION

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

Additional ecological information:

General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

The product contains heavy metals. Avoid transfer into the environment. Specific preliminary treatments are necessary

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

13 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Recommendation:

Disposal must be made according to official regulations.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

14 TRANSPORT INFORMATION

14.1 UN-Number

DOT, ADR, ADN, IMDG, IATA

Not applicable

14.2 UN proper shipping name

DOT, ADR, ADN, IMDG, IATA

Not applicable

14.3 Transport hazard class(es)

DOT, ADR, ADN, IMDG, IATA

Class

Not applicable

14.4 Packing group

DOT, IMDG, IATA

Not applicable

Marine pollutant:

No

14.6 Special precautions for user

Not applicable.

14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

Not applicable.

(Contd. on page 8)

US

SAFETY DATA SHEET (SDS)

According to 1907/2006/EC, Article 31

Printing Date 11/01/2016

Version number 4

Reviewed on 11/01/2016

Trade name: 245 CORE Sn63Pb37

UN "Model Regulation":

Not applicable

(Contd. of page 7)

15 REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

USA The following information relates to product regulation specific to the USA.

SARA (Superfund Amendments and Reauthorization Act)

Section 355 (extremely hazardous substances):

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

7439-92-1 | LEAD (Pb)

Chemicals known to cause cancer:

WARNING: This product contains a chemical(s) known to the State of California to cause cancer.

LEAD (Pb)

Chemicals known to cause reproductive toxicity:

WARNING: This product contains a chemical(s) known to the State of California to cause birth defects and/or other reproductive harm.

LEAD (Pb)

Carcinogenic categories

EPA (Environmental Protection Agency)

7439-92-1 | LEAD (Pb)

B2

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

CANADA:

Not classified.

Workplace Hazardous Materials Identification (WHMIS):

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR) and the Safety Data Sheet (SDS) contains all of the information required by the CPR.

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labeled according to the CLP regulation.

Hazard pictograms



GHS07 GHS08

Signal word Danger

Hazard-determining components of labeling:

LEAD (Pb)

Hazard statements

H302 Harmful if swallowed.

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 9)

US

SAFETY DATA SHEET (SDS)

According to 1907/2006/EC, Article 31

Printing Date 11/01/2016

Version number 4

Reviewed on 11/01/2016

Trade name: 245 CORE Sn63Pb37

(Contd. of page 8)

P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P314 Get medical advice/attention if you feel unwell.
P330 Rinse mouth.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 OTHER INFORMATION

The information contained herein is based on data considered accurate and is offered solely for information, consideration and investigation. Kester extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The data on this Material Safety Data Sheet relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and the necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Material Safety Data Sheet as a source for hazard information.

Department issuing Safety Data Sheet (SDS): Product Compliance / EHS Department

Contact: EHS_Kester@kester.com

Date of preparation / last revision 11/01/2016 / 3

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
WHMIS: Workplace Hazardous Materials Information System (Canada)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Acute Tox. 4: Acute toxicity – Category 4
Carc. 2: Carcinogenicity – Category 2
Carc. 2: Carcinogenicity – Category 2
Repr. 1: Reproductive toxicity – Category 1
Repr. 1B: Reproductive toxicity – Category 1B
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

*** Data compared to the previous version altered.**