

## DISPLAY

Screen Size	55"
Panel Technology	IPS
Back Light Type	Direct
Aspect Ratio	16:9
Native Resolution	1920 x 1080
Refresh Rate	60Hz
Brightness (Typ.)	700 nits
Contrast Ratio	1100:1
Dynamic Contrast Ratio	500,000:1
Color gamut	NTSC 72%
Viewing Angle (H x V)	178° x 178°
Color Depth	10bit, 1.07 Billion colors
Response Time (G to G)	8ms
Surface Treatment (Haze)	28%
Lifetime (Typ.)	60,000 Hrs
Operation Hours (Hours/Day)	24/7
Portrait / Landscape	Yes / Yes

## SOUND

Speaker	No
---------	----

---

## CONNECTIVITY

HDMI	Yes (x2), HDCP2.2
------	-------------------

---

DP	Yes, HDCP2.2
----	--------------

---

DVI-D	Yes, HDCP1.4
-------	--------------

---

Audio In	Yes
----------	-----

---

RS232C In	Yes
-----------	-----

---

RJ45(LAN)	Yes
-----------	-----

---

IR In	Yes
-------	-----

---

USB	Yes, USB2.0 Type A
-----	--------------------

---

DP Out	Yes
--------	-----

---

Audio Out	Yes
-----------	-----

---

RS232C OUT	Yes
------------	-----

---

## MECHANICAL

Bezel Color	Black
-------------	-------

---

Bezel Width	0.44mm Even Bezel
-------------	-------------------

---

Weight	40.6 lbs / 18.4 kg
--------	--------------------

---

Packed Weight	52.0 lbs. / 23.6 kg
---------------	---------------------

---

Monitor Dimension (W x H x D)	47.7 x 26.8 x 3.4 in. 1210.51 x 681.22 x 86.5mm
-------------------------------	---

---

<b>Shipping Dimensions (W x H x D)</b>	53.3 x 33.7 x 10.4 in. 1353 x 855 x 263 mm
--	--

---

<b>Handle</b>	Yes
---------------	-----

---

<b>IP Rating</b>	IP5X
------------------	------

---

<b>VESATM Standard Mount Interface</b>	600 x 400
--	-----------

---

## FEATURES

<b>Internal Memory</b>	8GB
------------------------	-----

---

<b>Temperature Sensor</b>	Yes
---------------------------	-----

---

<b>BLU Sensor</b>	Yes
-------------------	-----

---

<b>Acceleration(Gyro) Sensor</b>	Yes
----------------------------------	-----

---

<b>Smart Calibration</b>	Yes
--------------------------	-----

---

<b>Local Key Operation</b>	Yes
----------------------------	-----

---

<b>webOS Signage version</b>	webOS 4.1
------------------------------	-----------

---

<b>Local Contents Scheduling</b>	Yes
----------------------------------	-----

---

<b>Group Manager</b>	Yes
----------------------	-----

---

<b>USB Plug &amp; Play</b>	Yes
----------------------------	-----

---

<b>Fail over</b>	Yes
------------------	-----

---

<b>No Signal Image</b>	Yes
------------------------	-----

---

<b>RS-232C Sync</b>	Yes
---------------------	-----

---

<b>Local Network Sync</b>	Yes
---------------------------	-----

---

Video Tag	Yes (x4)
-----------	----------

---

Play via URL	Yes
--------------	-----

---

Screen Rotation	Yes
-----------------	-----

---

External Input Rotation	Yes
-------------------------	-----

---

Gapless Playback	Yes
------------------	-----

---

Tile Mode Setting	Yes (Max. 15X15)
-------------------	------------------

---

Setting Data Cloning	Yes
----------------------	-----

---

SNMP	Yes
------	-----

---

ISM Method	Yes
------------	-----

---

Auto Set ID	Yes
-------------	-----

---

Status Mailing	Yes
----------------	-----

---

Control Manager	Yes
-----------------	-----

---

Crestron Inside	Yes
-----------------	-----

---

Smart Energy Saving	Yes
---------------------	-----

---

PM mode	Yes
---------	-----

---

Wake on LAN	Yes
-------------	-----

---

Network Ready	Yes
---------------	-----

---

HDMI-CEC	Yes
----------	-----

---

SI Server Setting	Yes
-------------------	-----

---

webRTC	Yes
--------	-----

---

Pro:Idiom	Yes
-----------	-----

W/B Setting by Grey scale	Yes
---------------------------	-----

Scan Inversion	Yes
----------------	-----

## ELECTRICAL

Power Supply	100-240 Vac, 50/60 Hz
--------------	-----------------------

Power Type	Built-In Power
------------	----------------

Typical Power Consumption	210 W
---------------------------	-------

Max Power Consumption	250 W
-----------------------	-------

Typical Heat Dissipation	717 BTU/Hr
--------------------------	------------

Max Heat Dissipation	853 BTU/Hr
----------------------	------------

Smart Enegy Saving	110 W
--------------------	-------

DPM	0.5 W
-----	-------

Power off	0.5 W
-----------	-------

OPS compatible	Yes (Piggyback)
----------------	-----------------

OPS Power built in	No
--------------------	----

Operation Temperature	32°F to 104°F 0°C to 40°C
-----------------------	---------------------------

Operation Humidity	10% to 80%
--------------------	------------

## LG SOFTWARE & SERVICES\*

SuperSign CMS	Yes
---------------	-----

---

<b>SuperSign Contro</b>	Yes
<b>SuperSign Control+</b>	Yes (optional for purchase)
<b>SuperSign White Balance</b>	Yes (optional for purchase)
<b>SuperSign Media Editor</b>	Yes (optional for purchase)
<b>LG ConnectedCare</b>	Yes (optional for purchase)

---

## WARRANTY & OTHER

---

<b>Warranty</b>	3 Year Limited
<b>Regulatory</b>	FCC Class "B" / CE / KC
<b>Environmental</b>	ErP / Energy Star 8.0
<b>Onscreen Display Languages</b>	English, French, German, Spanish, Italian, Korean, Chinese (Original & Simplified), Portuguese (Portugal & Brazil), Swedish, Finnish, Norwegian, Danish, Japanese, Russian, Dutch, Czech, Greek, Turkish, Arabic
<b>Included Accessories</b>	Remote Control (includes 2 batteries), Power Cord, RS232C cable, LAN cable, DP cable, IR Receiver, Guide Bracket, Screws, Manual
<b>Optional Accessories</b>	OPS Kit (KT-OPSF)

---