

## LGWM 2

# SKF High Load, Wide Temperature Bearing Grease

SKF LGWM 2 is a synthetic-mineral oil based grease using the latest complex calcium sulphonate thickener technology. It is suitable for applications subjected to high loads, wet environments and fluctuating temperatures.

- Excellent corrosion protection
- Excellent mechanical stability
- Excellent high load lubricating capacity
- Good false brinelling protection
- Good pumpability down to low temperatures

### Typical applications:

- Wind turbine mains shafts
- Heavy duty off road applications
- Snow exposed applications
- Marine and offshore applications
- Spherical roller thrust bearing applications



## Technical data

Designation	LGWM 2/(pack size)	
DIN 51825 code	KP2G-40	
NLGI consistency class	1-2	
Soap type	Complex calcium sulphonate	
Colour	Yellow	
Base oil type	Synthetic (PAO)/ Mineral	
Operating temperature range	-40 to +110 °C (-40 to +230 °F)	
Dropping point DIN ISO 2176	>300 °C (>570 °F)	
Base oil viscosity		
40 °C, mm <sup>2</sup> /s	80	
100 °C, mm <sup>2</sup> /s	8,6	
Penetration DIN ISO 2137		
60 strokes, 10 <sup>-1</sup> mm	280-310	
100 000 strokes, 10 <sup>-1</sup> mm	+30 max	
Mechanical stability		
Roll stability, 50h at 80 °C, 10 <sup>-1</sup> mm	+50 max.	
Corrosion protection		
Emcor: - standard ISO 11007	0-0	
- water washout test	0-0	
- salt water test (100% seawater)	0-0	
Water resistance		
DIN 51 807/1, 3 hrs at 90 °C	1 max.	
Oil separation		
DIN 51 817, 7 days at 40 °C, static, %	3 max.	
Lubrication ability		
R2F, running test B at 120 °C	Pass at 140 °C (285 °F)	
R2F, Cold chamber test (+20 °C to -30 °C)	Pass	
Copper corrosion		
DIN 51 811, 110 °C	1 max.	
Rolling bearing grease life		
ROF test		
L <sub>50</sub> life at 10 000 r/min., hrs	1 824* at 110 °C	
EP performance		
Wear scar DIN 51350/5, 1 400 N, mm	1,5 max.	
4-ball test, welding load DIN 51350/4, N	4 000	
Fretting corrosion		
ASTM D4170 FAFNIR test at +25 °C, mg	5,2*	
ASTM D4170 FAFNIR test at -20 °C, mg	1,1*	
Available pack sizes	420 ml cartridge 5, 18, 50, 180 kg SKF SYSTEM 24 (LAGD/TLSD), TLMR	

\* Typical value



### SKF lubricants offer major competitive advantages:

- Designed and tested to outperform under real conditions
- Product data include specific test results enabling a better selection
- Strict quality control of every production batch help ensure consistent performance
- Quality control allows SKF to offer a five-year shelf-life\* from the date of production



Production processes and raw materials vastly influence grease properties and performance. It is virtually impossible to select or compare greases based only on their composition. Therefore, performance tests are needed to provide crucial information. In over 100 years, SKF has accrued vast knowledge about the interaction of lubricants, materials and surfaces.



This knowledge has led SKF, in many cases, to set industry standards in bearing lubricant testing. Emcor, ROF, ROF+, V2F, R2F and Bequiet are just some of the multiple tests developed by SKF to assess the performance of lubricants under bearing operating conditions. Many of them are widely used by lubricant manufacturers worldwide.

\* SKF LGFP 2 food grade grease offers a two-year shelf-life from the date of production

© SKF is a registered trademark of the SKF Group.

© SKF Group 2014

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

PUB MP/P8 12056 EN · January 2014

