

## PANEL

<b>Screen Size</b>	32"	<b>Panel Technology</b>	IPS
<b>Native Resolution</b>	1,920 x 1,080 (FHD)	<b>Brightness (nit)</b>	500
<b>Contrast Ratio</b>	1,000:1	<b>Color gamut</b>	NTSC 72%
<b>Viewing Angle (H x V)</b>	178 x 178	<b>Color Depth</b>	8bit, 16.7 Million colors
<b>Response Time</b>	9ms (G to G)	<b>Surface Treatment (Haze)</b>	Haze 12%
<b>Life time</b>	50,000Hrs (Min.)	<b>Operation Hours (Hours / Day)</b>	24 / 7
<b>Portrait / Landscape</b>	Yes / Yes		

## CONNECTIVITY

<b>Input</b>	Digital (HDMI(2), HDCP 1.4), RS232C IN, RJ45(LAN), IR IN, USB2.0 Type A(1)	<b>Output</b>	Audio Out, USB2.0 Type B(1)
--------------	--	---------------	-----------------------------

## MECHANICAL SPECIFICATION

<b>Bezel Color</b>	Black	<b>Bezel Width</b>	11.3/11.3/11.3/13.2 mm
<b>Weight (Head)</b>	5.8 kg	<b>Monitor Dimensions (W × H × D)</b>	723.0 x 419.4 x 39.1 mm
<b>Carton Dimensions (W × H × D)</b>	812 x 510 x 142 mm	<b>VESA™ Standard Mount Interface</b>	200 x 200

## KEY FEATURE(HARDWARE)

<b>Internal Memory</b>	8GB (System 5GB + Available 2.48GB)	<b>Temperature Sensor</b>	Yes
<b>Acceleration(Gyro) Sensor</b>	Yes		

## KEY FEATURE(SOFTWARE)

<b>webOS ver.</b>	webOS 6.0	<b>Embedded CMS</b>	Local Contents Scheduling, Group Manager
<b>USB Plug &amp; Play</b>	Yes	<b>Fail over</b>	Yes

<b>Background Image</b>	Booting Logo Image, No Signal Image	<b>Video Tag</b>	Yes
<b>Play via URL</b>	Yes	<b>Screen Rotation</b>	Yes
<b>Gapless Playback</b>	Yes	<b>Setting Data Cloning</b>	Yes
<b>SNMP</b>	Yes	<b>ISM Method</b>	Yes
<b>Status Mailing</b>	Yes	<b>Control Manager</b>	Yes
<b>Cisco Certification</b>	Yes	<b>Crestron Connected</b>	Yes
<b>Power</b>	Smart Energy Saving, PM mode, Wake on LAN, Network Ready	<b>HDMI-CEC</b>	Yes
<b>SI Server Setting</b>	Yes	<b>webRTC</b>	Yes
<b>Pro:Idiom</b>	Yes		

## ENVIRONMENT CONDITIONS

<b>Operation Temperature</b>	0°C to 40°C	<b>Operation Humidity</b>	10% to 80%
------------------------------	-------------	---------------------------	------------

## POWER

<b>Power Supply</b>	AC 100-240V~, 50/60Hz	<b>Power Type</b>	Built-In Power
---------------------	-----------------------	-------------------	----------------

---

## POWER CONSUMPTION

<b>Typ.</b>	48 W	<b>Max.</b>	65 W
<b>BTU (British Thermal Unit)</b>	1 64 BTU/Hr(Typ.), 222 BTU/Hr(Max.)	<b>Smart Energy Saving (70%)</b>	34 W
<b>DPM</b>	0.5 W↓	<b>Power off</b>	0.5 W↓

---

## CERTIFICATION

<b>Safety</b>	CB / NRTL	<b>EMC</b>	FCC Class "A" / CE / KC
<b>ErP / Energy Star</b>	N/A / Yes		

---

## SOFTWARE COMPATIBILITY

<b>SuperSign CMS</b>	Yes	<b>SuperSign Control+</b>	Yes
<b>SuperSign Cloud</b>	Yes	<b>Mobile CMS</b>	Yes
<b>Connected Care</b>	Yes		

---

## ACCESSORY

### Basic

Power Cord 1.55 M\*1, USB Cable (Type A-Type B) 1.8 M\*1, User Manual, QSG, Remote Controller(include battery 2ea), RS232C Gender, IR Receiver

---

## TOUCH

**Available object size for touch**

Ø6mm ↑

**Response Time (Based on 'Paint' app on Windows 10 PC)**

90ms ↓

---

**Accuracy**

3.5 mm

**Interface**

USB 2.0

---

**Operating System Support**

Win 10 / 11, Android

**Multi touch point**

Max. 10 Points

---