

All Spec

PANEL

Screen Size

55" Class (54.64" measured diagonally)

Resolution

1,920 x 1,080 (FHD)

Brightness

2,400 cd/m² (Min), 3,000 cd/m² (Typ)

CONNECTIVITY

Input

HDMI(2), DP, DVI-D, Audio, USB, IR Receiver,
Pixel Sensor

Output

DP, External Speaker Out (L/R)

External Control

RS232C (In/Out), RJ45

PHYSICAL SPECIFICATION

Bezel Width

9.9mm (L/R),12mm (T/B)

Monitor Dimension (W x H x D)

1,235.4 x 709.4 x 106 mm

Weight (Head)

27.0kg

ENVIRONMENT CONDITIONS

Operation Temperature

0°C to 50°C (w/o Direct Sunlight) / 0°C to
40°C (Direct Sunlight)

Operation Humidity

10 % to 80 %

POWER

Power Supply

100-240V~, 50/60Hz

Power Type

Built-In Power

POWER CONSUMPTION

Typ./Max	Smart Energy Saving
230 W / 310 W	100 W

STANDARD(CERTIFICATION)

Safety	EMC
RU / CB scheme	FCC Class "A" / CE / KCC

SOFTWARE COMPATIBILITY

webOS	SuperSign-w lite
webOS 1.0	Yes
SuperSign-c	
Yes	

ACCESSORY

Basic	Optional
Remote Controller (2 batteries included), Power Cord, IR extension cable/PCB, HDMI Cable, Manual, IR BRKT (Only in 75")	KT-SP0, AN-WF500 *Stand is not available