

PANEL

Screen Size	86"
Panel Technology	ADS
Back Light Type	Direct
Aspect Ratio	16:9
Native Resolution	3840x2160 (UHD)
Refresh Rate	120Hz
Brightness	330nit (Typ.)
Contrast Ratio	1,400:1
Dynamic CR	1,000,000:1
Color gamut	DCI 80%
Viewing Angle(H x V)	178x178
Color Depth	Advanced 8bit, 1.07 Billion colors
Response Time	8ms (G to G)
Surface Treatment(Haze)	1%
Life time	30,000Hrs (Min)
Operation Hours (Hours/Day)	16/7
Portrait / Landscape	Yes / Yes

CONNECTIVITY

Input	HDMI (3, HDCP 2.2/1.4), RS-232C In (4 Pin Phone-jack), RJ45 (LAN), USB 2.0 (2, Type A)
Output	Audio Out, RS-232C Out (4 Pin Phone-jack)

MECHANICAL SPECIFICATION

Bezel Color	Ashed Blue
Bezel Width	Off : 6.9/6.9/6.9/18.4 On : 15.9/15.9/15.9/19.9
Weight(Head)	45.2
Packed Weight	57.7
Monitor Dimension(W x H x D)	1927 x 1104 x 59.9
Carton Dimensions(W x H x D) (Box outer size)	2115 x 1215 x 228
VESA™ Standard Mount Interface	600 x 400

KEY FEATURE

HW	Internal Memory (eMMC) 1 6 GB, Built-in Wi-Fi, Sensor (Temperature Sensor, Auto Brightness Sensor), Local Key Operation (Power On/Off Only)
SW	webOS 6.0, Embedded CMS (Local Contents Scheduling, Group Manager), USB Plug & Play, Fail Over, Background Image (Booting Logo Image, No Signal Image), Sync Mode (RS-232C Sync, Local Network Sync), Screen Share, Video Tag (4, Max One HDMI Input), Play via URL, Rotation (Screen Rotation, External Input Rotation), Gapless Playback, Tile Mode Setting, Setting Data Cloning, SNMP, ISM Method, Auto Set ID, Status Mailing, Control Manager, 3rd Party Compatibility (Cisco Certi. (TBD, ~ ` 23.7)), Crestron Inside, Power (Smart Energy Saving, PM Mode, Wake on LAN, Network Ready), Beacon, HDMI-CEC1), SI Sever Setting, webRTC, Pro:Idiom

ENVIRONMENT CONDITIONS

Operation Temperature	0 °C to 40 °C (Portrait Scene : 0 °C to 35 °C)
Operation Humidity	10 % to 80 %

POWER

Power Supply	AC 100-240V~, 50/60Hz
Power Type	Built-In Power

POWER CONSUMPTION

Typ.	TBD W
Max.	TBD W
BTU (British Thermal Unit)	751 BTU/Hr(Typ.), 1024 BTU/Hr(Max.)
Smart Enegy Saving(70%)	TBD W
DPM	0.5W
Power off	0.5W

SOUND

Speaker	Yes
---------	-----

CERTIFICATION

Safety	CB
EMC	FCC Class "A" / CE

ErP / Energy Star	Yes (OldErP for Jordan) / No
ePEAT(US only)	Yes

SOFTWARE COMPATIBILITY

SuperSign CMS	Yes
SuperSign Control / Control+	Yes / Yes
SuperSign WB	Yes
LG ConnectedCare	Yes
Signage 365 Care	Yes

LANGUAGE

OSD	English, French, German, Spanish, Italian, Korean , Chinese(Simplified), Chinese(Original), Portugues(Brazil), Swedish, Finnish, Norwegian, Danish, Russian, Japanese, Portugues(Europe), Dutch, Czech, Greek, Turkiye, Arabic, polski
-----	---

ACCESSORY

Basic	Remote Controller(include battery 2ea), Power Cord, Regulation Book, Phone to D-Sub9 Gender, Cable Holder
-------	--