

SYSTEM

Processor	Intel® Celeron J4105 (Quad Core 1.5GHz, up to 2.5GHz burst), Fanless
Graphics	Integrated Graphics
OS	Non OS
Memory	4GB DDR4, 2666MHz, 2 SODIMM slots
Storage	16GB eMMC
Display Support	Up to 3 displays : 2560x1600@60Hz (via 1st DisplayPort 1.2 out) 3840x2160@60Hz (via 2nd DisplayPort 1.2 out) 3840x2160@60Hz (via USB Type-C)
Expansion Slot	M.2 Slots x 2 (Slot 1 : N/A, Slot 2 : WiFi + Bluetooth card) * Note: Slot 1 should be capable of supporting SATA SO-DIMM x 2 (Slot 1 : 4GB DDR4, Slot 2 : N/A)
TPM (Trust Platform Module)	Hardware TPM 2.0

CONNECTIVITY

DisplayPort	YES(out 2ea)
DP Version	1.2
DP (Max. Resolution at Hz)	3840X2160 60Hz
Fiber Ready	SFP Module support ready for Fiber NIC network connectivity (mutually exclusive with RJ45)
Thunderbolt (Power Delivery)	N/A

Thunderbolt(USB-C Compatibility)

N/A

USB

2 x USB 2.0 Type-A
4 x USB 3.1 gen1 (5Gb/s) Type-A
1 x USB 3.1 gen1 (5Gb/s) Type-C with DP out

USB-C

YES(out 1 ea)

USB-C (DP Version)

1.2

USB-C (Power Delivery)

N/A

[Location]

Horizontal

SOUND

Speaker

YES

Speaker_Channel

1ch

Speaker_Output (unit)

1.2W

Speaker_Direction

Front Firing

POWER

AC Input

100-240Vac, 50/60Hz

DC Output

19V 3.42A

Power Consumption (DC Off)

1.0W

Power Consumption (Sleep Mode)

1.2W

Long Idle (Display Off)

6.0W

Short Idle (Display On)

6.0W

TEC (kWh)	27.0 kWh
Type	External Power(Adapter)

MECHANICAL

Color (Front Cabinet)	Matt Black
Color (Middle Cabinet)	Matt Black
Color (Back Cover)	Matt Black
Wall Mountable	100 x 100 mm

DIMENSIONS & WEIGHT

Dimension in Shipping (W x H x D)	260 x 164 x 101
Dimension without Stand (W x H x D)	199 x 137 x 35
Pallet Stuffing (20ft/40ft/40ft HC)	3,000/6,300/7,560
Weight in Shipping	1.685
Weight with Stand	0.82
Weight without Stand	0.8

STANDARD

CB	YES
CE	YES
FCC-B	YES
KC (for Rep. of Korea)	YES

ROHS, REACH	YES
TUV-Ergo	YES
TUV-GS	YES
TUV-Type	YES
UL(cUL)	YES
VESA wall mount standard	YES

ACCESSORY

Adapter	YES
Adapter (Color)	Black
Power Cord	YES
Power Cord (Color/Length)	Black / 2.0m
External Antenna	YES
VESA Bracket	Horizontal/Vertical feet and VESA/wall mounting

NETWORK

LAN	1 x RJ45 : 10/100/1000 Base-T Gigabit Ethernet (Wake on LAN)
Wi-Fi	Dual Band 802.11 a/b/g/n/ac 2x2 (BT 5.0 Combo, Internal Antenna)
Bluetooth	BT5.0

CONTROL KEY

Key Location	Front
Key Number (Power Key Included)	1
Key Type	Tact
LED Color(On mode)	White (PC Power / HDD)
LED Color(Power save mode)	Blinking (PC)
LED Color(Standby)	OFF(PC)

BOX COSMETIC

Box Printing Type	Flexo
Packing Material	A-Flute
Stacking Type	Vertical

ETC

Humidity Range	Operating : 20%~80%, Storage : 10%~90%
Temperature Range	Operating : 10°C ~ 40°C, Storage : -20°C ~ 60°C

COMPLIANCE INFORMATION

[UK DoC\(CL600N-6N\)](#)

[WEB INFO\(CL600N-6N\)](#)

[MORE COMPLIANCE INFORMATION](#)