

LUX80

Specification

Detail

Product Name	LUX80
Screen Size	80 in. (diagonal)
Orientation	Landscape/Portrait
Recommended Usage	24/7
Aspect Ratio	16:9
Brightness (typ)	700 nits
Backlight	Edge-Lit LED
Contrast Ratio (typ)	5000:1
Response Time (typ)	4 ms
Frame Rate	120Hz
Viewing Angle (typ)	176H,V
Native Resolution	Full HD 1920 x 1080 (1080p)
Display Color	>1 billion colors. Full 10 bit data path
Surface Treatment	None
Control and Monitoring	RS232/LAN with SNMP
Line Voltage	100-240V; 50/60Hz
Power Consumption (typ)	350W
External Connections	DisplayPort, HDMI, VGA
Operating Temperature	0°F to + 104°F (0°C to + 40°C)
Storage and Transport Temperature	-4°F to + 140°F (-20°C to + 60°C)
Humidity	20 to 90% RH
Cabinet Dimensions (W x H x D)	72.2 in. x 41.7 in. x 2.8 in. (1834.9 mm x 1060.0 mm x 71.0 mm)
Bezel Width	1.3" (32 mm)
Weight	174 lbs (79 kg)
Weight (Shipping)	243 lbs (110 kg)
Touch Technology	N/A
OS Compatibility	N/A
Bezel color	Black
Mounting	Planar Profile Mounting System or VESA: 600 x 800 mm; 4 holes
Approvals	FCC Class A, EN60950, CE
Warranty	3 years Advance Exchange

Other Features

Integrated media player storage with AC power, redundant power supply, compatible with Planar Profile mounting system or UltraLux free-standing pedestals

UPC

8 10689 07183 9