

## LX55HD-L

### Specification

### Detail

Planar Part Number	997-7115
Technology	Commercial-grade direct view LCD
Diagonal Size	55 inches
Aspect Ratio	16:9
Native Resolution Panels	1920 x 1080
Bezel Width	5.5 mm
Brightness (typ)	450 nits
Response Time (typ)	8 ms
Contrast ratio (full field)	3500:1
Full viewing angle	178°
Backlight life (1/2 brightness)	50,000 Hrs
Mounted depth	3.6" wall to front of screen
Acoustic noise	Fan-less operation
Heat load	480 BTU per hour at 500 nit
Operating temperature range	5 - 40 Degrees C
Operating humidity range	20-90% RH non-condensing
Backlight control	Individual and wall control
Backlight sensing and reporting	At display level
Display module position sensing	Auto-sensing integrated
Power Consumption	179 watts (typical)
Power supply voltage	100-240 Volts AC, 50-60Hz auto switching
Power status	Diagnostics LEDs, health monitoring and alerts
Safety regulations	Complies with EN60950, FCC Class A, CISPR22/85, CE, EU RoHS
Data Inputs	4 Single Link DVI Inputs, 1 Dual Link DVI Inputs
Control	IR Remote, RS232, Ethernet (optional)
Per Panel Dimensions (Including Mount)	47.84" x 27.01" x 3.6"
Per Panel Weight (Including Mount)	59 lbs
Wall Dimensions (WxHxD)	N/A
Wall Dimensions (WxHxD) including stand	N/A
Shipping weight	150 lbs
In the Box	N/A
UPC	8 10689 07115 0