LITETOUCH









- Cost effective way to replace aging projector systems with no maintenance, bulb changes, calibration, or alignment needed.
- Multiple mounting solutions available (mobile cart, wall mount.)
- Can be easily upgraded by adding PC module.
- 4K Ultra High Definition interactive touchscreen with 20 points of touch, industry-leading brightness and clarity, and a built-in Android PC.
- Displays your computer screen wirelessly or via 3 HDMI inputs or VGA input with audio.
- Includes LitePen annotation and screen recording software.
- Industry-leading 5 year limited warranty included.
- Anti-Glare Glass chemically etched for a smooth, glare free surface.
- Professional installation available.
- Contact us for pricing and quantity discounts!



Phone: 606-547-8363
Email: sales@LTNTechnologies.com
www.LTNTechnologies.com

SPECIFICATIONS

	55"	65"	75"	86"
Resolution	3840 x 2160 (4K)			
Refresh Rate	60hz	60hz	60hz	60hz
Brightness	450cd/m2	450cd/m2	450cd/m2	400cd/m2
Light Source	LED	LED	LED	LED
Estimated Minimum Lifespan	50,000 hours	50,000 hours	50,000 hours	50,0000 hours
Input Connections	HDMix3, DisplayPort, VGA, 3.5mm PC Audio, RCA Component, RCA Composite, Microphone Input, RS232	HDMlx3, DisplayPort, VGA, 3.5mm PC Audio, RCA Component, RCA Composite, Microphone Input, RS232	HDMb/3, DisplayPort, VGA, 3.5mm PC Audio, RCA Component, RCA Composite, Microphone Input, RS232	HDMIx3, DisplayPort, VGA, 3.5mm PC Audio, RCA Component, RCA Composite, Microphone Input, RS232
Output Connections	HDMI, RCA Composite, SPDIF	HDMI, RCA Composite, SPDIF	HDMI, RCA Composite, SPDIF	HDMI, RCA Composite, SPDIF
Networking	Ethernet x2	Ethernet x2	Ethernet x2	Ethernet x2
PC / Android USB	2 x USB-A	2 x USB-A	2 x USB-A	2×USB-A
Viewing Angle	178 degree(H) / 178 degree(V)			
Android CPU	ARM A73+A53 Quad Core - 1.5 GHz			
GPU	Mali-G51	Mali-G51	Mali-G51	Mali-G51
Memory (RAM)	3 GB DDR4	3 GB DDR4	3 GB DDR4	3 GB DDR4
Internal Storage Capacity	16 GB	16 GB	16 GB	16 GB
System Version	Android 8.0	Android 8.0	Android 8.0	Android 8.0
Android Connections	2 x USB 3.0			
Max Watt	< 200 W	< 200W	< 200W	< 200W
Standby Power Consumption	< 0.5 W	< 0.5W	< 0.5 W	< 0.5W
AC Input	120 Volts	120 Volts	120 Volts	120 Volts
Net Weight	68 lbs	96 lbs	130 lbs	170 lbs
Gross Weight	103 lbs	116 lbs	163 lbs	207 lbs
Unit Size (HxWxD)	31 1/16" x 51 1/8" x 1 13/16"	35 5/8" x 59 1/4" x 3 1/2"	40 3/4" x 68 3/8" x 4 1/8"	46 1/2" x 78 3/8" x 4 3/8"
Color	Black	Black	Black	Black
Vesa Mounting	4 - M6 screw hole 400mm x 400mm	4 - M8 screw hole 600mm x 400mm	4 - M8 screw hole 600mm x 400mm	4 - M8 screw hole 700mm x 400mm
Speakers	2 x 16 Watts			
Touchscreen Type	Active IR Touch (20 Point)			
Glass	4mm Tempered Anti-Glare Glass	4mm Tempered Anti-Glare Glass	4mm Tempered Anti-Glare Glass	4mm Tempered Anti-Glare Glass
Touch Connection	2 x USB-B	2 x USB-B	2 x USB-B	2 x USB-B
Supported Operating Systems	Windows 7/Windows 8/Windows 8.1/Windows 10/Linux/Mac OS X/ Android/ Chrome OS/IOS	Windows 7/Windows 8/Windows 8.1/Windows 10/Linux/Mac OS X/ Android/ Chrome OS/ iOS	Windows 7/Windows 8/Windows 8.1/Windows 10/Linux/Mac OS X/ Android/ Chrome OS/ iOS	Windows 7/Windows 8/Windows 8.1/Windows 10/Linux/Mac OS X/ Android/ Chrome OS/iOS

Previous page New page New page Text Enser Whiteboard Record Webcam Settings Save Screenshot Pen Highlighter Shapes Cursor mode Glear Crop Page number



ADDITIONAL ACCESSORIES AVAILABLE

LITEMICTM VOICE AMPLIFICATION



Wireless Microphone System with 100 Watt Speakers



Mobile Cart with Shelf, Basket and A-Outlet Plug Strip

WALL MOUNT M. WALL MOUN



Tilting Wall Mount with Post-Installation Leveling



QUALITY WITHOUT COMPROMISE!