

Lumens DC132U document camera is a Full HD/2K professional-quality visualizer which produces bright images and vivid colors. It supports high-resolution capture (QXGA, 1080 HD, and SXGA) with image and video recording up to 30 frames per second. Our no-joint, highly flexible gooseneck enables 360° viewing angles and object viewing from just 4 cm for extreme close-ups. Use the included Ladibug software for advanced image control and connect to remote guests using your favorite conferencing platforms, such as Zoom, Meet, Skype, or Teams. The stylish light weight design makes it easy to carry the DC132U anywhere for creative presentations.



Key Features

- 1080 HD / 2048 QXGA resolution
- USB plug & play
- 16x total zoom (via software)
- Shooting area (18.8" x 14.1") larger than A3
- Macro shooting from 4cm
- 5-year warranty*



2-in-1 Camera Solution

Twist the gooseneck to any angle to view a document, face the presenter or angle towards the class for a live video conference.



Excellent Image Quality

DC132U produces professional-quality images with vivid colors. It outputs 1080p or even 2K video with image and video recording up-to 30 frames per second. The DC132U is ideal for use in education and training.



One-touch Optimization (Auto-Tune)

At the touch of a button, the camera quickly achieves accurate focus, color balance and image exposure.



Imaging Flexibility

The camera can capture documents and objects larger than A3. Adjust the position of the camera for close-up or wide-angle imaging. Zoom into the image using the provided Ladibug software.



Macro Close-Up

Take extreme close-ups (4cm minimum distance) and capture detailed images of small objects such as insects.

Applications



K-12 Education







Corporate

Product Specifications

| | Camera | | Audio |
|------------------------|--|----------------------|---|
| Sensor | 1/3" 3M CMOS | Built-in Microphone | Yes |
| Total Pixels | 3.3MP | Features | |
| Total Zoom | 16x | | |
| Digital Zoom | 16x (via Software) | Auto Tune | Yes, One Button for Optimization |
| Mechanical Zoom | 8x |] | |
| Output Resolution | 2048x1536, 1600x1200,1920x1080, 1280x720, 1024x768, 800x600, 640x480 Video / Audio Recording | Yes (via Software) | |
| | | Image Mode | Photo / Text |
| Frame Rate | | Freeze | Yes |
| Close-up | 1080p / 720p 30fps 4 cm | Mask / Spotlight | Yes (via Software) |
| Shooting Area Max. | 480x360 mm (18.8" x 14.1") | Image Capture | Single or Continuous Capturing (via Software) |
| Sharpness | MTF 1100 Line | Ladibug™ Software | Support Windows 11, 10, 7 |
| Focus Mode | Auto / Manual | | Mac OS X, Chrome OS |
| Image Rotation | 0° / 180° / Flip / Mirror | General | |
| Lamp | LED Lamp on Camera Head | Anti-Theft | Kensington Anti-Theft Lock Device |
| Arm | Joint-Free Gooseneck | VESA Mount | Yes, 75mm x 75mm |
| Input & Output | | | , |
| Power Supplied | USB Bus Power | Included Accessories | USB 2.0 cable |
| Output | USB 2.0 | Power Consumption | 2.25W (Max.) |
| Control | USB | | Folded : 106 x 280 x 136 mm |
| USB | | Dimensions: (WxHxD) | (4.2" x 11" x 5.4") |
| USB Image Transmission | USB 2.0 (480 Mbps) | | Open : 106 x 380 x 350 mm (4.2" x 15" x 13.8") |
| Driver | UVC / UAC | | |
| USB Video Format | MJPEG / YUV | Weight | 2.65 lbs (1.2 Kg) |

I/O Connections





Lumens Integration, Inc. 4116 Clipper Court Fremont, CA, 94538 Phone: +1-866-600-0988 Fax: +1-510-252-1389 Lumens Europe De Nayerstraat 17 9470 Denderleeuw Belgium Phone : +32-473-58-38-95 Fax : +32-2-452-76-00



Lumens is the registered trademark of Lumens Digital Optics Inc. Changes in specification or design may be done without notification. *The warranty policy may be different depending on the sales region, please contact your local salesperson.