

## LUX70 Touch

### Specification

### Detail

Product Name	LUX70 Touch
Screen Size	70 in. (diagonal)
Orientation	Landscape/Portrait
Recommended Usage	24/7
Aspect Ratio	16:9
Brightness (typ)	700 nits
Backlight	Edge-Lit LED
Contrast Ratio (typ)	5000:1
Response Time (typ)	4 ms
Frame Rate	120Hz
Viewing Angle (typ)	176H,V
Native Resolution	Full HD 1920 x 1080 (1080p)
Display Color	>1 billion colors. Full 10 bit data path
Surface Treatment	Anti-Reflective 3mm - ERO™ Optically Bonded Vandal Glass Protection
Control and Monitoring	RS232/LAN with SNMP
Line Voltage	100-240V; 50/60Hz
Power Consumption (typ)	300W
External Connections	DisplayPort, HDMI, VGA
Operating Temperature	0-40°C (32 -104°F)
Storage and Transport Temperature	-20-60°C (-4-140°F)
Humidity	20 to 90% RH
Cabinet Dimensions (W x H x D)	62.5" x 36.4" x 3.4" (1587.5mm x 925.7mm x 85.4mm)
Bezel Width	1.1" (27.6mm)
Weight	179 lbs (81 kg)
Weight (Shipping)	219 lbs (99 kg)
Touch Technology	IR 6 point touch
OS Compatibility	Windows 7, Vista, XP, Mac OSX and Linux
Bezel color	Black or white
Mounting	Planar Profile Mounting System or VESA: 400 x 400 mm; 4 holes
Approvals	FCC Class A, EN60950, CE
Warranty	3 years Advance Exchange

Other Features

Integrated media player storage with AC power, redundant power supply, compatible with Planar Profile mounting system or UltraLux free-standing pedestals

UPC

8 10689 06797 9



205 Westwood Ave, Long Branch, NJ 07740  
Phone: 866-94 BOARDS (26273) / (732)-222-1511  
Fax: (732)-222-7088 | E-mail: [sales@touchboards.com](mailto:sales@touchboards.com)