

LUX80 Touch

Specification

Detail

| | |
|-----------------------------------|---|
| Product Name | LUX80 Touch |
| Screen Size | 80 in. (diagonal) |
| Orientation | Landscape/Portrait |
| Recommended Usage | 24/7 |
| Aspect Ratio | 16:9 |
| Brightness (typ) | 700 nits |
| Backlight | Edge-Lit LED |
| Contrast Ratio (typ) | 5000:1 |
| Response Time (typ) | 4 ms |
| Frame Rate | 120Hz |
| Viewing Angle (typ) | 176H,V |
| Native Resolution | Full HD 1920 x 1080 (1080p) |
| Display Color | >1 billion colors. Full 10 bit data path |
| Surface Treatment | Anti-Reflective 3mm - ERO™ Optically Bonded Vandal Glass Protection |
| Control and Monitoring | RS232/LAN with SNMP |
| Line Voltage | 100-240V; 50/60Hz |
| Power Consumption (typ) | 350W |
| External Connections | DisplayPort, HDMI, VGA |
| Operating Temperature | 0°F to + 104°F (0°C to + 40°C) |
| Storage and Transport Temperature | -4°F to + 140°F (-20°C to + 60°C) |
| Humidity | 20 to 90% RH |
| Cabinet Dimensions (W x H x D) | 73.5" x 43.1" x 3.4" (1867.8mm x 1095.8mm x 85.4mm) |
| Bezel Width | 1.9" (48mm) |
| Weight | 243 lbs (110 kg) |
| Weight (Shipping) | 288 lbs (131 kg) |
| Touch Technology | IR 6 point touch |
| OS Compatibility | Windows 7, Vista, XP, Mac OSX and Linux |
| Bezel color | Black or white |
| Mounting | Planar Profile Mounting System or VESA: 600 x 800 mm; 4 holes |
| Approvals | FCC Class A, EN60950, CE |
| Warranty | 3 years Advance Exchange |

Other Features

Integrated media player storage with AC power, redundant power supply, compatible with Planar Profile mounting system or UltraLux free-standing pedestals

UPC

8 10689 06801 3