

824-W

# Safety Data Sheet

## Section 1: Identification

### Product Identifier and Other Means of Identification

**Product Name:** 824-W**Other Means of Identification:** Isopropyl Alcohol Wipe**Related Part #** 824-WX25, 824-WX50, 824-WX500

### Recommended Use and Restriction on Use

**Use:** Cleaning wipes**Uses Advised Against:** Industrial Use Only. Not for use on monitor screens or glass with anti-glare coatings

### Details of Manufacturer or Importer

**Manufacturer**MG Chemicals  
1210 Corporate Drive  
Burlington, Ontario L7L 5R6  
CANADAMG Chemicals (Head Office)  
9347-193 Street  
Surrey, British Columbia V4N 4E7  
CANADA**TEL** +1-800-340-0772**FAX** +1-800-340-0773**E-MAIL** [support@mgchemicals.com](mailto:support@mgchemicals.com)**WEB** [www.mgchemicals.com](http://www.mgchemicals.com)**TEL** +1-905-331-1396**FAX** +1-905-331-2682**E-MAIL** [info@mgchemicals.com](mailto:info@mgchemicals.com)**E-MAIL** (Competent Person): [sds@mgchemicals.com](mailto:sds@mgchemicals.com)

### Emergency Phone Number

**For hazardous material incidents ONLY** (leaks, spills, fires, exposures or accidents)USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**

(Service access code: 335388)

**For emergencies involving the transport of dangerous goods;** 24/7 serviceCANADA—Call CANUTEC collect at **+1-613-996-6666** or **\*666** on cellular phones

## 824-W

### Section 2: Hazard(s) Identification



#### Classification of Hazardous Chemical

##### GHS Categories

Criteria	Category	Signal Word	Pictograms
Flammable Liquid	2	Danger	Flame
Eye irritation	2A	Warning	Exclamation
Specific Target Organ Toxicity    Single Exposure	3	Warning	Exclamation

*Note:* The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity). Severity categories rankings do not allow comparisons between classes.

#### Label Elements

<b>Signal Word</b>	<b>DANGER</b>
<b>Pictograms</b>	<b>Hazard Statements</b>
	H225: Highly flammable liquid and vapor
	H319: Causes serious eye irritation H336: May cause drowsiness or dizziness
<b>Prevention</b>	<b>Precautionary Statements</b>
P210	Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No Smoking.
P261	Avoid breathing vapors or mist.
P271	Use only outdoors or in well-ventilated area.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves and eye protection.

*Section continued on the next page*

**824-W**
*Continued ...*

<b>Response</b>	<b>Precautionary Statements</b>
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
P304 + P340, P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor if you feel unwell.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
<b>Storage</b>	<b>Precautionary Statements</b>
P403 + P235	Store in well-ventilated place. Keep cool.
P405	Store locked up.
<b>Disposal</b>	<b>Precautionary Statements</b>
P501	Dispose of contents in accordance to local, regional, national, and international regulations.

**Hazards Not Otherwise Classified**

<b>Other Criteria</b>	<b>Hazard Statements/Precautionary Statement</b>	<b>Signal Word</b>	<b>Pictograms</b>
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

**Section 3: Composition/Information on Ingredients**

<b>CAS #</b>	<b>Chemical Name</b>	<b>%(weight)</b>
67-63-0	propan-2-ol <sup>a)</sup>	99.7%

a) Commonly known as isopropyl alcohol (IPA)

**824-W****Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
<b>IF IN EYES</b>	P305 + P351 + P338, P337 + P313
<b>Immediate Symptoms</b>	<i>redness, irritation, tearing, pain</i>
<b>Response</b>	Rinse cautiously with water for 20 minutes or more. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
<b>IF INHALED</b>	P304 + P340, P312
<b>Immediate Symptoms</b>	<i>cough, dizziness, drowsiness, headaches, weakness</i>
<b>Response</b>	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor if you feel unwell.
<b>IF ON SKIN (or hair)</b>	P303 + P361 + P353
<b>Immediate Symptoms</b>	<i>Low toxicity: redness, dry skin, mild irritation</i>
<b>Response</b>	Take off immediately all contaminated clothing. Rinse skin with water.
<b>IF SWALLOWED</b>	P301 + P330, P331
<b>Immediate Symptoms</b>	<i>Low toxicity: nausea, dizziness, weakness, headaches</i>
<b>Response</b>	Rinse mouth. Do NOT induce vomiting.

**Section 5: Fire-Fighting Measures**

<b>Response</b>	In case of fire: Use dry chemical, carbon dioxide, water fog, or chemical foam to extinguish. Use water spray to cool containers.
<b>Specific Hazards</b>	Vapors may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.
<b>Combustion Products</b>	Produces carbon oxides (CO, CO <sub>2</sub> )
<b>Fire-Fighter</b>	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

**824-W****Section 6: Accidental Release Measures**

<b>Personal Protection</b>	See personal protection equipment in Section 8.
<b>Precautions for Response</b>	Remove or keep away all sources of ignition or extreme heat. Avoid breathing vapors.
<b>Environmental Precautions</b>	Not applicable
<b>Containment</b>	Not applicable
<b>Cleaning</b>	Collect wipes in a sealable, solvent-resistant container.
<b>Disposal Methods</b>	Dispose of spill waste according to Section 13.

**Section 7: Handling and Storage**

<b>Prevention</b>	Keep out of reach of children.  Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No Smoking.  Avoid breathing vapors or mist. Use only outdoors or in a well-ventilated area.
<b>Handling</b>	Wear protective gloves and eye protection.  Wash hands thoroughly after handling.
<b>Storage</b>	Store in a well-ventilated area. Keep cool.

**824-W**
**Section 8: Exposure Controls/Personal Protection**
**Substances with Occupational Exposure Limit Values**

<b>Chemical Name</b>	<b>Country</b>	<b>Long Term Exposure Limits (PEL)</b>	<b>Short Term Exposure Limits (STEL)</b>
propan-2-ol	ACGIH	200 ppm	400 ppm
	U.S.A. OSHA PEL	400 ppm	Not established
	Canada AB	200 ppm	400 ppm
	Canada BC	200 ppm	400 ppm
	Canada ON	200 ppm	400 ppm
	Canada QC	400 ppm	500 ppm

*Note:* The ACGIH<sup>1</sup>, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS database<sup>2</sup> and from suppliers' SDS were also consulted. Short term exposure limits (STEL) are usually for 15 min and long term permissible exposure limits (PEL) for 8 h.

**Engineering Controls**

**Ventilation** Keep airborne concentrations below exposure limits.

**Personal Protective Equipment**

**Eye protection** Wear appropriate protective eyeglasses or chemical safety goggles.

**RECOMMENDATION:** Use safety glasses with lateral protection (side shields).

**Skin Protection** For likely contacts, use of protective butyl rubber, nitrile, neoprene, polyethylene gloves or other chemically resistant gloves.

For incidental contacts, use disposable nitrile or neoprene gloves, or other chemically resistant gloves.

Do NOT use latex rubber, polyvinyl alcohol (PVA) or PVC gloves.

*Section continued on the next page*

## 824-W

### Respiratory Protection

For over-exposures up to 10 x OEL of vapors or mist, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

### General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

### Section 9: Physical and Chemical Properties

<b>Physical State</b>	Liquid, in solid mixture	<b>Lower Flammability Limit</b>	2%
<b>Appearance</b>	Colorless	<b>Upper Flammability Limit</b>	12%
<b>Odor</b>	Alcohol like	<b>Vapor Pressure @20 °C</b>	4.2 kPa [32 mmHg]
<b>Odor Threshold</b>	0.44 ppm	<b>Vapor Density</b>	2.1 (Air =1)
<b>pH</b>	Not available	<b>Relative Density @25 °C</b>	0.785
<b>Freezing/Melting Point</b>	-88 °C [-126 °F]	<b>Solubility in Water</b>	Fully miscible
<b>Initial Boiling Point</b>	≥81.8 °C [≥179 °F]	<b>Partition Coefficient n-octanol/water</b>	Not available
<b>Flash Point <sup>a)</sup></b>	12 °C [54 °F]	<b>Auto-ignition Temperature</b>	425 °C [797 °F]
<b>Evaporation Rate</b>	1.5 (ButAc = 1)	<b>Decomposition Temperature</b>	Not available
<b>Flammability</b>	Highly flammable	<b>Viscosity @20 °C</b>	2.4 mPa·s [3.1 mm <sup>2</sup> /s]

a) Tag closed cup value

## 824-W

### Section 10: Stability and Reactivity

<b>Reactivity</b>	At elevated temperatures, may react with aluminum and generate hydrogen gas.
<b>Chemical Stability</b>	Chemically stable at normal temperatures and pressures
<b>Conditions to Avoid</b>	Avoid ignition sources, excessive heat, and incompatible substances.
<b>Incompatibilities</b>	Strong oxidizing agents, strong acids, strong bases, halogenated compounds, aluminum at temperatures $\geq 49\text{ }^{\circ}\text{C}$ [ $\geq 120\text{ }^{\circ}\text{F}$ ]
<b>Polymerization</b>	Will not occur
<b>Decomposition</b>	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

### Section 11: Toxicological Information

#### Summary of Effects and Symptoms by Routes of Exposure

<b>Eyes</b>	Causes eye redness, serious eye irritation, tearing, or pain.
<b>Skin</b>	May cause redness or a mild irritation.
<b>Inhalation</b>	May cause drowsiness or dizziness. Excessive exposure may cause narcotic effects, weakness, and headaches.
<b>Ingestion</b>	See inhalation symptoms.
<b>Chronic</b>	Prolonged or repeated exposure may defat skin and cause skin dryness and cracking, and local redness and discomfort.

#### Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
propan-2-ol	5 840 mg/kg Rat	12 800 mg/kg Rabbit	16 000 ppm 8 h Rat

*Note:* Toxicity data from the RTECS<sup>2</sup> and ECHA databases were consulted. The data from supplier SDS were also consulted.

*Section continued on the next page*



**824-W****Other Toxicological Effects**

<b>Skin corrosion/irritation</b>	Based on available data, the classification criteria are not met. Causes mild skin irritation based on Draize tests on rabbits.
<b>Serious eye damage/irritation</b>	Causes severe eye irritation: propan-2-ol is a severe irritant based on Draize tests on rabbits.
<b>Sensitization</b> (allergic reactions)	Based on available data, the classification criteria are not met.
<b>Carcinogenicity</b> (risk of cancer)	Propan-2-ol is not classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
<b>Mutagenicity</b> (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
<b>Reproductive Toxicity</b> (risk to sex functions)	Based on available data, the classification criteria are not met.
<b>Teratogenicity</b> (risk of fetus malformation)	Based on available data, the classification criteria are not met.
<b>STOT-single exposure</b>	Propan-2-ol can affect the central nervous system by inhalation causing drowsiness or dizziness.
<b>STOT-repeated exposure</b>	Based on available data, the classification criteria are not met.
<b>Aspiration hazard</b>	Based on available data, the classification criteria are not met.

**Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Based on available data, propan-2-ol does not meet the environmental toxicant classification with LC50 and EC50 >100 mg/L.

- Propan-2-ol has a minimal LC50 96 h of 9 640 mg/L for Pimephales promelas (fathead minnow); an EC50 24 h of 5 102 mg/L Daphnia magna (water flea); and an EC50 72 h of 2 000 mg/L Desmodemus subspicatus (green algae).

**Acute Ecotoxicity**

Available toxicity data does not meet classification thresholds

*Section continued on the next page*

## 824-W

### Chronic Ecotoxicity

Available toxicity data does not meet classification thresholds

### Biodegradability

The constituents are volatile.

### Other Effects

Regulated Volatile Organic Content (VOC) = 100% (785 g/L)

## Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

## Section 14: Transport Information

### Ground

**Refer to TDG** (Canadian Transportation of Dangerous Goods regulations) and **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

824-WX25, 824-WX50, 824-WX500

**NOT REGULATED** as per  
US.DOT. Special Provision 47  
TDG Special Provision 56

NOTE: **Net Fill** of 2 ml per  
packet

*FOR REFERENCE ONLY*

**UN number:** UN3175

**Shipping Name:** SOLIDS CONTAINING  
FLAMMABLE LIQUIDS, N.O.S. (isopropanol)

**Class:** 4.1

**Packing Group:** II

**Marine Pollutant:** No

*Section continued on the next page*

**824-W****Air****Refer to ICAO-IATA regulations.**

824-WX25, 824-WX50, 824-WX500  
**NOT REGULATED** as per  
Special Provisions A46

On air waybill, write: "Not restricted  
as per special provision A46".

NOTE: **Net Fill** of 2 ml per  
packet

*FOR REFERENCE ONLY*

**UN number:** UN3175

**Shipping Name:** SOLIDS CONTAINING FLAMMABLE  
LIQUIDS, N.O.S. (isopropanol)

**Class:** 4.1

**Packing Group:** II

**Marine Pollutant:** No

**Special Provision A46:** Mixtures of solids which are not subject to these Regulations and flammable liquids may be transported under this entry without first applying the classification criteria of Division 4.1, providing there is no free liquid visible at the time the substance is packaged and the packaging must pass a leakproofness test at the Packing Group II level. Small inner packagings consisting of sealed packets or articles containing less than 10 mL of a Packing Group II or III flammable liquid absorbed into a solid material are not subject to these Regulations provided there is no free liquid in the packet or article.

**Sea****Refer to IMDG regulations.**

824-WX25, 824-WX50, 824-WX500  
**NOT REGULATED** as per  
Special Provisions 216

NOTE: **Net Fill** of 2 ml per packet

*FOR REFERENCE ONLY*

**UN number:** UN3175

**Shipping Name:** SOLIDS CONTAINING  
FLAMMABLE LIQUIDS, N.O.S. (isopropanol)

**Class:** 4.1

**Packing Group:** II

**Marine Pollutant:** No

**Special Provision 216:** Mixtures of solids which are not subject to the provisions of this Code and flammable liquids may be transported under this entry without first applying the classification criteria of class 4.1, provided there is no free liquid visible at the time the substance is loaded or at the time of the packaging or cargo transport unit is closed. Each cargo transport unit shall be leakproof when used as a bulk container. Sealed packets and articles containing less than 10 mL of a packing group II or III flammable liquid absorbed into a solid material are not subject to the provisions of this Code provided there is no free liquid in the packet or article.

**Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.**

**824-W****Section 15: Regulatory Information****Canada****Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**


All hazardous ingredients are listed on the DSL.

**Hazardous Products Act (R.S.C., 1985, c. H-3)**

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

**USA****Other Classifications****HMIS® RATING**

<b>HEALTH:</b>	<b>1</b>
<b>FLAMMABILITY:</b>	<b>3</b>
<b>PHYSICAL HAZARD:</b>	<b>0</b>
<b>PERSONAL PROTECTION:</b>	

**NFPA® 704 CODES**

*Approximate HMIS and NFPA Risk Ratings Legend:*

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

**CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

**EPCRA** (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains up to 99.7% propan-2-ol (CAS # 67-63-0) which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

**TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

*Section continued on the next page*

## 824-W

**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any of the listed substances.

### Europe

**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

**WEEE** (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

### Section 16: Other Information

**SDS Prepared by** MG Chemicals Regulatory Department

**Date of Revision** 31 March 2021

**Supersedes** 17 March 2021

**Reason for Changes:** Added p-statement P405 in section 2.

### Reference

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

*Section continued on the next page*

## 824-W

### Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
ECHA	European Chemicals Agency
EU	European Union
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

**Technical Queries** Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.mgchemicals.com](http://www.mgchemicals.com).

Email: [support@mgchemicals.com](mailto:support@mgchemicals.com)

Phone: +1-905-331-1396

**Mailing Addresses** *Manufacturing & Support*  
1210 Corporate Drive  
Burlington, Ontario, Canada  
L7L 5R6

*Head Office*  
9347-193rd Street  
Surrey, British Columbia, Canada  
V4N 4E7

### Disclaimer

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.