

TOTAL GROUND CARBON CONDUCTIVE COATING

838AR-LIQUID

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Name: Total Ground™ Carbon Conductive Coating

SDS Code: 838AR-Liquid

Related Part # 838AR-15ML, 838AR-150ML, 838AR-900ML, 838AR-3.78L

Recommended Use and Restriction on Use

Use: Electrically conductive coating and EMI/RFI shield

Uses Advised Against: Not available

Details of Manufacturer or Importer

Manufacturer

MG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA

MG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA

☎ +1-800-340-0772

FAX +1-800-340-0773

E-MAIL support@mgchemicals.com

WEB www.mgchemicals.com

☎ +1-905-331-1396

FAX +1-905-331-2682

E-MAIL info@mgchemicals.com

E-MAIL (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY—leaks, spills, fires, exposures or accidents

USA or CANADA: Call CHEMTREC ☎: **+1-800-424-9300**

For emergencies involving dangerous goods; Collect 24/7

CANADA: Call CANUTEC ☎: **+1-613-996-6666** or ***666** on cellular phones

TOTAL GROUND CARBON CONDUCTIVE COATING 838AR-LIQUID

Section 2: Hazard(s) Identification




Classification of Hazardous Chemical

GHS Categories

Criteria	Category	Signal Word	Pictograms
Flammable Liquid	2	Danger	Flame
Carcinogenicity	2	Warning	Health
Eye Irritation	2	Warning	Exclamation
Specific Target Organ Toxicity Single Exposure	3	Warning	Exclamation

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H225: Highly flammable liquid and vapor
	H351: Suspected of causing cancer by inhalation
	H319: Causes serious eye irritation H336: May cause drowsiness or dizziness

Section continued on the next page

TOTAL GROUND CARBON CONDUCTIVE COATING 838AR-LIQUID

Continued...

Prevention	Precautionary Statements
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No Smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof equipment.
P243	Take action to prevent static discharges.
P261 + P271	Avoid breathing mist/vapors/spray. Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/eye protection/face protection.
P264	Wash hands thoroughly after handling.
Response	Precautionary Statements
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P303 + P361 + P353	IN ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.

Section continued on the next page

TOTAL GROUND CARBON CONDUCTIVE COATING 838AR-LIQUID

Continued...

Storage	Precautionary Statements
P403 + P235	Store in well-ventilated place. Keep cool.
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents/container in accordance to local/regional/international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	% (weight)
67-64-1	acetone	38%
78-93-3	butan-2-one ^{a)}	37%
1333-86-4	carbon black	6%
67-63-0	propan-2-ol ^{b)}	5%
108-65-6	1-methoxy-2-propanol acetate	5%

a) Also known as methyl ethyl ketone (MEK)

b) Also known as isopropyl alcohol or isopropanol (IPA)

TOTAL GROUND CARBON CONDUCTIVE COATING 838AR-LIQUID

Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
IF ON SKIN (or hair)	P303 + P361 + P353, P263
Immediate Symptoms	<i>redness, mild irritation, dry skin</i>
Response	Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse.
IF INHALED	P304 + P340 + P312, P308 + P313
Immediate Symptoms	<i>cough, drowsiness, dizziness, headaches, nausea, unconsciousness</i>
Response	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell. IF exposed or concerned: Get medical advice/attention.
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	<i>redness, severe irritation, pain</i>
Response	Rinse cautiously with water for 15 minutes or more. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
IF SWALLOWED	P301 + P330 + P331
Immediate Symptoms	<i>nausea, abdominal pain, diarrhea, drowsiness, dizziness</i>
Response	Rinse mouth. Do NOT induce vomiting.

TOTAL GROUND CARBON CONDUCTIVE COATING**838AR-LIQUID****Section 5: Fire-Fighting Measures**

Extinguishing Media	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish. Use water spray to cool containers.
Specific Hazards	The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion. Prevent fire-fighting wash from entering waterway or sewer system.
Combustion Products	Produces carbon oxides (CO,CO ₂).
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

Section 6: Accidental Release Measures

Personal Protection	See personal protection recommendations in Section 8.
Precautions for Response	Avoid breathing the mist/spray/vapors. Remove or keep away all sources of extreme heat or open flames.
Environmental Precautions	Prevent spill from entering drains and waterways.
Containment Methods	Contain with inert absorbent (such as soil, sand, vermiculite).
Cleaning Methods	Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.
Disposal Methods	Dispose of spill waste according to Section 13.

TOTAL GROUND CARBON CONDUCTIVE COATING

838AR-LIQUID

Section 7: Handling and Storage

- Prevention** Keep out of reach of children.
- Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No Smoking.
- Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
- Avoid breathing mist/vapors/spray. Use only outdoors or in a well-ventilated area.
- Keep container tightly closed.
- Ground and bond container and receiving equipment.
- Use explosion-proof equipment.
- Take action to prevent static discharges.
- Handling** Wear protective gloves/clothing/eye protection.
- Wash hands thoroughly after handling.
- Take off contaminated clothing and wash it before reuse.
- Storage** Store in well-ventilated place. Keep cool.
- Store locked up.

Section 8: Exposure Controls/Personal Protection

Substances with Occupational Exposure Limit Values

Chemical Name	Country/ Provinces	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
acetone	ACGIH	500 ppm	750 ppm
	U.S.A. OSHA PEL	1 000 ppm	Not established
	Canada AB	500 ppm	750 ppm
	Canada BC	250 ppm	500 ppm
	Canada ON	500 ppm	750 ppm
	Canada QC	750 ppm	1 000 ppm

Section continued on the next page

TOTAL GROUND CARBON CONDUCTIVE COATING 838AR-LIQUID

Continued...

Chemical Name	Country/ Provinces	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
butan-2-one (methyl ethyl ketone)	ACGIH	200 ppm	300 ppm
	U.S.A. OSHA PEL	200 ppm	Not established
	Canada AB	200 ppm	300 ppm
	Canada BC	50 ppm	100 ppm
	Canada ON	200 ppm	300 ppm
	Canada QC	150 ppm	300 ppm
carbon black ^{a)}	ACGIH	3.5 mg/m ³	Not established
	U.S.A. OSHA PEL	3.5 mg/m ³	Not established
	Canada AB	3.5 mg/m ³	Not established
	Canada BC	3 mg/m ³	Not established
	Canada ON	3.5 mg/m ³	Not established
	Canada QC	3.5 mg/m ³	Not established
propan-2-ol	ACGIH	200 ppm (TWA)	400 ppm
	U.S.A. OSHA PEL	400 ppm	Not established
	Canada AB	200 ppm	400 ppm
	Canada BC	200 ppm	400 ppm
	Canada ON	200 ppm	400 ppm
	Canada QC	400 ppm	500 ppm
1-methoxy-2-propanol acetate	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	50 ppm	Not established
	Canada AB	Not established	Not established
	Canada BC	50 ppm	75 ppm
	Canada ON	50 ppm	Not established
	Canada QC	Not established	Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from by RTECS database² and data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) Respirable airborne particles

Engineering Controls

Ventilation

Keep airborne concentrations below the occupational exposure limits (OEL).

Section continued on the next page

TOTAL GROUND CARBON CONDUCTIVE COATING 838AR-LIQUID**Personal Protective Equipment**

- Eye protection** Wear appropriate protective eyeglasses or chemical safety goggles.
Recommendation: Ensure that glasses have side shields for lateral protection.
- Skin Protection** For likely contacts, use of protective butyl rubber or other chemically resistant gloves.
- Respiratory Protection** For over-exposures up to 10 x OEL of mist/vapors/spray, wear respirator such as a half-mask respirator with organic vapor cartridges and particulate filter.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.
RECOMMENDATION: Consult your local safety supply store to ensure your respirator has filter cartridges appropriate for the ingredients listed in section 3 of this SDS, and that the respirator is fitted to the employee by a professional.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

TOTAL GROUND CARBON CONDUCTIVE COATING
838AR-LIQUID
Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit ^{b)}	2%
Appearance	Black	Upper Flammability Limit ^{b)}	12%
Odor	Ketone-like	Vapor Pressure ^{b)} @20 °C	17 kPa [125 mmHg]
Odor Threshold ^{a)}	5 ppm	Vapor Density	≥2 (Air =1)
pH	Not available	Specific Gravity @25 °C	0.85
Freezing/Melting Point	Not available	Solubility in Water	Partially miscible
Boiling Point ^{a)}	56 °C [132 °F]	Partition Coefficient	Not available
Flash Point ^{a)}	-17 °C [1.4 °F]	Auto-ignition Temperature ^{c)}	≥315 °C [≥599 °F]
Evaporation Rate	Fast	Decomposition Temperature	Not available
Flammability (solid, gas)	Not available	Viscosity @25 °C	154 cP

a) Values based on acetone component.

b) Lower and Upper Explosive Limits, and vapor pressure of mixture calculated using Le Chatelier principle and component physical values.

c) The auto-ignition value is based on 1-methoxy-2-propanol acetate, which is the component with the lowest value.

Section 10: Stability and Reactivity

Reactivity	Not available
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Ignition sources, open flames, excessive heat, and incompatible substances
Incompatibilities	Oxidizing agents, strong acids
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

TOTAL GROUND CARBON CONDUCTIVE COATING**838AR-LIQUID****Section 11: Toxicological Information****Routes of Exposure**

Inhalation, Eye contact, Skin contact, and Ingestion

Symptoms Summary

Eyes	Causes redness, severe irritation, and pain.
Inhalation	May cause cough, drowsiness, dizziness, headaches, nausea, or unconsciousness.
Ingestion	May cause nausea, abdominal pain, and diarrhea (also see inhalation symptoms).
Skin	Causes skin redness, mild irritation, and dry skin.
Chronic	Prolonged or repeated exposure may cause skin dryness, cracking, as well as defatting the skin.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
acetone	5 800 mg/kg Rat	20 mL/kg Rabbit ^{a)}	16 000 ppm 4 h Rat ^{a)}
butan-2-one	2 737 mg/kg Rat	6 480 mg/kg Rabbit	23 500 mg/m ³ 8 h Rat
carbon black	>15 g/kg Rat	>3 g/kg Rabbit	Not established
propan-2-ol	3 600 mg/kg Rat	12 800 mg/kg Rabbit	16 000 ppm 8 h Rat
1-methoxy-2-propanol acetate	8 532 mg/kg Rat	>5 g/kg Rabbit	Not available

Note: Toxicity data from the RTECS database accessed through the Canadian Centre for Occupational Health and Safety (CCOHS)² were consulted. The data from supplier (M)SDS were also consulted.

a) Supplier safety data sheet

Section continued on the next page

TOTAL GROUND CARBON CONDUCTIVE COATING 838AR-LIQUID**Other Toxicological Effects**

Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/irritation	Acetone is a known serious eye irritant.
Sensitization (allergic reactions)	Based on available data, the classification criteria are not met.
Carcinogenicity (risk of cancer)	The carbon black [1333-86-4] is possibly carcinogenic by airborne routes of exposures under WHMIS. Carbon Black [1333-86-4] IARC Group 2B: Possibly carcinogenic to humans ACGIH A4: Not classified as a human carcinogen CA Prop 65: Listed as a carcinogen (airborne, as unbound particles of respirable size) NTP: Not listed
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	Based on available data, the classification criteria are not met.
Teratogenicity (risk of fetus malformation)	Based on available data, the classification criteria are not met.
STOT-single exposure	Inhalation of acetone, butan-2-one, and propan-2-ol may affect the central nervous system.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met. There is less than 10% category 1 components.

TOTAL GROUND CARBON CONDUCTIVE COATING**838AR-LIQUID****Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Acetone, butan-2-one, carbon black, propan-2-ol, and 1-methoxy-2-propanol acetate are not classifiable as an environmental toxicant (with minimal LC50 of >100 mg/L).

- Acetone has a minimal LC50 96 h of 5 540 mg/L for *Oncorhynchus mykiss* (rainbow trout) and an EC50 48 h of 13 500 mg/L for *Daphnia magna* (water flea).
- The butan-2-one has minimal LC50 of 3 130 mg/L 96 h for *Pimephales promelas* (fathead minnow); EC50 24 h 5 102 mg/L 24 h *Daphnia magna* (water flea).
- Propan-2-ol has a minimal LC50 96 h of 9 640 mg/L for *Pimephales promelas* (fathead minnow); EC50 24 h of 5 102 mg/L for *Daphnia magna* (water flea); EC50 24 h of >2 000 mg/L *Desmodesmus subspicatus* (green algae).
- 1-Methoxy-2-propanol has a minimal LC50 96 h of ≥ 100 mg/L *Salmo gairdneri* and an EC50 48 h of >500 mg/L for *Daphnia magna* (water flea).

Acute Ecotoxicity

Not regulated

Chronic Ecotoxicity

Not Regulated

Biodegradability

Solvent part expected to be biodegradable, but not the polymer. The volatile solvent constituents will oxidize rapidly in air by photochemical reaction.

Other Effects

Actual VOC (Volatile Organic Compounds) content according to the US (EPA) and Canadian (CEPA) authorities.

Actual VOC = 47% [404 g/L]

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

TOTAL GROUND CARBON CONDUCTIVE COATING

838AR-LIQUID

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations);
USA DOT 49 CFR (Parts 100 to 185) **Regulations.**

Sizes 5 L and under

Limited Quantity



Sizes greater than 5 L

UN number: UN1263
Shipping Name: PAINT
Class: 3
Packing Group: II
Marine Pollutant: No



Flash Point \geq -17 °C [1.4 °F]

Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Sizes up to 5 L (passenger), 60 L (cargo)

UN number: UN1263
Shipping Name: PAINT
Class: 3
Packing Group: II
Marine Pollutant: No



Flash Point \geq -17 °C [1.4 °F]

Sea

Refer to IMDG regulations.

Sizes 5 L and under

Limited Quantity



Sizes greater than 5 L

UN number: UN1263
Shipping Name: PAINT
Class: 3
Packing Group: II
Marine Pollutant: No



Flash Point \geq -17 °C [1.4 °F]

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

TOTAL GROUND CARBON CONDUCTIVE COATING

838AR-LIQUID

Section 15: Regulatory Information

Canada

WHMIS 1988 Classification



B2 – Flammable Liquid;
 D2A – Very Toxic (Carcinogen IARC 2B);
 D2B – Toxic Other (Eye Irritant)

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.

Industry and Science Canada

MG Labels products intended for the workplace to conform to WHMIS labeling regulations. Product identification, net quantity declaration, minimum printing type size heights, and packaging of this product are in compliance.

Health Canada

Products produced by MG Chemicals intended for retail display conform to the Canadian Consumer Labeling Regulations.


USA

Other Classifications

HMIS® RATING

HEALTH:	*	2
FLAMMABILITY:		3
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

Section continued on the next page

TOTAL GROUND CARBON CONDUCTIVE COATING 838AR-LIQUID**CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain products that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains acetone (CAS# 67-64-1) and butan-2-one (CAS# 78-93-3), which are subject to the CERCLA reporting requirements at the 5000 lb (2268 kg) threshold.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, June 06, 2014 revision, USA).

This product contains carbon black, which is listed as a carcinogenic substance when airborne, as unbound particles of respirable size.

Europe**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, or PBDE's, and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information

SDS Prepared by Michel Hachey

Date of Review 21 October 2015

Supersedes Not applicable

Reason for Changes: New product classified to meet both HCS2012 and WHMIS 2015 regulations.

Section continued on the next page

TOTAL GROUND CARBON CONDUCTIVE COATING 838AR-LIQUID**Reference**

- 1) ACGIH 2013 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2013).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
ECHA	European Chemicals Agency
EU	European Union
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer This material safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.