

MA-100SB | MA-100DB | Personal Wireless PA System

Ultra Light, Ultra Compact, Superb Performance



Don't be misled by the compact size of this highly portable, personal sound system. Lightweight, robust and battery operated, it can be carried via the built-in handle, on a shoulder strap or mounted on a mic stand for all situations where you need to raise the volume of your voice to communicate with a small audience.

Features

- Rugged yet lightweight one-piece molded cabinet.
- Hand-carry, shoulder strapped or mounted on a microphone stand.
- Built-in 1 or 2 diversity receivers for reliable, extended reception range.
- Built-in USB music player & recorder with LCD screen.
- Built-in one-button alarm/siren for warning of threats.
- User-friendly control panel provides intuitive easy operation.
- High efficiency class-D amplifier drives a full-range speaker.
- Switching power supply efficiently provides a regulated output voltage.
- AC and lithium rechargeable battery operation.
- Available in black or white color.

Ideal Applications

- School classrooms
- Places of worship
- Presentations, seminars and meetings
- Day-care activities; playground duty
- Indoor/outdoor gatherings
- Tour guides & Paging
- Fire fighters, law enforcement, search & rescue squads
- Street performers
- Factory and company tours

MA-100SB 1CH + USB Player & Recorder



MA-100DB 2CH + USB Player & Recorder



Controls and Indicators (Model Shown: MA-100DB)



Specifications

Model		MA-100SB	MA-100DB
		Portable PA	
Max. Power Output		50 Watts	
Amplifier		Class D	
Sensitivity		Typical: 90 dB Maximum: 102 dB	
T.H.D.		< 1%	
Frequency Response		50 Hz – 18 kHz	
Speaker		5 " full-range, high efficiency	
Audio Inputs	Wired	6.3 mm (1/4 ")	
	Line-In	3.5 mm (1/8 ")	
Audio Output		3.5 mm (1/8 ")	
Alarm Siren		Siren sound with fade-in mode	
Installation		Microphone stand, table mounted, shoulder belt	
Power Supply	AC	External 100 – 240 V AC switching power supply (Max. Power Consumption: 60 W)	
	DC & Battery	Built-in 14.8 V / 2.6 AH rechargeable lithium battery (MB-10 × 1)	
Charge Time		Up to 4 hours (automatic charging management)	
Standby Time		Up to 12 hours	Up to 10 hours
Battery Indicator		4-level indicator (25/50/75/100%)	
Color		Black or white option	
Dimensions (W × H × D)		135 × 144 × 240 mm / 5.3 × 5.6 × 9.4 "	
Weight (battery included)		Approx. 1.8 kg / 3.9 lbs	Approx. 1.9 kg / 4.1 lbs
Wireless System			
Receiver Channel		Single	Dual
Frequency Range		480 – 934 MHz (country dependent)	
Bandwidth		24 MHz	
Preset Channels		16	
Channel Set-up		Scan & ACT sync	
Transmitter		ACT-32H / ACT-32HC Handheld	
Microphone		MM-107 Wired Dynamic Microphone	
Antenna		Built-in	
Audio Player			
Built-in USB Port		USB 2.0	
USB Play & Record		LCD displays track name, number, time, recording status.	
Operation		On-board. USB remote control included.	
Patents & Approvals		Patented. Telecom and safety regulations approved.	
Notes		Refer to actual product in the event of product description discrepancy. Frequency range and maximum deviation comply with regulations of different countries.	



