

M12-FP-RTD PROBE

Flexible RTD Probe with M12 Connector



Features

- 36 inch Probe for Remote Monitoring
- Flexible Probe Design for Easy Positioning

Applications

- Autoclave Verification & Mapping
- Steam Sterilization
- Lyophilization
- Monitoring High-Temperature Surfaces
- Container Mapping
- Measurements Inside Small Vials & Tubing

This RTD probe is compatible with the MadgeTech HiTemp140-M12 data logger and is equipped with an M12 connector. This probe is narrow, lightweight and flexible with a 36 inch probe length and 0.086 inch diameter. The durable, flexible design reduces the risk of breakage generally associated with stainless steel probes.



M12-FP-RTD PROBE SPECIFICATIONS*

Compatible Data Loggers: HiTemp140-M12

Measurement Range: -60 °C to 260 °C (-76 °F to 500 °F)

Operating Environment: -60 °C to 260 °C (-76 °F to 500 °F)

Dimensions: Probe Length: 36 in (914 mm)
Probe Diameter: 0.086 in (2.1 mm)

Material: Stainless Steel, PFA, Polyamide 6-6 GF

Probe IP Rating: IP67

ORDERING INFORMATION

*SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. SPECIFIC WARRANTY REMEDY LIMITATIONS APPLY. CALL 1-603-456-2011 OR GO TO WWW.MADGETECH.COM FOR DETAILS.

MODEL	DESCRIPTION
M12-FP-RTD Probe	M12 PFA Insulated Flexible RTD Probe with M12 Connector
HiTemp140-M12	High Temperature Data Logger with an M12 Probe Connector
MicroDisk	Surface Temperature Probe Attachment

ASK ABOUT
OUR OTHER
DATA
LOGGERS

Temperature
Humidity
Pressure
pH
Level
Shock
LCD Display
Pulse/Event/State
Current
Voltage
Wireless
Intrinsically Safe
Spectral Vibration
Motion

For Quantity Discounts call 603-456-2011 or email sales@madgetech.com