HIGH PRESSURE/TURBO SMOKE MACHINE UNIVERSAL COOLING SYSTEM ADAPTER KIT

FEATURES

- Universal design will fit most automotive radiators and expansion tanks •
- Easily smoke test any empty cooling system with the use of the universal adapter •
- Rubber hose fitting on adapter will connect to most diagnostic smoke machines •
- Ultimate coverage provided by 3 rubber ring gaskets included in the kit
- Secure fit using the simple twist style design •

SPECIFICATIONS

- 41018A 1
- Radiator Adapter
- 43060-WH Whip Hose for 43060-UTA Turbo Adapter 2.
- 43060-RA-TB Radiator Adapter Fitting for Turbo/Evap 3.
- 43012-35 0D35 x ID30 Rubber Ring 4
 - 43012-39 0D39 x ID30 Rubber Ring
- 43012-44 6.
- 0D44 x ID30 Rubber Ring





CAUTION

5.

- Always read instructions carefully before using the tool
- Always wear eve protection that meets OSHA and ANSI Z87.1 standards
- Always wear gloves when working with the tool •

INSTRUCTIONS

- Drain the coolant from the radiator. 1
- 2. Select a suitable sized rubber bushing and fit it to the lower part of the radiator adapter. Insert the adapter into the radiator or expansion tank filler neck. Turn the sealing collar to make a seal between the tools and the radiator or expansion tank filler neck.
- 3. Check the cooling system pressure of the vehicle.
- 4. Attach the turbo/intake diagnostic smoke machine to the adapter.
- 5. Using the instructions from turbo/intake diagnostic smoke machine, pressurize the cooling system with smoke. Use the flashlight to check for leaks.



