




2-WAY PISTON VALVE MANIFOLD FOR CO2 (R744)



- Our Free Floating Piston Valve results in less wear and tear in comparison to market standard twisting piston valves
- Double O-Ring allows for a much better seal resulting in less leaks
- Oil filled, class 1.0, 70 mm gauges
- Easy to read pressure scales on gauge face
- Solid extruded aluminum body
- Large easy-to-grip-knobs
- 1/4" SAE
- Steel braided hoses for CO2
- Assemblies packed in plastic carrying case
- Plastic carrying case, p/n 58102-PBR

Gauge class – diameter	1.0 - 70 mm
Units	PSI/MPa
Refrigerant scales	R744
Gauge p/n (HP/LP)	55102-2400 55102-1400
Manifold body with hook and hose holder (1/4" SAE)	55102
Manifold with oil filled gauges only (1/4" SAE)	55103
Manifold (as above) with 3 - 150 cm braided hoses	55661

CLASS 1.0 REPLACEMENT GAUGE FOR CO2



High pressure p/n	Low pressure p/n	Gauge Diameter	Units	Refrigerant Scales
55102-2400	55102-1400	70 mm	PSI/MPa	R744

STEEL BRAIDED HOSES FOR CO2



- Steel Braided Hoses
O.D of stainless steel rope: 0.18 mm
Braided by 4 wires
- Section: PTFE Tube: 7 mm x 5 mm / Sandwich: 0.5 mm
- Outside Diameter 9 mm
- Thread 7/16-20UNF
- Working Pressure 200 BAR
- Burst 800 BAR

HOSE LENGTH	150 cm
Steel braided hose for CO2	55601
SET of 3 steel braided hoses for CO2	55360