



Mastercool[®] Inc.
"World Class Quality"

1 ASPEN DRIVE, RANDOLPH, NJ 07869
PHONE: 973-252-9119 / FAX: 973-252-2455
WEB: WWW.MASTERCOOL.COM

69395 COMBUSTIBLE GAS RECOVERY MACHINE



SPECIFICATIONS:

- 1/2 hp oil less compressor
- Operating Temperature: 32 to 122°F
- Weight: 28.3 lbs
- Dimensions: 18" (l) x 10" (w) x 14" (h)
- Case Material is HDPE (High Density Polyethylene)
- Compatible refrigerants: All CFC, HCFC, and HFC's

Spark Free **TWINTURBO** REFRIGERANT RECOVERY MACHINE

• COMPATIBLE WITH ALL CFC, HCFC AND HFC'S

- 1/4" flare fittings
- 115 V / 60 Hz

COMPATIBLE WITH COMBUSTIBLE GASES

FEATURES & BENEFITS:

- Largest volume recovery rate in market
- Sealed crank case eliminated refrigerant loss during the recovery process
- Revolutionary double piston oil-less compressor provides fast recovery times
- Large, easy to read 2 1/2" gauges
- Purge valve ensures 100% refrigerant removal from the condenser and the recovery machine
- Large fan and condenser keeps the unit running cooler and speeds up the recovery process
- Safety high pressure switch
- Simple internal structure for field service
- For use with all refrigerants including R410A
- Injection molded high density polyethylene case for maximum durability
- Front cover has bumper guards built in to reduce damage to the control knobs