



Made in America

### Features:

- D-Ring fastening is ideal for bundling trays and IC tubes
- Adjustable, releasable and reusable - easy to install
- Low charging meets ANSI/ESD S20.20 and ANSI/ESD S541
- Custom sizes available
- Operating Temperature: 300°F (149°C) max
- Melting Temperature: 459°F (237°C)
- Straps should be tested regularly to make sure they retain their ESD properties
- Made in America



\*Trays not included

<a href="#">35653</a>	Low Charging Cable Tie, Non-Stretch D-Ring, 3/4 in (19 mm) x 18 in (457 mm)
<a href="#">35654</a>	Low Charging Tie, Non-Stretch D-Ring, 3/4 in (19 mm) x 20 in (19 mm)
<a href="#">35655</a>	Low Charging Cable Tie, Non-Stretch D-Ring, 3/4 in (19 mm) x 24 in (609 mm)
<a href="#">35656</a>	Low Charging Cable Tie, Non-Stretch D-Ring, 3/4 in (19 mm) x 30 in (762 mm)

Specifications and procedures subject to change without notice. Unless otherwise noted, tolerance is ±10%.

### LOW CHARGING CABLE TIES

# MENDA

3651 WALNUT AVE., CHINO, CA 91710  
 PHONE: (951) 627-2453 • FAX: (951) 755-8848  
 WEBSITE: [MendaPump.com](http://MendaPump.com)

**DRAWING  
 NUMBER:**  
 35653

**DATE:**  
 April  
 2017