

HIGH-DENSITY STORAGE — QWIKTRAK™



qwikTRAK Storage System — {11.15}

Super Erecta, Super Erecta Pro, Super Adjustable, MetroMax Q, MetroMax i, MetroMax 4




Getting started:

Document the available floor space

- Actual length: Nominal track length + the nominal width of each end unit + 3" (76mm)
- Actual width: Nominal Shelf length + 3.5" (89mm)
- Actual height of a mobile qwikTRAK unit is: Nominal post height + 4.5" (115mm)

It is recommended that the tracks are installed at least 2" (52mm) from the wall.



Shelves Sold Separately: All end, intermediate, and mobile units must be 18" (457mm) or wider. Each stationary end and intermediate unit must have a minimum of four shelves. Super Adjustable shelves may be used for all tiers.

Stationary End Unit Kit (Choose one kit for each system)

Includes 74" high posts (1880mm) high stationary posts, and hardware necessary for connecting stationary end units to tracks. Shelves are sold separately.


Super Erecta, Super Erecta Pro, Super Adjustable Super Erecta				MetroMax Q Steel Posts	MetroMax Polymer Posts
Cat. No. Chrome Plated	Cat. No. Metroseal Green	Cat. No. Metroseal Gray	Cat. No. Stainless Steel	Cat. No.	Cat. No.
BTEC	BTEK3	BTEK4	BTES	BTEQ3	BTEX3



Stationary Intermediate Units

Required when overall desired track length exceeds 21' (6405mm). Optional when track length is under 21' (6405mm). Includes 74" high posts (1880mm) high stationary posts, and hardware necessary for connecting one stationary intermediate unit to tracks. Shelves are sold separately.

Super Erecta, Super Erecta Pro, Super Adjustable Super Erecta				MetroMax Q Steel Posts	MetroMax Polymer Posts
Cat. No. Chrome Plated	Cat. No. Metroseal Green	Cat. No. Metroseal Gray	Cat. No. Stainless Steel	Cat. No.	Cat. No.
BTAC	BTAK3	BTAK4	BTAS	BTAQ3	BTAX3



Mobile Units (One kit required per mobile unit)

Includes four 74" (1880mm) high mobile posts, four casters, donut bumpers, and other hardware to assemble a mobile unit. Shelves are sold separately.

Super Erecta, Super Erecta Pro, Super Adjustable Super Erecta				MetroMax Q Steel Posts	MetroMax Polymer Posts
Cat. No. Chrome Plated	Cat. No. Metroseal Green	Cat. No. Metroseal Gray	Cat. No. Stainless Steel	Cat. No.	Cat. No.
BTMC	BTMK3	BTMK4	BTMS	BTMQ3	BTMX3

Under normal conditions, aisle width of 30"-36" (760-914mm) is recommended. The storage of very large objects within the system, however, may require an aisle width larger than 36" (914mm).



Note: Casters feature an acetyl grooved wheel. Chrome plated (BTMC) includes casters with plated steel components. BTMK3/BTMS/BTMQ3/BTMX3 include casters with stainless

Track Sets Includes tracks and hardware needed to assemble track runs up to 21' (6400mm).

Length (ft.) (mm)	Cat. No.	Length (ft.) (mm)	Cat. No.
2.5 762	BTS2.5NA	14 4267	BTS14NA
6 1828	BTS6NA	15 4572	BTS15NA
7 2135	BTS7NA	16 4877	BTS16NA
8 2440	BTS8NA	17 5182	BTS17NA
9 2743	BTS9NA	18 5486	BTS18NA
10 3048	BTS10NA	19 5791	BTS19NA
11 3352	BTS11NA	20 6096	BTS20NA
12 3657	BTS12NA	21 6400	BTS21NA
13 3962	BTS13NA		

Note: BTS2.5NA includes a joining kit to connect the tracks to other track sets.



The easiest way to build qwikTRAK.

Notes:

1. qwikTRAK is available with 74" posts (1880mm) as standard. Requests for TALLER posts must be reviewed by Metro Engineering. For applications requiring posts SHORTER than 74" (1880mm), contact your Metro representative.
2. Existing Metro Super Erecta, Super Adjustable, MetroMax Q, and MetroMax i shelving units can be retrofitted as part of a qwikTRAK installation.
3. Weight capacities for standard qwikTRAK: Super Erecta, Super Adjustable, MetroMax Q systems are designed to hold up to 2,000 lbs. (907kg) per shelving unit. MetroMax i stationary units can hold up to 2,000 lbs. (907kg); MetroMax i mobile units can hold up to 1,200 lbs. (544kg) per unit. MetroMax 4 stationary units can hold up to 2,000 lbs. (907kg); MetroMax 4 mobile units can hold up to 800 lbs. (363kg) per unit.
4. Added rigidity for heavily loaded systems. Super Erecta standard adjustment shelves provide the most rigid wire shelving mobile units; Recommended when configuring systems using 60" and 72" long shelves subject to the heaviest loads and frequent movement (multiple times daily). MetroMax Q epoxy coated steel posts may be used with MetroMax i shelves for added rigidity when managing sensitive packaged items and heavier unit loads; steel posts are corrosion resistant.