

Casters for Dry Areas



CASTER
INSTALLATION



GOOD

Plated Stem Casters — {11.20}

Plated caster horns and hardware for basic dry environments.



5LD



5MB



5MDBA



5MPB



5MPR

Wheel Diameter (in.) (mm)	Face (in.) (mm)	Load Rating (lbs.) (kg)	Type	Wheel Tread	Temperature Range (Continuous Usage) (Fahrenheit) (Celsius)	Cat. No.
4	102 .5 12	125 56	Stem/Swivel	Resilient Donut	-20°-160° -29°-71°	4LD
5	127 .5 12	125 56	Stem/Swivel	Resilient Donut	-20°-160° -29°-71°	5LD
5	127 1.25 32	200 90	Stem/Swivel	Resilient, Flat	-20°-160° -29°-71°	5M
5	127 1.25 32	200 90	Stem/Brake	Resilient, Flat	-20°- 160° -29°-71°	5MB
5	127 1.25 32	200 90	Stem/Rigid	Resilient, Flat	-20°- 160° -29°-71°	5MR
5	127 1.25 32	250 113	Stem/Swivel	High Modulus Donut	-20°-180° -29°-82°	5MDA
5	127 1.25 32	250 113	Stem/Brake	High Modulus Donut	-20°-180° -29°-82°	5MDBA
5	127 1.25 32	250 113	Stem/Rigid	High Modulus Donut	-20°-180° -29°-82°	5MDRA
5	127 1.25 32	300 135	Stem/Swivel	Polyurethane, Flat	-20°-180° -29°-82°	5MP
5	127 1.25 32	300 135	Stem/Brake	Polyurethane, Flat	-20°-180° -29°-82°	5MPB
5	127 1.25 32	300 135	Stem/Rigid	Polyurethane, Flat	-20°-180° -29°-82°	5MPR
6	152 1.5 38	400 182	Stem/Swivel	Polyurethane, Flat	-20°-180° -29°-82°	6MP
6	152 1.5 38	400 182	Stem/Brake	Polyurethane, Flat	-20°-180° -29°-82°	6MPB
6	152 1.5 38	400 182	Stem/Rigid	Polyurethane, Flat	-20°-180° -29°-82°	6MPR

Note: Rigid casters are held in place by a connecting channel. When ordering, shelf width must be provided. Rigid connecting channel (stainless steel): Cat. No. 14RS, 18RS, 21RS, 24RS, 30RS, or 36RS. Load Height for all 5M and 5MP casters — 6.09" ± .06" (155 ± 1.5mm). Load Height for 4LD caster — 4.62" ± .06" (118 ± 1.5mm). Load Height for 5LD caster — 5.06" ± .06" (143 ± 1.5mm). Brakes are foot-operated.

Plated Stem Casters

Use with Super Erecta posts and shelves (see pages 42 and 48) to create a mobile shelving unit to meet your special needs. Stem casters are shipped with donut bumper at no additional charge.



Donut Bumper

Donut Bumpers — {11.40}

- Non-phthalate, flexible vinyl material

Diameter (in.) (mm)	Height (lbs.) (kg)	Cat. No.	Each
3.5 89	.75 19	9992DB*	9.40
5.5 140	.81 21	9992N	14.60

*Included with each Super Erecta stem caster as noted on previous page.

Low Profile 3" Casters — {11.20}

Ideal for creating shorter height mobile units for undercounter use. Threaded stem fits stationary posts with threaded base. (Remove leveling foot and install caster)

Wheel Diameter (in.) (mm)	Face (in.) (mm)	Load Rating (lbs.) (kg)	Type	Wheel Thread	Temperature Range (Continuous Usage) (Fahrenheit) (Celsius)	Cat. No.
3 76	.94 24	100 45	Threaded Stem, Swivel	Resilient Rubber	-30° - 160° -34° - 71°	3TM
3 76	.94 24	100 45	Threaded Stem, Swivel/Brake	Resilient Rubber	-30° - 160° -34° - 71°	3TMB

Note 1: Not intended for carts that travel long distances.



3TM



3TMB

Decorative Casters — {10.06}

- Black nylon housing with non-marking polymer tread.
- 2.5" (63mm) models have threaded stem and attach to stationary shelving posts.
- 4" (100mm) casters include threaded insert for use with mobile posts.

Type	Diameter (in.) (mm)	Fits Post Type	Cat. No.
Swivel/Brake	2.5 63	Stationary	HDC3BB
Swivel	4 100	Mobile	HDC5B
Swivel/Brake	4 100	Mobile	HDC5BB

Casters shipped with post inserts for adaptability to mobile posts.



HDC5B

HDC5BB

Wheel Material? What's the difference?

Wheel Material	Oil & Grease Resistance	Rollability	Noise
Resilient Rubber	LOW	FAIR	LOW
Neoprene	HIGH	GOOD	LOW
Polyurethane	HIGH	GOOD	MODERATE
High-Modulus Rubber	HIGH	GOOD	LOW
Conductive	LOW	FAIR	LOW