



We put space to work.

Item # _____

Job _____

Super Adjustable Super Erecta® Wire Shelf Carts (Stem Caster Style)


- **Stem Caster Carts combine Super Adjustable Super Erecta** wire shelving features with the mobility of stem casters to provide a high-quality, strong and versatile material handling cart.
- **Carts are preconfigured with two swivel and two swivel brake casters.** All Metro casters are non-marking and come complete with a 3½" (89mm) donut bumper.
- **Total cart capacity (evenly distributed)**
 - **Cart with Polyurethane casters:** 900 lb. (408kg)
 - **Cart with Resilient Rubber casters:** 600 lb. (272kg)
- **Unique Design: Open wire surfaces minimize** dust accumulation and allow a free circulation of air and greater visibility.
- **Reclaim wasted space. Easy "No tool" shelf adjustment.** The Corner Release System allows shelves to be repositioned quickly to maximize the use of vertical space.
- **Unique Post Design:** SiteSelect post design provides a visual guide for positioning and adjusting shelves, saving considerable time during assembly and adjustment. Posts have circular grooves at 1" (25mm) intervals and are numbered every 2" (51mm). An easy-to-identify double groove, every 8" (203mm), offers a quick way to align all shelves.
- **Easily Adjustable at 1" (25mm increments):** Unique Corner Release and SiteSelect Posts create a total system that offers "Tool-Free," fast adjustment at 1" (25mm) intervals along the entire height of the post. Unlock the corner releases, reposition the wedges and sleeves, and re-locate the shelf. The shelf simply seats into place.
- **Versatile Construction:** Super Adjustable Super Erecta wire shelving can change as quickly as your needs change. By using various accessories, hundreds of shelving combinations become possible.



5A356ABR



Corner Release



SiteSelect Post

All Metro Catalog Sheets are available on our website: www.metro.com



InterMetro Industries Corporation
North Washington Street, Wilkes-Barre, PA 18705
Product Information. U.S. and Canada: 1.800.992.1776
Outside U.S. and Canada: www.metro.com/contactus

L02-035
Printed in U.S.A. Rev. 11/19

Information and specifications are subject to change without notice. Please confirm at time of order.

Copyright © 2019 InterMetro Industries Corp.



Super Adjustable Super Erecta® Wire Shelf Carts (Stem Caster Style)



Job _____



Super Adjustable Super Erecta® Wire Shelf Carts (Stem Caster Style)

We put space to work.®

STANDARD UNITS

Consist of designated number of shelves, (4) posts, plastic split sleeves, donut bumpers, and designated casters. Shelves and posts are Chrome finish. Carts use stem caster posts (Model Number 63UP).

Four-Tier Units

Overall Height 67⁷/₈" (1724mm)

Model Number with Casters		Shelf Width/Length		Approx. Pkd. Wt.	
Two Swivel Two Brake Resilient Rubber Casters	Two Swivel Two Brake Polyurethane Casters	(in.)	(mm)	(lbs.)	(kg)
A336BC	A336EC	18x36	457x914	60	27
A356BC	A356EC	18x48	457x1219	72	32
A366BC	A366EC	18x60	457x1524	88	40
A436BC	A436EC	21x36	530x914	69	31
A456BC	A456EC	21x48	530x1219	81	36
A466BC	A466EC	21x60	530x1524	98	44
A536BC	A536EC	24x36	610x914	76	34
A556BC	A556EC	24x48	610x1219	92	41
A566BC	A566EC	24x60	610x1524	112	51

Five-Tier Units

Overall Height 67⁷/₈" (1724mm)

5A336BC	5A336EC	18x36	457x914	70	31
5A356BC	5A356EC	18x48	457x1219	84	37
5A366BC	5A366EC	18x60	457x1524	105	48
5A436BC	5A436EC	21x36	530x914	80	36
5A456BC	5A456EC	21x48	530x1219	95	42
5A466BC	5A466EC	21x60	530x1524	116	52
5A536BC	5A536EC	24x36	610x914	89	40
5A556BC	5A556EC	24x48	610x1219	108	48
5A566BC	5A566EC	24x60	610x1524	133	61

Note: The post used on the carts is model number 63UP.



Resilient Rubber Casters

Polyurethane Casters

TO ORDER BY COMPONENTS

- Order shelves from sheet 10.01A or price list. (Will be packed with plastic split sleeves.)
- Order stem casters from sheet 11.20 or price list. Donut bumper comes with caster.

LOAD RATING: Not to exceed 3 times the caster load rating.

** Carts with polyurethane casters are designed to hold up to 900 lbs. (408kg).

Carts with rubber casters can hold up to 600 lbs. (272kg).

Important: When ordering by components remember that stability decreases as the ratio of height to width increases. Units should be kept as wide and low as possible.

an Ali Group Company



The Spirit of Excellence