

# Corrosion resistance, removable shelf mats & antimicrobial protection at all touch-points.

### MetroMax Q Security Units — {14.01}

- Heavy gauge open wire construction.
- Microban antimicrobial product protection is built into the enclosures, doors, handles, and shelves.
- Optional intermediate shelves: MetroMax Q quick adjust shelves or corrosion proof MetroMax i.
- Ergonomic ¼-turn door handle: Doors open 270 degrees and can be secured along sides.

#### MetroMax Q Stationary Units - 66.19" (1681mm) High

Actual Outsid				
Width	Width Length		helf	
(in.) (mm)	(in.) (mm)	(in.)	(mm)	Cat. No.
26.94 685	38.88 987	24x36	610x914	MQSEC53E
26.94 685	50.88 1292	24x48 6	10x1219	MQSEC55E
26.94 685	62.88 1597	24x60 6	10x1524	MQSEC56E

Note: Leveling foot on post can be adjusted up to 1" (25mm) to compensate for uneven floors.

#### MetroMax Q Stem Caster Mobile Units — 67.81" (1723mm) High

Models include four 5" (127mm) diameter casters with polyurethane tread; two swivel and two swivel with brakes.

Actual Outside Dimensoins (including Bumpers and Handle)					Cat. No. Includes	Cat. No. Includes	
Wio (in.)	dth (mm)	Length (in.) (ı	h mm)	Fit (in.)	s Shelf (mm)	Casters with Plated Finish	Corrosion Resistant Polymer Casters
27.81	707	40.75 1	035	24x36	610x914	MQSEC53DE	MQSEC53VE
27.81	707	52.75 1	340	24x48	610x1219	MQSEC55DE	MQSEC55VE
27.81	707	64.75 1	645	24x60	610x1524	MQSEC56DE	MQSEC56VE

<sup>\*&</sup>quot;DE" models use two 5MPX and two 5MPBX casters.

#### MetroMax Q Heavy-Duty Mobile Units — 68.5" (1740mm) High

Mounted on aluminum dolly with 5" (127mm) plate casters and wraparound bumpers.

Ac Wid	(includ	ide Dimensoi ing Handle) Len		E:e.	s Shelf	Appi Pkd.		
(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)	Cat. No.
28.06	713	39.13	994	24x36	610x914	166	75	MQSEC53LE
28.06	713	51.13	1299	24x48	610x1219	176	80	MQSEC55LE
28.06	713	63.13	1603	24x60	610x1524	179	81	MQSEC56LE

Note: The aluminum dollies used on the LE models have two B5P and two B5PB plate casters.

#### Intermediate Shelves for MetroMax Q Security Q Cat. No. Cat. No. Cat. No. Shelf with Grid Mat Shelf with Solid Mat Shelf with Grid Mat Width (mm) MX2436G MX2436F MQ2436G 24 610 36 914 MX2448G MX2448F MQ2448G 610 48 1220 24 MX2460F 24 610 1524 MX2460G MQ2460G







## Units **DO NOT** include intermediate shelves.

Intermediate shelves must be ordered separately.

Standard Units consist of top and bottom wire shelves, tri-lobal adapters, steel posts, wire enclosures, and doors. Casters are included with mobile units.

<sup>\*\*\*&</sup>quot;VE" models use two 5PCX and two 5PCBX casters. Recommended for wet or damp environments.