

Stem Caster Carts — Solid Stainless Steel Embossed

Description	Width (in.) (mm)	Length (in.) (mm)	Height (in.) (mm)	Casters (amt.) (type)	Approx. Pkd. Wt. (lbs.) (kg)	Cat. No.
Solid Embossed	24 610	48 1219	68 1727	2 5MP	125 56	PR48ES
				2 5MPB		
Solid Embossed	24 610	60 1524	68 1727	2 5MP	153 66	PR60ES
				2 5MPB		

Embossed Stainless Shelves are perfect for:
Pot & Pan Drying Applications



Heavy-Duty Dolly Trucks

Safely Hold up to
1000lbs.
per mobile unit.

(Heavy-Duty Mobile Shelving)

- Carts configured with dolly bases are recommended for heavier duty applications. The dolly base is shock absorbent and the heavier duty plate casters are designed to withstand abusive conditions.
- Dolly trucks are recommended when the carts must travel longer distances, over thresholds, and/or between facilities on a regular basis.
- Dolly trucks can transport up to 1,000 lbs. (454kg) evenly distributed.

HIGH TRAFFIC. EXTREME IMPACT.



Super Erecta Dolly Trucks

Consist of four chrome wire shelves, aluminum dolly base, 63" (1600mm) plated posts, plastic split sleeves, donut bumpers and resilient rubber or poly casters as designated.

Shelf Width/Length (in.) (mm)	Approx. Pkd. Wt. (lbs.) (kg)	Catalog Number with Casters		
		Two BSDN Two BSDNB	Two B5P Two B5PB	Two 6P Set BL6P
24x36 610x914	96 43	N536JC	N536LC	N536MC
24x48 610x1219	118 53	N556JC	N556LC	N556MC
24x60 610x1524	142 64	N566JC	N566LC	N566MC

Overall heights: JC, LC models — 68.44" (1739mm), MC models — 70.06" (1800mm).

- JC models: Standard swivel plate casters, two with brake; resilient rubber tread.
- LC models: Standard swivel plate casters, two with brake; polyurethane tread.
- MC models: Larger plate casters; two swivel; one swivel/brake set; polyurethane tread.

