

Top-Track Storage System — {11.12}

Wire Shelving — Super Erecta, Super Erecta Pro, Super Adjustable




Super Erecta® Top-Track®

Getting started:

Document the available floor space

- Actual length: Nominal track length + the nominal width of each end unit + 2" (51mm)
- Actual width: Nominal Shelf length + 3.5" (89mm)
- Actual height of system is approx. 87" (2210mm)

It is recommended that the tracks are installed at least 5" (127mm) from the wall.



Shelves Sold Separately: All end, intermediate, and mobile units must be 18" (457mm) or wider. Each stationary end and intermediate unit must have a minimum of four shelves. Super Adjustable shelves may be used for all tiers.

Stationary End Unit Kits (One kit is required per single system)
Includes hardware necessary for connecting stationary end units to track. 86" (2185mm) posts are included. Shelves sold separately.


Shelf Width (in) (mm)	Cat. No. Chrome Plated	Cat. No. Metroseal Green	Cat. No. Metroseal Gray	Cat. No. Stainless Steel
18 457	TTE18C	TTE18K3	TTE18K4	TTE18S
21 530	TTE21C	TTE21K3	TTE21K4	TTE21S
24 610	TTE24C	TTE24K3	TTE24K4	TTE24S



Stationary Intermediate Units

Required when overall desired track length exceeds 21' (6405mm). Optional when track length is under 21' (6405mm). Includes 86" high posts (2184mm) high stationary posts, and hardware necessary for connecting one stationary intermediate unit to tracks. Shelves are sold separately.

Shelf Width (in) (mm)	Cat. No. Chrome Plated	Cat. No. Metroseal Green	Cat. No. Metroseal Gray	Cat. No. Stainless Steel
18 457	TTA18C	TTA18K3	TTA18K4	TTA18S
21 530	TTA21C	TTA21K3	TTA21K4	TTA21S
24 610	TTA24C	TTA24K3	TTA24K4	TTA24S



Mobile Unit Kits (One kit required per mobile unit)

Kit includes special 74" (1880mm) posts, casters/caster channels, donut bumpers, and roller bearing assemblies. Shelves are sold separately.

Shelf Width (in) (mm)	Overall Width (in) (mm)	Cat. No. Chrome Plated	Cat. No. Metroseal Green	Cat. No. Metroseal Gray	Cat. No. Stainless Steel
18* 457	20 1/4 514	TTM18C	TTM18K3	TTM18K4	TTM18S
21 530	23 1/4 590	TTM21C	TTM21K3	TTM21K4	TTM21S
24 610	26 1/4 667	TTM24C	TTM24K3	TTM24K4	TTM24S

Note: Casters feature wheels with polyurethane tread. Chrome plated kits include casters with plated steel components. Metroseal and Stainless Steel kits include casters with stainless steel components.

Under normal conditions, aisle width of 30"-36" (760-914mm) is recommended. The storage of very large objects within the system, however, may require an aisle width larger than 36" (914mm).

* If 18" wide mobile units are planned, the maximum allowable length shelf is 60" (1524mm) long. If 18" (457mm) wide by 60" (1524mm) long mobile units are planned, a maximum of five 18" (457mm) mobile units are allowable between two stationary units. 18" (457mm), 21" (530mm), 24" (610mm) wide mobile units can be intermixed in a given system.



Track Sets Includes tracks and hardware needed to assemble runs up to 21' (6400mm).

Length (ft.) (mm)	Cat. No.	Length (ft.) (mm)	Cat. No.
2.5 762	TTS2.5NA	14 4267	TTS14NA
6 1828	TTS6NA	15 4572	TTS15NA
7 2135	TTS7NA	16 4877	TTS16NA
8 2440	TTS8NA	17 5182	TTS17NA
9 2743	TTS9NA	18 5486	TTS18NA
10 3048	TTS10NA	19 5791	TTS19NA
11 3352	TTS11NA	20 6096	TTS20NA
12 3657	TTS12NA	21 6400	TTS21NA
13 3962	TTS13NA		

Note: TTS2.5NA includes a joining kit to connect the tracks to other track sets.



The easiest way
to build Top-Track.

Additional Notes:

1. To accommodate bumpers, the actual size of a mobile unit is 2.5" (63.5mm) wider than the shelf width shown. For example, an 18" (457mm) wide unit is actually 20.5" (52mm).
2. Recommended maximum load rating for a mobile unit is 900 lbs. (410kg). Floor should be level, smooth, and free from large cracks and raised obstacles.
3. Added rigidity for heavily loaded systems. Super Erecta standard adjustment shelves provide the most rigid wire shelving mobile units; Recommended when configuring systems using 60" (1524mm) and 72" (1829mm) long shelves subject to the heaviest loads and frequent movement (multiple times daily).

