

Brake Lock/Swivel Lock Combination Casters — {11.37}

Patented, foot-operated design enables a single pair of casters to serve as swivel, rigid or brake casters. Conveniently positioned on the dolly, not on the wheels, the downward pressure pedals prevent scuffing of shoes.



- **Convenient.** Pedals are on the dolly, not the wheels, making operation more convenient. Downward pressure on the pedals save shoes from scuffing.
- **Castors.** Long wearing polyurethane. Resists abrasion. Non-marking, shock absorbing. Wheels are available in 6" (152mm) and 8" (203mm) size.
- **Recommended Caster Selection.** Two swivel casters at one end and brake/swivel lock set at the other end. Other caster combinations can be used, however, including brake/swivel lock sets at both ends. Wraparound bumper recommended.

Note: Aluminum dust covers and tow bar assemblies are not compatible with the Brake Lock/Swivel Lock Combination casters.




When "Rigid" is engaged the swivel casters will lock into the trailing position for easy steering of heavy loads over long distances. When "Swivel" is engaged the caster set swivels freely for easier maneuvering.



When the "Brake" pedal is engaged both of the BL casters are locked. The cart remains still for loading and unloading.

Type	Wheel Diameter (in.) (mm)		Face (in.) (mm)		For Use With	Load Rating (lbs.) (kg)		Weight (lbs.) (kg)		Cat. No.
*Brake/Lock	6	152	2	51	24" (610mm) Deep Dolly and 6P Caster	600	272	7 1/4	3.3	BL6P24
*Brake/Lock	8	203	2	51	24" (610mm) Deep Dolly and 8P Caster	600	272	9	4.1	BL8P24
Swivel	6	152	2	51	BL6P24 Brake/Lock Set	600	272	5 1/4	2.3	6P
Rigid	6	152	2	51	6P Swivel Caster	600	272	5	2.26	6PR
Swivel	8	203	2	51	BL8P24 Brake/Lock Set	600	272	6 1/2	2.9	8P
Rigid	8	203	2	51	8P Swivel Caster	600	272	6	2.7	8PR

Load Heights: ($\pm 1/16"$) (± 1.6 mm) 6P Series — $7 7/8"$ (200mm), 8P Series — $9 13/16"$ (249mm).



Push Handle



Extended Handle

Handles — {11.40}

Use on corresponding width Super Erecta units to provide additional maneuverability to dolly carts or stem caster carts. Aluminum split sleeves included for attaching to cart.

Push Handles				Extended Handles	
Length (in.) (mm)	Cat. No. Chrome	Cat. No. Stainless		Cat. No. Chrome	Cat. No. Stainless
14 355	PH14NC	PH14NS		EH14NC	EH14NS
18 457	PH18NC	PH18NS		EH18NC	EH18NS
21 530	PH21NC	PH21NS		EH21NC	EH21NS
24 610	PH24NC	PH24NS		EH24NC	EH24NS
30 760	PH30NC			EH30NC	
36 914	PH36NC			EH36NC	

Note: Handles fit unit widths only. Extended handles add 6" (152.4mm) to length of unit.