

MOBILE PAN RACKS



End-Load “Knock Down” Racks — Single Section — {13.70}

Width/Height/Depth (in.) (mm)		Inside Height (in.) (mm)		Slide Spacing (in.) (mm)		Pan Capacity Size (in.) (mm)		Approx. Pkd. Wt. (lbs.) (kg)		Cat. No.	
20.38x64.13x28	518x1630x711	55.88	1417	3	76	18	18x26	457x660	53	23.8	RT183N
				or 36		14x18	355x457				
20.38x64.13x28	518x1630x711	55.88	1417	5	127	11	18x26	457x660	50	22.5	RT115N
				or 22		14x18	355x457				
20.38x64.13x28	518x1630x711	55.88	1417	1.5	28	34	18x26	457x660	55	24.7	RT1334N

Note: 5" (127mm) swivel casters, two with brakes, are standard on units listed above.
Weight Load Capacity: 20 lbs. (9kg) per slide level; 300 lbs. (136kg) per unit. Allowable temperature range: -30°F (-34°C) to 160°F (71°C).



RT115N



RT3318N



Side-Load “Knock Down” Racks — {13.72}

Width/Height/Depth (in.) (mm)		Inside Height (in.) (mm)		Slide Spacing (in.) (mm)		Pan Capacity Size (in.) (mm)		Approx. Pkd. Wt. (lbs.) (kg)		Cat. No.	
28.38x64.13x18.75	721x1628x476	56.5	1435	3	76	18	18x26	457x660	40	18	RT3318N
28.38x64.13x18.75	721x1628x476	56.5	1435	5	127	11	18x26	457x660	38	17.1	RT3511N

Note: 5" (127mm) swivel casters, two with brakes, are standard on units listed above.
Weight Load Capacity: 20 lbs. (9kg) per slide level; 300 lbs. (136kg) per rack. Allowable temperature range: -30°F (-34°C) to 160°F (71°C).

Super Erecta Wire Pan Racks — {13.42}

- End-load models provide a large tray landing area, side-load models are highly space efficient.
- Choice of 1.5" (38mm) spacing (38 pans) or 3" (76mm) (20 pans) spacing.
- Quick, easy no-tool assembly, rolls easily on 5" (127mm) swivel casters.
- Durable Super Erecta Brite™ finish.
- All units are 69" (1752mm) high.

Width/Length (in.) (mm)		Slide Spacing (in.) (mm)		Pan Capacity Size (in.) (mm)		Approx. Pkd. Wt. (lbs.) (kg)		Description	Cat. No.	
21.75x27	552x685	1.5	38	38	18x26	457x660	61	27.7	End-Load	RE1
21.75x27	552x685	3	76	20	18x26	457x660	70	31.8	End-Load	RE3
19.5x30	495x762	1.5	38	38	18x26	457x660	61	27.6	Side-Load	RS1
19.5x30	495x762	3	76	20	18x26	457x660	70	31.8	Side-Load	RS3

Weight Load Capacity: 30 lbs. (13.6kg) per level; 200 lbs. (91kg) per rack.



Side Load

End Load



Super Erecta Portable Wire Prep Rack — {13.44}

Made to accommodate standard 18"x26" (457x660mm) trays or pans.

- The .5" (12.7mm) food grade polyethylene cutting board/work surface provides an area for slicing, mixing, garnishing or other types of food preparation.
- Rolls easily on 5" (127mm) swivel casters.
- Units assemble quickly and easily without special tools.

Width/Length (in.) (mm)		Height (in.) (mm)		Slide Spacing (in.) (mm)		Pan Capacity Size (in.) (mm)		Approx. Pkd. Wt. (lbs.) (kg)		Description	Cat. No.	
21.75x27	550x685	36	914	1.5	38	16	18x26	457x660	50	22.6	End-Load	RE1P
21.75x27	550x685	36	914	3	76	8	18x26	457x660	60	27.2	End-Load	RE3P



Portable Wire Prep Rack



Accessories for RE/RS Racks

Description	Model
3.5" (90mm) Diameter Rubber Donut Bumper	9992DB
5.5" (140mm) Diameter Rubber Donut Bumper	9992N