

## SAFETY DATA SHEET DST - GENERAL PURPOSE DUST REMOVER, AEROSOL

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification			
Product identifier			
Product name	DST - GENERAL PURPOSE DUST REMOVER, AEROSOL		
Product number	MCC-DST, MCC-DST36A, MCC-DSTZ, MCC-DST14A, MCC-DSTZ14, MCC-DST08A		
Synonyms; trade names	419-500, 758OZ134		
Recommended use of the ch	emical and restrictions on use		
Application	Cleaning agent.		
Details of the supplier of the s	safety data sheet		
Supplier	MICROCARE CORPORATION		
Manufacturer	MICROCARE CORPORATION 595 John Downey Drive New Britain, CT 06051 United States of America CAGE: OATV9 Tel: + 1 800 638 0125, +1 860-827-0626 Fax: +1 860-827-8105 techsupport@microcare.com		
Emergency telephone number	er de la constant de		
Emergency telephone numbe Emergency telephone	CHEMTREC 1-800-424-9300 (within the U.S.) +1 703-741-5970 (from anywhere in the world)		
	CHEMTREC 1-800-424-9300 (within the U.S.)		
Emergency telephone	CHEMTREC 1-800-424-9300 (within the U.S.) +1 703-741-5970 (from anywhere in the world)		
Emergency telephone 2. Hazard(s) identification	CHEMTREC 1-800-424-9300 (within the U.S.) +1 703-741-5970 (from anywhere in the world)		
Emergency telephone 2. Hazard(s) identification Classification of the substance	CHEMTREC 1-800-424-9300 (within the U.S.) +1 703-741-5970 (from anywhere in the world) e or mixture		
Emergency telephone 2. Hazard(s) identification Classification of the substance OSHA Regulatory Status	CHEMTREC 1-800-424-9300 (within the U.S.) +1 703-741-5970 (from anywhere in the world) e or mixture This Product is Hazardous under the OSHA Hazard Communication Standard.		
Emergency telephone 2. Hazard(s) identification Classification of the substance OSHA Regulatory Status Physical hazards	CHEMTREC 1-800-424-9300 (within the U.S.) +1 703-741-5970 (from anywhere in the world) e or mixture This Product is Hazardous under the OSHA Hazard Communication Standard. Press. Gas, Compressed - H280		
Emergency telephone 2. Hazard(s) identification Classification of the substance OSHA Regulatory Status Physical hazards Health hazards	CHEMTREC 1-800-424-9300 (within the U.S.) +1 703-741-5970 (from anywhere in the world) e or mixture This Product is Hazardous under the OSHA Hazard Communication Standard. Press. Gas, Compressed - H280 Not Classified		
Emergency telephone 2. Hazard(s) identification Classification of the substance OSHA Regulatory Status Physical hazards Health hazards Environmental hazards	CHEMTREC 1-800-424-9300 (within the U.S.) +1 703-741-5970 (from anywhere in the world) e or mixture This Product is Hazardous under the OSHA Hazard Communication Standard. Press. Gas, Compressed - H280 Not Classified Not Classified Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. Mild		

#### Pictogram



Signal word	Warning	
Hazard statements	H280 Contains gas under pressure; may explode if heated.	
Precautionary statements	P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P251 Pressurized container: Do not pierce or burn, even after use P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501 Dispose of contents/ container in accordance with local regulations.	
Supplemental label information	Safety data sheet available on request. For use in industrial installations only.	

### Other hazards

This product does not contain any substances classified as PBT or vPvB.

### 3. Composition/information on ingredients

Mixtures	
HFC-134a Tetrafluoroethane	60-100%
CAS number: 811-97-2	

## Classification Press. Gas, Liquefied - H280

The full text for all hazard statements is displayed in Section 16.

Composition comments	The exact percentage (concentration) of composition has been withheld as a trade secret in
	accordance with paragraph (i) of CFR 1900.1200 TSCA: The ingredients of this product are
	on the TSCA Inventory.

### Composition

4. First-aid measures

## Description of first aid measures

General information	Never give anything by mouth to an unconscious person. Do not induce vomiting. Place unconscious person on their side in the recovery position and ensure breathing can take place. If breathing stops, provide artificial respiration. Keep out of the reach of children.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.
Ingestion	Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Consult a physician for specific advice.
Skin Contact	Remove contaminated clothing and rinse skin thoroughly with water.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Consult a physician for specific advice.
Most important symptoms	and effects, both acute and delayed
General information	The severity of the symptoms described will vary dependent on the concentration and the

# eneral information The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation	Vapors may cause headache, fatigue, dizziness and nausea. Difficulty in breathing.	
Ingestion	Due to the physical nature of this material it is unlikely that swallowing will occur.	
Skin contact	No specific symptoms known.	
Eye contact	Prolonged contact may cause redness and/or tearing.	
Indication of immediate medica	al attention and special treatment needed	
Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.	
5. Fire-fighting measures		
Extinguishing media		
Suitable extinguishing media	The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.	
Special hazards arising from the	ne substance or mixture	
Specific hazards	Keep away from heat, sparks and open flame. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapors. Aerosol containers can explode when heated, due to excessive pressure build-up.	
Hazardous combustion products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors. Oxides of carbon. Oxides of nitrogen.	
Advice for firefighters		
Protective actions during firefighting	Move containers from fire area if it can be done without risk. Bursting aerosol containers may be propelled from a fire at high speed.	
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.	
	-	
6. Accidental release measure	-	
	-	
	S	
Personal precautions, protectiv	s /e equipment and emergency procedures Aerosol containers can explode when heated, due to excessive pressure build-up. Warn everybody of potential hazards and evacuate if necessary. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an	
Personal precautions, protectiv Personal precautions	s /e equipment and emergency procedures Aerosol containers can explode when heated, due to excessive pressure build-up. Warn everybody of potential hazards and evacuate if necessary. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an	
Personal precautions, protective Personal precautions	s re equipment and emergency procedures Aerosol containers can explode when heated, due to excessive pressure build-up. Warn everybody of potential hazards and evacuate if necessary. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Contain spillage with sand, earth or other suitable non-combustible material.	
Personal precautions, protective Personal precautions Environmental precautions Environmental precautions	s re equipment and emergency procedures Aerosol containers can explode when heated, due to excessive pressure build-up. Warn everybody of potential hazards and evacuate if necessary. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Contain spillage with sand, earth or other suitable non-combustible material.	
Personal precautions, protective Personal precautions Environmental precautions Environmental precautions Methods and material for contact	s re equipment and emergency procedures Aerosol containers can explode when heated, due to excessive pressure build-up. Warn everybody of potential hazards and evacuate if necessary. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Contain spillage with sand, earth or other suitable non-combustible material. ainment and cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames	
Personal precautions, protective Personal precautions Environmental precautions Environmental precautions Methods and material for contact Methods for cleaning up	s re equipment and emergency procedures Aerosol containers can explode when heated, due to excessive pressure build-up. Warn everybody of potential hazards and evacuate if necessary. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Contain spillage with sand, earth or other suitable non-combustible material. ainment and cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation.	
Personal precautions, protective Personal precautions Environmental precautions Environmental precautions Methods and material for conta Methods for cleaning up Reference to other sections	s re equipment and emergency procedures Aerosol containers can explode when heated, due to excessive pressure build-up. Warn everybody of potential hazards and evacuate if necessary. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Contain spillage with sand, earth or other suitable non-combustible material. ainment and cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation.	
Personal precautions, protective Personal precautions Environmental precautions Environmental precautions Methods and material for contact Methods for cleaning up Reference to other sections 7. Handling and storage	s re equipment and emergency procedures Aerosol containers can explode when heated, due to excessive pressure build-up. Warn everybody of potential hazards and evacuate if necessary. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level. Contain spillage with sand, earth or other suitable non-combustible material. <b>ainment and cleaning up</b> Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation.	

3/9

Storage precautions Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Specific end uses(s) Specific end use(s) The identified uses for this product are detailed in Section 1. Reference to other sections. Store away from incompatible materials (see Section 10).

### 8. Exposure Controls/personal protection

#### **Control parameters**

## Occupational exposure limits

### HFC-134a Tetrafluoroethane

Long-term exposure limit (8-hour TWA): OES 4240 mg/m<sup>3</sup>

### Additional Occupational **Exposure Limits**

#### Exposure controls

## Protective equipment

Appropriate engineering controls	No specific ventilation requirements. This product must not be handled in a confined space without adequate ventilation.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.
Other skin and body protection	Wear suitable protective clothing as protection against splashing or contamination.
Hygiene measures	No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products. When using do not eat, drink or smoke.
Respiratory protection	Vapors are heavier than air and may travel along the floor and accumulate in the bottom of containers. In confined or poorly-ventilated spaces, a supplied-air respirator must be worn. Wear self-contained breathing apparatus with full facepiece.

#### 9. Physical and Chemical Properties

#### Information on basic physical and chemical properties

Appearance	Liquefied gas
Color	Colorless.
Odor	Slight. Ether.
Odor threshold	No information available.
рН	No information available.
Melting point	No information available.
Initial boiling point and range	-26.1°C/-15.0°F @ 1013 hPa

Flash point	The product is not flammable.	
Evaporation rate	> 1 (CCL4 = 1.0)	
Evaporation factor	No information available.	
Flammability (solid, gas)	No information available.	
Upper/lower flammability or explosive limits	Upper flammable/explosive limit: n/a Lower flammable/explosive limit: n/a	
Other flammability	The product is not flammable.	
Vapor pressure	96 PSIA @ 20°C	
Vapor density	3.6 @ 25 C / 77 F	
Relative density	1.21 g/cm3 at 25 °C (77 °F) (as liquid)	
Bulk density	Not applicable.	
Solubility(ies)	Slightly soluble in water.	
Partition coefficient	No information available.	
Auto-ignition temperature	No information available.	
Decomposition Temperature	No information available.	
Viscosity	No information available.	
Explosive properties	No information available.	
Comments	Aerosol.	
Refractive index	Not determined.	
Particle size	Not applicable.	
Molecular weight	No information available.	
Volatility	100%	
Saturation concentration	No information available.	
Critical temperature	No information available.	
Volatile organic compound	Not applicable.	
10. Stability and reactivity		
Reactivity	There are no known reactivity hazards associated with this product.	
Stability	Stable at normal ambient temperatures and when used as recommended.	
Possibility of hazardous reactions	Will not polymerize.	
Conditions to avoid	Avoid exposing aerosol containers to high temperatures or direct sunlight. Keep away from heat, sparks and open flame. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapors.	
Materials to avoid	Alkali metals. Alkaline earth metals. Powdered metal.	

Hazardous products	decomposition	Heating may generate the following products: Toxic and corrosive gases or vapors. Halogenated hydrocarbons. Hydrogen fluoride (HF). Carbon monoxide (CO). Carbon dioxide (CO2).	
11. Toxicolo	11. Toxicological information		
Information	on toxicological ef	fects	
Other health	h effects	There is	no evidence that the product can cause cancer.
Inhalation		Vapors	irritate the respiratory system. May cause coughing and difficulties in breathing.
Ingestion	n May car intoxica		use stomach pain or vomiting. May cause nausea, headache, dizziness and tion.
Skin Contac			has a defatting effect on skin. May cause allergic contact eczema. Contact with liquid y cause frostbite.
Eye contact	t	Мау сал	use temporary eye irritation.
Toxicologica	al information on ir	ngredients	<u>-</u>
			HFC-134a Tetrafluoroethane
	Other health effe	ects	There is no evidence that the product can cause cancer.
	Acute toxicity - ir	halation	
	Acute toxicity inh (LC₅₀ gases ppm		567,000.0
	Species		Rat
	ATE inhalation (gases ppm)		567,000.0
	Inhalation		Vapors irritate the respiratory system. May cause coughing and difficulties in breathing.
	Ingestion		May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication.
	Skin Contact		May cause allergic contact eczema. Contact with liquid form may cause frostbite.
	Eye contact		May cause temporary eye irritation.
12. Ecologie	cal Information		
Ecotoxicity	There are no data on the ecotoxicity of this product.		

### Ecological information on ingredients.

### HFC-134a Tetrafluoroethane

Acute toxicity - fish	LC₅₀, 96 hours: 450 mg/l, Fish
Acute toxicity - aquatic invertebrates	EC₅₀, 48 hours: 980 mg/l, Daphnia magna

## Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Bioaccumulative potential			
Bio-Accumulative Potential	No data available on bioaccumulation.		
Partition coefficient	No information available.		
Ecological information on ingre	edients.		
	HFC-134a Tetrafluoroethane		
Partition coefficient Pow: 1.06			
Mobility in soil			
Mobility	The product contains volatile substances which may spread in the atmosphere.		
Other adverse effects			
Other adverse effects	The product contains a substance or substances that will contribute to global warming (greenhouse effect).		
13. Disposal considerations			
Waste treatment methods			
General information	Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.		
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.		
14. Transport information			
General	As supplied, this product is consigned under the Limited Quantities provisions. Requirements for marking and labeling of package varies depending on mode of transport. If uncertain of proper markings and labeling, call MicroCare for assistance.		
UN Number			
UN No. (IMDG)	1950		
UN No. (ICAO)	1950		
UN proper shipping name			
Proper shipping name (TDG)	LIMITED QUANTITY		
Proper shipping name (IMDG)	UN1950 AEROSOLS, NON-FLAMMABLE, 2.2, LIMITED QUANTITY		
Proper shipping name (ICAO)	UN1950 AEROSOLS, NON-FLAMMABLE, 2.2, LIMITED QUANTITY		
Proper shipping name (DOT)	LIMITED QUANTITY		
Transport hazard class(es)			
IMDG Class	2.2 LIMITED QUANTITY		
ICAO class/division	2.2 LIMITED QUANTITY		
Packing group			
ICAO packing group	Not Applicable		
Environmental hazards			
Environmentally Hazardous Substance No.			

Transport in bulk according to Not applicable. No information required. Annex II of MARPOL 73/78 and the IBC Code

#### 15. Regulatory information

#### **US Federal Regulations**

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities Not listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA) Not listed.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities Not listed.

SARA 313 Emission Reporting Not listed.

CAA Accidental Release Prevention Not listed.

SARA (311/312) Hazard Categories Pressure

OSHA Highly Hazardous Chemicals Not listed.

#### **US State Regulations**

California Proposition 65 Carcinogens and Reproductive Toxins Not listed.

California Air Toxics "Hot Spots" (A-I) Not listed.

California Air Toxics "Hot Spots" (A-II) Not listed.

California Directors List of Hazardous Substances Not listed.

Massachusetts "Right To Know" List Not listed.

Rhode Island "Right To Know" List Not listed.

Minnesota "Right To Know" List

*HFC-134a Tetrafluoroethane* Present.

New Jersey "Right To Know" List Not listed.

Pennsylvania "Right To Know" List Not listed.

#### Inventories

**Canada - DSL/NDSL** Yes

#### US - TSCA

*HFC-134a Tetrafluoroethane* Present.

16. Other information	
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	11/14/2017
Revision	62
Supersedes date	10/6/2017
SDS No.	AEROSOL - DST
SDS status	Approved.
Hazard statements in full	H280 Contains gas under pressure; may explode if heated.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.