

SAFETY DATA SHEET

CDIW - STENCIL, SQUEEGEE and MISPRINT CLEANER PRESATURATED WIPES

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification

Product identifier

Product name CDIW - STENCIL, SQUEEGEE and MISPRINT CLEANER PRESATURATED WIPES

Product number MCC-CDIW, MCC-CDIWR

Synonyms; trade names CDIW-ScreenClean Solvent Presaturated Wipes"; "CDIWR-ScreenClean Solvent

Presaturated Wipes, Refill"

Recommended use of the chemical and restrictions on use

Application Cleaning agent.

Details of the supplier of the safety data sheet

Supplier MICROCARE CORPORATION

Manufacturer MICROCARE CORPORATION

595 John Downey Drive New Britain, CT 06051 United States of America

CAGE: OATV9

Tel: +1 860-827-0626 Fax: +1 860-827-8105 techsupport@microcare.com

Emergency telephone number

Emergency telephone CHEMTREC 1-800-424-9300 (within the U.S.)

+1 703-741-5970 (from anywhere in the world)

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Flam. Liq. 3 - H226

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2A - H319

Label elements

Pictogram





Signal word Warning

Hazard statements H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary statements P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.

P302+P352 If on skin: Wash with plenty of water.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

Supplemental label

information

Safety data sheet available on request. For use in industrial installations only.

Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

3. Composition/information on ingredients

Mixtures

1-propoxypropan-2-ol 60-100%

CAS number: 1569-01-3

Classification

Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319

D.I. WATER 30-60%

CAS number: 7732-18-5

Classification

Not Classified

ETHYL ACETATE 1-5%

CAS number: 141-78-6

Classification

Flam. Liq. 2 - H225 Eye Irrit. 2A - H319 STOT SE 3 - H336

PROPAN-2-OL 1-5%

CAS number: 67-63-0

Classification

Flam. Liq. 2 - H225 Eye Irrit. 2A - H319 STOT SE 3 - H336

The full text for all hazard statements is displayed in Section 16.

Composition comments

TSCA: The ingredients of this product are on the TSCA Inventory. The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of CFR 1900.1200

Composition

4. First-aid measures

Description of first aid measures

General information Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation Move affected person to fresh air at once. When breathing is difficult, properly trained

personnel may assist affected person by administering oxygen. Keep affected person warm

and at rest. Get medical attention immediately.

Ingestion Due to the physical nature of this material it is unlikely that swallowing will occur. Do not

induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Never give

anything by mouth to an unconscious person. Consult a physician for specific advice.

Skin Contact Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort

continues

Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Vapours may cause drowsiness and dizziness. Headache. Irritation of nose, throat and

airway.

Ingestion Due to the physical nature of this material it is unlikely that swallowing will occur. Ingestion of

large amounts may cause unconsciousness. May cause nausea, headache, dizziness and

intoxication.

Skin contact Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. May

cause skin irritation/eczema.

Eye contact May cause temporary eye irritation. Irritating to eyes. Symptoms following overexposure may

include the following: Redness. Pain.

Indication of immediate medical attention and special treatment needed

Notes for the doctor

No specific recommendations. If in doubt, get medical attention promptly.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray,

fog or mist.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards Materials such as cleaning rags and paper wipes that are contaminated with flammable liquids

may self-ignite after use and should be stored in designated fireproof containers with tight-

fitting, self-closing lids.

Hazardous combustion

products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or

vapors. Oxides of carbon.

Advice for firefighters

Protective actions during

firefighting

Containers close to fire should be removed or cooled with water. Use water to keep fire

exposed containers cool and disperse vapors.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

......

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots,

clothing or apron, as appropriate. No smoking, sparks, flames or other sources of ignition near

spillage. Provide adequate ventilation.

Environmental precautions

Environmental precautions Avoid release to the environment. Do not discharge into drains or watercourses or onto the

ground. Contain spillage with sand, earth or other suitable non-combustible material.

Methods and material for containment and cleaning up

Methods for cleaning up Warn everybody of potential hazards and evacuate if necessary. If leakage cannot be

stopped, evacuate area. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate

ventilation. Contain and absorb spillage with sand, earth or other non-combustible material.

Collect and place in suitable waste disposal containers and seal securely.

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health

hazards.

7. Handling and storage

Precautions for safe handling

Usage precautionsDo not eat, drink or smoke when using the product. Keep away from heat, sparks and open

flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable

level.

Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep

container tightly closed. Keep away from heat, sparks and open flame.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

Reference to other sections. Store away from incompatible materials (see Section 10).

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

ETHYL ACETATE

Long-term exposure limit (8-hour TWA): OSHA 400 ppm 1400 mg/m³ Long-term exposure limit (8-hour TWA): ACGIH 400 ppm 1440 mg/m³

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): OSHA 400 ppm 980 mg/m³ Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 492 mg/m³ Short-term exposure limit (15-minute): ACGIH 400 ppm 984 mg/m³

A4

OSHA = Occupational Safety and Health Administration.

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

Additional Occupational

Exposure Limits

Ingredient comments WEL = Workplace Exposure Limits

Exposure controls

Protective equipment





Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Avoid heat, flames and other sources

of ignition.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl alcohol (PVA). Viton rubber (fluoro rubber). It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

Other skin and body protection

Not considered to be a significant hazard due to the small quantities used.

Hygiene measures

Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

Respiratory protection

No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Clear liquid.

Color Colorless.

Odor Alcoholic.

Odor threshold No information available.

PH No information available.

Melting point Not applicable.

Initial boiling point and range 120°C/249°F @ 101.3 kPa

Flash point 48.9°C/120°F TCC (Tag closed cup).

Evaporation rate

No information available.

Evaporation factor

No information available.

Flammability (solid, gas)

No information available.

Upper/lower flammability or

explosive limits

Upper flammable/explosive limit: N/D Lower flammable/explosive limit: N/D

Vapor pressure 0.23 kPa @ 25°C

Vapor density 4.0

Relative density 0.97

Bulk density

Not applicable.

Solubility(ies)

Soluble in water.

Partition coefficient

No information available.

Auto-ignition temperature

No information available.

Decomposition Temperature

No information available.

Viscosity Not applicable.

Explosive properties No information available.

Oxidizing properties There are no chemical groups present in the product that are associated with oxidizing

properties.

Comments Information given is applicable to the major ingredient.

Refractive index Not applicable.

Particle size Not applicable.

Molecular weight Not applicable.

Volatility 100%

Saturation concentration No information available.

Critical temperature Not applicable.

Volatile organic compound This product contains a maximum VOC content of 785 g/l.

10. Stability and reactivity

Reactivity There are no known reactivity hazards associated with this product.

Stability Stable at normal ambient temperatures.

Possibility of hazardous

reactions

Will not polymerize.

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:

Strong oxidizing agents. Strong alkalis. Strong mineral acids.

Materials to avoid Strong oxidizing agents.

Hazardous decomposition

products

Fire creates: Vapors/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

11. Toxicological information

Information on toxicological effects

Other health effects There is no evidence that the product can cause cancer.

Inhalation May cause respiratory system irritation. Vapors may cause headache, fatigue, dizziness and

nausea. Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion Not considered to be a significant hazard due to the small quantities used.

Skin Contact Product has a defatting effect on skin. May cause skin irritation/eczema.

Eye contact Irritating to eyes. Liquid, aerosols and vapors of this product are irritating and can cause pain,

tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that

of fine dust in the eyes.

5.800.0

Acute and chronic health

hazards

Keep out of the reach of children.

Toxicological information on ingredients.

PROPAN-2-OL

Acute toxicity - oral

Acute toxicity oral (LD50

mg/kg)

Species Rat

ATE oral (mg/kg) 5,800.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 13,000.0

mg/kg)

Species Rabbit

ATE dermal (mg/kg) 13,000.0

Acute toxicity - inhalation

Acute toxicity inhalation

(LC₅₀ vapours mg/l)

16,000.0

Species Rat

ATE inhalation (vapours

mg/l)

16,000.0

Carcinogenicity

IARC Group 3 Not classifiable as to its carcinogenicity to humans.

NTP carcinogenicity Not listed.

OSHA Carcinogenicity Not listed.

12. Ecological Information

Ecotoxicity There are no data on the ecotoxicity of this product.

Ecological information on ingredients.

Revision date: 6/6/2017 Revision: 22 Supersedes date: 3/9/2017

CDIW - STENCIL, SQUEEGEE and MISPRINT CLEANER PRESATURATED WIPES

PROPAN-2-OL

Acute toxicity - fish LC₅₀, 96 hours: 9,640 mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 5102 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

IC₅₀, 72 hours: >2,000 mg/l, Algae

Persistence and degradability

Persistence and degradability The product contains mainly inorganic substances which are not biodegradable. The other

substances in the product are expected to be readily biodegradable.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient No information available.

Ecological information on ingredients.

PROPAN-2-OL

Partition coefficient : 0.05

Mobility in soil

Mobility The product is soluble in water.

Other adverse effects

Other adverse effects The product contains volatile organic compounds (VOCs) which have a photochemical ozone

creation potential.

13. Disposal considerations

Waste treatment methods

General information Materials such as cleaning rags and paper wipes that are contaminated with flammable liquids

may self-ignite after use and should be stored in designated fireproof containers with tight-fitting, self-closing lids. Waste packaging should be collected for reuse or recycling. Reuse or

recycle products wherever possible.

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

14. Transport information

General Requirements for marking and labeling of package varies depending on mode of transport. If

uncertain of proper markings and labeling, call MicroCare for assistance. As supplied, this

product is consigned under the Limited Quantities provisions.

DOT transport notes As supplied, this product is consigned under the Limited Quantities provisions.

UN Number

UN No. (IMDG) UN3175

UN No. (ICAO) ID8000

UN proper shipping name

Proper shipping name (TDG) LIMITED QUANTITY

Proper shipping name (IMDG) UN3175, Solids Containing Flammable Liquid, N.O.S. (Glycol Ethers, Isopropanol), 4.1, PGII,

Limited Quantity

Proper shipping name (ICAO) ID8000, Consumer Commodity, 9, Limited Quantity

Proper shipping name (DOT) LIMITED QUANTITY

Transport hazard class(es)

IMDG Class 4.1

ICAO class/division ID8000, Consumer Commodity, 9, Limited Quantity

Packing group

IMDG packing group Ш

Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

EmS F-A, S-I

15. Regulatory information

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

Not listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

ETHYL ACETATE

Final CERCLA RQ: 5000(2270) pounds (Kilograms)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

Not listed.

SARA 313 Emission Reporting

Not listed.

CAA Accidental Release Prevention

Not listed.

SARA (311/312) Hazard Categories

Acute Fire

OSHA Highly Hazardous Chemicals

Not listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

Not listed.

California Air Toxics "Hot Spots" (A-I)

PROPAN-2-OL

Present.

California Air Toxics "Hot Spots" (A-II)

Not listed.

California Directors List of Hazardous Substances

ETHYL ACETATE

Present.

PROPAN-2-OL

Present.

Massachusetts "Right To Know" List

ETHYL ACETATE

Present.

PROPAN-2-OL

Present.

Rhode Island "Right To Know" List

ETHYL ACETATE

Present.

PROPAN-2-OL

Present.

Minnesota "Right To Know" List

ETHYL ACETATE

Present.

PROPAN-2-OL

Present.

New Jersey "Right To Know" List

ETHYL ACETATE

Present.

PROPAN-2-OL

Present.

Pennsylvania "Right To Know" List

ETHYL ACETATE

Present.

PROPAN-2-OL

Present.

Inventories

Canada - DSL/NDSL

1-propoxypropan-2-ol

DSL

D.I. WATER

Domestic Substance List

ETHYL ACETATE

DSL

PROPAN-2-OL

DSL

US - TSCA

Yes

16. Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 6/6/2017

Revision 22

Supersedes date 3/9/2017

SDS No. PRESAT - CDIW

SDS status Approved.

Hazard statements in full H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.