

MimioView

High-resolution pictures and live video can really engage students and drive home a lesson. And your teachers can do it with plug-and-play simplicity. They take the document camera out of the box, attach a single cord, and it's ready to go. Teachers don't have to learn additional programs because it automatically integrates with MimioStudio™ classroom software, and that means students can begin their learning immediately.

"I love that the teacher or students can mark up a LIVE picture at the whiteboard..."

Cameron Nichols Elementary School Teacher Take all the wonder of interactive lessons and activities and launch them even further by adding pictures or live video. This is the most user-friendly document camera available. No tangle of wires or endless cords to plug in. One USB plug does it all.

The MimioView[™] document camera also automatically integrates with MimioStudio software and instantly captures high-resolution pictures and live video. Teachers can display, freeze, annotate and save.

- Plug into a single USB computer port for both power and data.
- No external power sources or wall cords.
- Autofocus by pushing a single button.
- Capture both dimensional objects and flat documents.
- Two adjustable light sources.
- Save work by easily annotating images and creating files to use over and over.
- Enjoy exceptional detail with highresolution 1600 x 1200 imaging.



Zoom or show an angle view, with the convenient gooseneck arm.



205 Westwood Ave, Long Branch, NJ 07740 Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 | E-mail: sales@touchboards.com



Specifications

Package Contents

2M Micron camera, microscope adapter, 2 adjustable LED light sources, flexible gooseneck, "micro-B" USB connector (3 m/10 ft), 1 DVD containing MimioStudio classroom software.

Specifications

Minimum Software

Requirements

MimioStudio 7 and higher on a Windows, Mac, or Linux OS.

For specific system requirements, please visit us at: mimio.com/support/downloads

Output Resolution

UXGA (1600 x 1200)

Sensor Pixel

2M Micron

Input/Output

USB 2.0 High Speed only

Operation

Single USB cable

Zoom

5.5x mechanical zoom,16x digital zoom

Lighting

Adjustable LED lighting (x2)

Shooting Area

420 mm x 315 mm when height is 360 mm (16.5 in. x 12.4 in.)

Driver Interface

UVC

User Input

4 Buttons: View, Auto Tune, Rotate and Freeze

Image Rotation

90-degree increments (CW/CCW)

Macro

Microscope adapter

Overall Weight

1.25 kg (2.8 lb)

Footprint Dimensions

12.7 cm x 14 cm (5 in. x 5.5 in.)

Operating Temperature

5°C to 35°C (41°F to 95°F)

Storage Temperature

-20°C to 55°C (-4°F to 131°F)

Focus

Automatic

Colour Balance

Automatic

Video and Images

Save to MimioStudio Gallery

Content Alignment

Straightedge incorporated on base

Camera Adjustment

Flexible gooseneck for camera

Certification & Compliance

Safety & EMC: FCC (U.S.), IC (Canada), CE (Europe), GOST-R (Russia), VCCI (Japan), C-tick (Australia/New Zealand), KCC (Korea), CQC (China). Environmental: RoHS, WEEE.

Warranty and Support

Mimio hardware is warranted for 2 years from date of purchase, with an additional 3 years with product registration at mimio.com/warranty, for a total of 5 years. MimioStudio software is supplied with a limited lifetime warranty, expiring 1 year after discontinuation of the product.

