

MU-53HN Uni-Directional Headworn Microphones

Touchboards

205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com

Key Features

- Uni-directional pick-up pattern.
- Visually unobtrusive and comfortable to wear.
- Flexible and durable frame with comfortable, soft ear hooks which require no adjustment for optimum comfort.
- Interchangeable MU-53M uni-directional capsule module and MU-55M subminiature waterproof omni-directional capsule module.
- Featuring a high dynamic range and able to withstand a maximum SPL without distortion.
- Capsule module and cable are easily detached from the frame and can be worn on the left or right side of the frame to suit personal preferences.
- The very thin capsule-shaft mount is fully rotatable.
- The capsule-shaft allows for adjustments in length, direction and angle for precise and optimum capsule positioning in relation to the speakers mouth.
- Patented, swiveling earhook design allows for inward rotation, facilitating easy storage, packaging and carriage.
- Available in black and beige colors.
- Flexible gooseneck.
- Supplied as standard with MIPRO's mini XLR plug.
- Features a smooth, warm, natural sound.
- Fold-flat design for easy storage.

Technical Specifications

Capsule Module	10 mm Ø uni-directional cardioid condenser microphone
Frequency Response	50 Hz – 18 kHz ± 3 dB
Capsule Impedance	200 Ω
Sensitivity	-46 dBV ± 3 dBV / Pa (0 dB = 1 V / Pa)
Maximum SPL	125dB (typical, 1%T.H.D.)
Capsule-shaft holder	Dual - left and right side
Plug	MIPRO's mini-XLR 4-pin plug or TA4F
Cable Length	150 cm / 59.1 "
Color	Black or Beige color
Weight	30 g / 1.1 oz

