
MeasurLink® ENABLED

Angle Index (Standard Accessory)



TM **SERIES 176 — Toolmakers' Microscopes**

- Compact universal toolmakers' microscope that can be installed on any site.
- Newly designed LED illuminators provide enhanced observation for higher accuracy and resolution.
- Optional LED circular illuminator available for applications requiring all-round lighting.
- Achieves a maximum measuring height of 115 mm despite the compact size.
- Installation of Digimatic micrometer heads (164-163, optional) makes measurement easy and precise.
- A vernier scale (Angle Index) built into the eyepiece mount enables accurate angular measurements.
- Lenses are available for a wide range of magnifications (20X to 200X in total).





Note: Micrometer heads are optional.

SPECIFICATIONS

Model No.		TM-505B	TM-1005B
Order No.		176-818	176-819
Optical tube		Monocular type (Vertical tilt angle: 30°)	
Observation image		Erect	
Eyepiece protractor		Resolution (graduation): 1°, Rotation angle: 360°, Resolution (angle): 6', Adjustable zero point	
Eyepiece		Standard accessory: 15X (field number: 13), Options: 10X, 20X	
Objective		Standard accessory: 2X, Optional: 5X, 10X	
Microscope head	Maximum height of workpiece	115 mm	107 mm
	Focusing method	Manual (Coarse feed)	
Illumination unit	Transmitted illumination	Stepless brightness adjustment, White LED light source with green filter	
	Reflected illumination	Oblique single-source type, Stepless brightness adjustment, White LED light source	
Cross-travel stage	Measuring range	50×50 mm	100×50 mm (An optional 50 mm gauge block is required to cover full range. A CERA block is recommended.)
	Table size	152×152 mm	240×152 mm
	Usable area of the stage glass	96×96 mm	154×96 mm
	Maximum stage glass loading	5 kg	
Linear measurement method		Micrometer head*	
Resolution		Depends on the micrometer head specifications* (for 164-163 : 0.001 mm)	
Micrometer head travel range		For 164-163 : 50 mm	
Power supply		AC100 to 240 V 50/60 Hz Maximum power consumption: 4.2 W	
Main unit mass		14 kg	15 kg
* Micrometer heads are optional for TM-505R and TM-1005R			

* Micrometer heads are optional for **TM-505B** and **TM-1005B**.

Note: The main unit with Digimatic micrometer head (**164-164**) is provided in the **TM** Series. **TM-A505B** (**176-820A**)

TM-A1005B (176-821A)
Other specifications are the same as the other TM Series.





Refer to the **TM** Series Brochure (E14013) for more details.