Optional Accessories SERIES 544 — Laser Scan Micrometer (Display Unit)

Digimatic code output unit

- 2-channel Digimatic code output
- In simultaneous measurement, measurement data are output as follows: Program No. 0 to No. 4 in OUTPUT-1 Program No. 5 to No. 9 in OUTPUT-2 (10 programs operated)
- 10 pin MIL type connector.
- Output cable is not supplied. Connecting cable (optional) 1 m (**936937**)
- Available for **LSM-6200** (**544-071**, **544-072**) and **LSM-6902H** (**544-498-1**, **544-499-1**).

Note 1: Output is 6 digits of measurement data.


Note 2: Displaying 6th and 7th digit after the decimal point is not supported.




SPECIFICATIONS

Order No. **02AGC840**

XY Measurement



Parallel Measurement



Dual connection unit

• Enables second unit connection to **LSM-6200** (**544-071**, **544-072**). (both units must be the same model)

Note: Cannot be used for **LSM-6902H** (**544-498-1**, **544-499-1**).

- Depending on the layout of the two measuring units, large-diameter measurement, XY measurement, and parallel measurement are possible.
- Both of the measuring units and display units can be simultaneously operated.



Order No.	02AGP150

2nd I/O analog I/F

- I/O, analog output.
- Simultaneous measurement is supported by two pairs of GO/NG judgment outputs.
- Available for LSM-6200 (544-071, 544-072) and LSM-6902H (544-498-1, 544-499-1).

SPECIFICATIONS

Order No.	02AGC880
Standard Accessories	Connector (DDK) 57-30360 (214188)

Cable for BCD and 2nd I/O simultaneous mount


Both BCD (02AGC910) and 2nd I/O analog I/F (02AGC880) can be mounted on LSM-6200 (544-071, 544-072) and LSM-6902H (544-498-1, 544-499-1) using this cable.

Note: If using this cable, the dual connection unit (**02AGP150**) cannot be used.

CDI	FICA	TIO	NIC
)FI	ICA		IND

Order No.	02AGE060
-----------	----------

DIMENSIONS



Unit: mm

