
■ Major specifications of USB Input Tool Direct

- Output specifications: Mass: 59 g USB 2.0 or 1.1

 - USB 2.0 certification
- Power supply: USB bus power
- Communication speed: obtained
- 12 Mbps (full speed) Complies with the EU **EMC** Directive



Note: It is recommended to use a commercially available USB hub that has USB certification.

■ USB-ITPAK usage environment

| | ge |
|-----------------------------|--|
| Supported operating systems | Windows 2000 SP4, Windows XP SP2 or later, Windows Vista, Windows 7, 8 and 10 |
| Supported Excel versions | Excel 2000, 2002, 2003, 2007 and 2013 |
| Hard disk | At least 20 MB of free space (required for installation) |
| CD-ROM drive | Required for installation |
| USB ports | At least two ports (for the USB dongle and USB-ITN) |
| Resolution | At least 800 x 600 pixels, and at least 256 displayable colors |

 \bullet The natural language selected in USB-ITPAK must be the same as that used in the operating system.

■ Codes for the main measuring instruments classified according to the USB Input Tool Direct code, part number, and plug type

Determine the plug type suitable for your measuring instrument (one of the seven types from A to G) in the following table, and then select the corresponding USB Input Tool Direct.

| Model | USB-ITN-A | USB-ITN-B | USB-ITN-C | from A to G) in the foll | USB-ITN-E | USB-ITN-F | USB-ITN-G |
|---|---|---|---|--|---|--|---|
| Order No. | 06AFM380A | 06AFM380B | 06AFM380C | 06AFM380D | 06AFM380E | 06AFM380F | 06AFM380G |
| Whether the existence of a data switch affects usability | e Incorporates a data switch, so the tool is usable regardless of whether or not the measuring instrument has a switch. | | | Does not incorporate a data switch, so an instrument fitted with a switch is required in order to use the instrument alone. (However, the tool can be used with USB-ITPAK.) | | | |
| Cable type | A Water-proof with switch | B Water-proof with switch | C With switch | D 10-pin plain | E 6-pin round | F Straight type | G Water-proof straight type |
| Illustration of the plug that connects to the measuring instrument | Data Switch | Data switch | Data switch | | | | |
| Socket type on the measuring instrument | - | 9 | - | the | | - | TOT : |
| Codes of major compatible measuring instruments | /Super Caliper] -500 series CD67-S_PM CD-PMX/PM/GM -550/551 series CDC-P_PMX CDN-P_PMX [Digimatic Carbon Fiber Caliper] -552 series CFC-G/GL/GC/GU [Digimatic Depth Gage] -571 series VDS-PMX Digimatic Scale Unit] -572 series SD-G [Digimatic Micrometer] (Tiber Caliper) -337 series IMJ-MJ [Digimatic Microme Head] -350 series MHN-MB/MJB/MJN [Digimatic Exclusive Micrometer] (The end of the mark is MJ/MJB/M/MB/PM/PM | -293series MDC-MJ/MJB/MJT MDE-MJ [Tubular Inside Micrometer] -337 series IMZ-MJ -339 series IMJ-MJ [Digimatic Micrometer Head] -350 series MHN-MB/MJB/MJNB [Digimatic Exclusive Micrometer] (The end of the mark is- MJ/MJB/M/MB/PM/PMB [Digimatic Holtest] -468 series | Micrometer Head] -164 series MJT MB [Digimatic Caliper] -500 series CD-CX/C/S_C -550/ 551 CDC-C/CX, CDN-C/CX [Digimatic Depth Gage] -571 series VDS-DCX/DC [Digimatic Scale Unit] -572 series SD-D/SDV-D [Digimatic Exclusive Caliper] -573 series The end of the | [Surface Roughness Tester] -178 series SJ-201/210/301/ 400/500 [Coating Thickness Gage] -179 series DGE-745/755 [Linear Height] -518 series QMH-S [Reference Gage] -515 series HMD-C [Digimatic Indicator] -543 series ID-H [Laser Scan Micrometer] -544 series LSM-9506/6100/ 6200/6900 [µ-checker] Digital µ-checker (Using the foot switch) | [Digimatic Micrometer] -121 series BD -164 series MHD-M -227 series CLM -293 series MDQ-M MDC-M [Tubular Inside Micrometer] -337 series IMJ-M [Tubular Inside Micrometer] -339 series IMJ-M [Digimatic Holtest] -468 series HTD [Reference Gage] -515 series HME-DM [Borematic] -568 series SBM-C [Hardness Testing Machines] -810 series HM-100/200 HV-100/HH-411 HR-500 | that incorporate a data [Digimatic Height Gage] -192/570/574 series HDM-A/AX, HD-A/AX HDS-H_C/C HDF-N [Digimatic Caliper] -500/550/551 series CD/CDC/CDN [Digimatic Bore Gage] -511 series CG-D [Digimatic Indicator] -543 seires ID-C_X/_RB/_GB [Digimatic Depth Gage/ Digimatic Thickness Gage] -547 series Digimatic Thickness Gage] -552 series CFC-P/-L/-C/-U [Digimatic Scale Unit] -572 series SD-E, SDV-E SD-F, SDV-F SD-F, SDV-F SD-F, STOV-F STON-F STON | [Digimatic Indicator] -543 series ID-N ID-B |
| | | | | Measur [Digimatic Indicator] -543 series ID-F [Linear Gage/Counter] -542 series EF-PRH/ZR, EH-P/Z/S/D EB-P/Z/D EC-D [Litematic] -318 series VL-A/AS/AH | | that do not have a dat [Digimatic Indicator] -543 series ID-C/S/C_A [Digimatic Depth Gage/ Digimatic Thickness Gage] -547 series Digimatic model (ID-C) -575 series ID-U | No corresponding models |

