

# SPC Connecting Cables

- These cables are used to output measurement data from the digimatic gage with the output feature to the digimatic mini processor, digimatic display unit, multiplexer or other device.
- Cables of one or two meters are available.
- Note that the shape of connector differs depending on the model.

Input plug to Data Processor		
Order No.		Applicable gages
Straight type <b>905338</b> : 1m (40") <b>905409</b> : 2m (80")		<b>ALL CALIPERS WITHOUT ABSOLUTE ENCODER</b> Height Gage <b>570-2XX, 192-6XX, 192-67X</b> Indicators <b>575-XXX, 543-6XX, 543-2XX, 543-4XX</b> Depth Gages <b>547-21X, 547-25X, 571-2XX</b> Scale Unit <b>572-XXX</b> Thickness Gages <b>547-3XX, 547-4XX</b>
Back type <b>905689</b> : 1m (40") <b>905690</b> : 2m (80")		
Right type <b>905691</b> : 1m (40") <b>905692</b> : 2m (80")		
Left type <b>905693</b> : 1m (40") <b>905694</b> : 2m (80")		
With data out switch type <b>959149</b> : 1m (40") <b>959150</b> : 2m (80") <b>04AZB512</b> : 1m (40") L-Type <b>04AZB513</b> : 2m (80") L-Type		
With data out switch type <b>05CZA624</b> : 1m (40") <b>05CZA625</b> : 2m (80")		
With data out switch type <b>05CZA662</b> : 1m (40") <b>05CZA663</b> : 2m (80")		
6 pins type <b>937387</b> : 1m (40") <b>965013</b> : 2m (80")		
10 pins type <b>936937</b> : 1m (40") <b>965014</b> : 2m (80")		
Flat straight type <b>21EAA194</b> : SPC cable (40" / 1m) <b>21EAA190</b> : SPC cable (80" / 2m)		