




# SPC Connecting Cables

- These cables are used to output measurement data from the digimatic gage with the output feature to the digimatic mini processor, digimatic display unit, multiplexer or other device.
- Cables of one or two meters are available.
- Note that the shape of connector differs depending on the model.

Input plug to Data Processor		
Order No.		Applicable gages
Straight type <b>905338</b> : 1m (40") <b>905409</b> : 2m (80")		<b>ALL CALIPERS WITHOUT ABSOLUTE ENCODER</b> Height Gage <b>570-2XX, 192-6XX, 192-67X</b> Indicators <b>575-XXX, 543-6XX, 543-2XX, 543-4XX</b> Depth Gages <b>547-21X, 547-25X, 571-2XX</b> Scale Unit <b>572-XXX</b> Thickness Gages <b>547-3XX, 547-4XX</b>
Back type <b>905689</b> : 1m (40") <b>905690</b> : 2m (80")		
Right type <b>905691</b> : 1m (40") <b>905692</b> : 2m (80")		
Left type <b>905693</b> : 1m (40") <b>905694</b> : 2m (80")		
With data out switch type <b>959149</b> : 1m (40") <b>959150</b> : 2m (80") <b>04AZB512</b> : 1m (40") L-Type <b>04AZB513</b> : 2m (80") L-Type		
With data out switch type <b>05CZA624</b> : 1m (40") <b>05CZA625</b> : 2m (80")		
With data out switch type <b>05CZA662</b> : 1m (40") <b>05CZA663</b> : 2m (80")		
6 pins type <b>937387</b> : 1m (40") <b>965013</b> : 2m (80")		
10 pins type <b>936937</b> : 1m (40") <b>965014</b> : 2m (80")		
Flat straight type <b>21EAA194</b> : SPC cable (40" / 1m) <b>21EAA190</b> : SPC cable (80" / 2m)		
		Coolant-Proof Caliper <b>500-68X, 500-76X, 500-78X.</b> Coolant-Proof Digimatic scale units <b>572-61X.</b>
		<b>Digimatic Micrometer IP65</b>
		<b>ALL MICROMETERS (not for IP65 mics)</b> Indicators <b>543-11X, 543-13X, 543-14X, 543-18X, 543-17X</b> Holtest <b>468-2XX, 468-9XX</b> Micrometer Head <b>164-162, 164-172, 350-71X, 329-71X</b> Borematics <b>568-XXX</b> Others Mikematic, Quickmike Bench Mike <b>121-XXX</b>
		Indicators <b>543-5XX</b> MU-Checkers <b>519-4XX, 519-621A</b> MU-Gages <b>179-204, 179-205, 179-206</b> Display <b>542-022-5A, 542-032-5A, 542-036-5A</b> Display <b>572-011A, 572-031A</b> Linear Height <b>518-3XX</b> Litematic <b>318-2XX</b> Heightmatic <b>57X SERIES.</b> Digi Derm <b>179-7XX</b> Hardness Tester ( <b>Micro Hardness Type</b> )
		<b>ID-WID-B coolant proof digimatic Indicators</b>