



SPC Connecting Cables

- These cables are used to output measurement data from the digimatic gage with the output feature to the digimatic mini processor, digimatic display unit, multiplexer or other device.
- Cables of one or two meters are available.
- Note that the shape of connector differs depending on the model.

Input plug to Data Processor		
Order No.		Applicable gages
Straight type 905338 : 1m (40") 905409 : 2m (80")		ALL CALIPERS WITHOUT ABSOLUTE ENCODER Height Gage 570-2XX, 192-6XX, 192-67X Indicators 575-XXX, 543-6XX, 543-2XX, 543-4XX Depth Gages 547-21X, 547-25X, 571-2XX Scale Unit 572-XXX Thickness Gages 547-3XX, 547-4XX
Back type 905689 : 1m (40") 905690 : 2m (80")		
Right type 905691 : 1m (40") 905692 : 2m (80")		
Left type 905693 : 1m (40") 905694 : 2m (80")		
With data out switch type 959149 : 1m (40") 959150 : 2m (80") 04AZB512 : 1m (40") L-Type 04AZB513 : 2m (80") L-Type		
With data out switch type 05CZA624 : 1m (40") 05CZA625 : 2m (80")		
With data out switch type 05CZA662 : 1m (40") 05CZA663 : 2m (80")		
6 pins type 937387 : 1m (40") 965013 : 2m (80")		
10 pins type 936937 : 1m (40") 965014 : 2m (80")		
Flat straight type 21EAA194 : SPC cable (40" / 1m) 21EAA190 : SPC cable (80" / 2m)		