

Optional Accessories

Order No.	Type	Description
02AZE140A	A	Connecting cables for U-WAVE-T For foot switch
264-620	IP67	U-WAVE-TC
264-621	Buzzer	U-WAVE-TC
264-624	IP67	U-WAVE-TCB Transmitter
264-625	Buzzer	U-WAVE-TCB Transmitter
02AZF310	IP67	Connecting unit for U-WAVE-TC/TCB

Depth Gauge SERIES 571 — Pin End Type

- Coolant proof models achieve IP67 protection level.
- Optional longer extension bases are available. (Refer to page D-76.)
- Allows integration into statistical process control and measurement systems for models with measurement data output connector. (Refer to page A-3.)



571-302-20

SPECIFICATIONS

Metric				
Order No.	Range (mm): L1 (L2 and L3)	Resolution (mm)	Base (W×T) (mm)	Maximum permissible error <i>E_{MPE}</i> (mm)*
571-301-20	0 - 150	0.01	100×6	±0.02
571-302-20	0 - 200			
Inch / Metric				
Order No.	Range: L1 (L2 and L3)	Resolution	Base (W×T) (mm)	Maximum permissible error <i>E_{MPE}</i> *
571-311-20	0 - 150 mm / 0 - 6 in	0.0005 in / 0.01 mm	100×6	±0.001 in / ±0.02 mm
571-312-20	0 - 200 mm / 0 - 8 in			

- Battery: SR44 (1 pc.), **938882**. For initial operational checks (standard accessory).
- Battery life: Approx. 5 years
- * Maximum permissible error, *E_{MPE}*, is the term (notation) used in JIS B 7518: 2018, revised based on ISO/TR 14253-6: 2012.

DIMENSIONS

