

# In-Line

Pneumatic Screwdrivers

## fleX&Power

by mountz

#### **KEY FEATURES**

Various models that range from 2.6 - 95.5 lbf.in

High performance oil free motor delivers environmentally friendly, durable, power and speed. One third more power than competitive models.

Safe operation with reduced noise, vibration and low torque reaction.

High accuracy patented clutch with precision automatic shut-off clutch.

Soft texture ergonomic grip for operator comfort.

One touch torque adjustment, eliminates difficult set up of drivers. Torque nut cover prevents operator tampering.

Four different colored tool bands allow color coding of specific torque values (Red, Green, Blue, Yellow are included)

Built with new aluminum alloy to provide durability and reduced maintenance - no cracking, fading or chipping found in composite body tools.

Wide ranges and RPM selections all for easy tool specification based on application requirements.

| Min.



### **COLOR CODE RINGS**

Four different colored tool bands allow color coding of specific torque values (Red, Green, Blue, Yellow are included)



	Torque Ranges										Air	Air	Fastening Capacity	
						Grip			Weight	Noise	Usage	Hose	Machine	Tapping
Model	Driver Type	Item #	lbf.in	N.m	RPM	Dia.	Length	Drive Size	lbs.	dBa	cfm	Bore	Screw Dia	Screw Dia
XP35	Lever Start	360000	2.6 - 17.4	0.3 - 2	2200	$1^{-1}/4"$	8"	1/4" F/Hex	1.3	72	8.5	5.0 mm	M2.2 - M4.5	M1.7 - M3.5
XP35PS	Push-to-Start	360005	2.6 - 17.4	0.3 - 2	2200	$1^{-1}/4$ "	7"	1/4" F/Hex	1.2	72	8.5	5.0 mm	M2.2 - M4.5	M1.7 - M3.5
XP40	Lever Start	360001	4.3 - 30.4	0.5 - 3.4	1000	1 1/4"	8"	1/4" F/Hex	1.3	72	8.5	5.0 mm	M2.8 - M5.2	M2.2 - M4.2
XP40PS	Push-to-Start	360006	4.3 - 30.4	0.5 - 3.4	1000	1 1/4"	7"	1/4" F/Hex	1.2	72	8.5	5.0 mm	M2.8 - M5.2	M2.2 - M4.2
XP45	Lever Start	360002	6.9 - 34.7	0.8 - 3.9	800	1 1/4"	8"	1/4" F/Hex	1.3	74	8.5	5.0 mm	M3.3 - M5.8	M2.7 - M4.7
XP45PS	Push-to-Start	360007	6.9 - 34.7	0.8 - 3.9	800	1 1/4"	7"	1/4" F/Hex	1.2	74	8.5	5.0 mm	M3.3 - M5.8	M2.7 - M4.7
XP48	Lever Start	360003	4.3 - 39.1	0.5 - 4.4	1700	$1^{-1}/2$	9 1/2"	1/4" F/Hex	1.9	76	15.9	8.0 mm	M3.6 - M6.3	M2.8 - M5.3
XP48PS	Push-to-Start	360008	4.3 - 39.1	0.5 - 4.4	1700	1 1/2"	8 1/2"	1/4" F/Hex	1.8	76	15.9	8.0 mm	M3.6 - M6.3	M2.8 - M5.3
XP60	Lever Start	360004	26 - 95.5	2.9 - 10.8	550	1 1/2"	9 1/2"	1/4" F/Hex	1.9	76	15.9	8.0 mm	M5.0 - M7.6	M4.0 - M6.3
XP60PS	Push-to-Start	360009	26 - 95.5	2.9 - 10.8	550	1 1/2"	8 1/2"	1/4" F/Hex	1.8	76	15.9	8.0 mm	M5.0 - M7.6	M4.0 - M6.3



Mr. Metric is the leading metric fastner specialist in North America. Well regarded as experts in metric. Mr. Metric is known for hard to find metric items at competitive prices, Visit www.mrmetric.com

FLEXPOWER IN-LINE 01.28



#### Follow Mountz

Keep informed about our torque tool products, events and industry news. Select your favorite social media site to catch the latest news from Mountz.











Vou Tubo

naahaal:

or Blog

Linkedin