

# Right Angle

Pneumatic Screwdrivers

**flexPower**  
by mountz

## KEY FEATURES

Various models that range from 2.6 - 95.5 lbf.in.

High performance oil free motor delivers environmentally friendly, durable, power and speed. One third more power than competitive models.

Safe operation with reduced noise, vibration and low torque reaction.

High accuracy patented clutch with precision automatic shut-off clutch.

Soft texture ergonomic grip for operator comfort.

One-touch torque adjustment, eliminates difficult set up of drivers. Torque nut cover prevents operator tampering.

Four different colored tool bands allow color coding of specific torque values (Red, Green, Blue, Yellow as standard are included)

Built with new aluminum alloy to provide durability and reduced maintenance - no cracking, fading or chipping found in composite body tools.

Wide ranges and RPM selections all for easy tool specification based on application requirements.

## COLOR CODE RINGS


Four different colored tool bands allow color coding of specific torque values (Red, Green, Blue, Yellow are included)



| Model | Item # | Torque Ranges |            | RPM  | Grip Dia. | Length  | Drive Size | Weight lbs. | Noise dBa | Air Usage cfm | Min. Air Hose Bore | Fastening Capacity |                   |
|-------|--------|---------------|------------|------|-----------|---------|------------|-------------|-----------|---------------|--------------------|--------------------|-------------------|
|       |        | lbf.in        | N.m        |      |           |         |            |             |           |               |                    | Machine Screw Dia  | Tapping Screw Dia |
| XP35A | 360015 | 2.6 - 17.4    | 0.3 - 2    | 2200 | 1 1/4"    | 11 1/4" | 1/4" F/Hex | 1.75        | 72        | 8.5           | 5.0 mm             | M2.2 - M4.5        | M1.7 - M3.5       |
| XP40A | 360016 | 4.3 - 30.4    | 0.5 - 3.4  | 1000 | 1 1/4"    | 11 1/4" | 1/4" F/Hex | 1.75        | 72        | 8.5           | 5.0 mm             | M2.8 - M5.2        | M2.2 - M4.2       |
| XP48A | 360017 | 4.3 - 39.1    | 0.5 - 4.4  | 1700 | 1 1/2"    | 13 1/4" | 1/4" F/Hex | 3.25        | 76        | 15.9          | 8.0 mm             | M3.6 - M6.3        | M2.8 - M5.3       |
| XP55A | 360018 | 10.4 - 65.1   | 1.2 - 7.4  | 1000 | 1 1/2"    | 13 1/4" | 1/4" F/Hex | 3.25        | 76        | 15.9          | 8.0 mm             | M3.8 - M6.9        | M3.0 - M5.9       |
| XP60A | 360019 | 26 - 95.5     | 2.9 - 10.8 | 550  | 1 1/2"    | 13 1/4" | 1/4" F/Hex | 3.25        | 76        | 15.9          | 8.0 mm             | M5.0 - M7.8        | M4.0 - M6.3       |

**mr. metric**

Mr. Metric is the leading metric fastener specialist in North America. Well regarded as experts in metric. Mr. Metric is known for hard to find metric items at competitive prices. Visit [www.mrmetric.com](http://www.mrmetric.com)



## COIL AIR HOSE

Dual swivel hose fittings provide 360° rotation.

FLEXPOWER  
RIGHT ANGLE

01.30

**mountz**  
the torque tool specialists®

800.456.1828