



NRDDF

Recovery Unit for Flammable Refrigerants



Digital Backlit Display

Oil-Free Compressor

One Key Operation

Purge Function

Brushless DC Technology

Fast • Compact • Ignition-Proof

Sparkless, Ignition-Proof Design

- Designed and tested to UL 121201, CSA C22.2 No. 213-17 and IEC 60079-7 Standards
- Suitable for A2L, A2 and A3 refrigerants

Brushless DC Motor

- Light
- More efficient

Large Backlit Display

- Easy-to-read large LCD display
- Backlit for clarity

Twin Cylinder with 2-Row Oversized Condenser

- Fast recovery

Oil-Free Compressor

- Suitable for all commonly used refrigerants

Purge Function

- Prevent mixing of various refrigerants

Model		NRDDF			
Refrigerant Type		Category III: R-12, R-134a, R-401C, R-500, R-1234YF, R-600a Category IV: R-22, R-401A, R-401B, R-402B, R-407C, R-407D, R-408A, R-409A, R-411A, R-411B, R-412A, R-502, R-509, R-290 Category V: R-32, R-402A, R-404A, R-407A, R-407B, R-410A, R-507			
Power Supply	V/Hz	115V/60Hz			
Motor	HP	1			
Max Current Draw	A	10			
Compressor		Oil-less, Air-cooled, Piston style			
Automatic Safety Shut-Off		558 psi/38.5 bar			
Recovery Rate	lbs/min		R-22	R-134a	R-410a
		Direct Vapor	0.55	0.37	0.49
		Direct Liquid	6.88	5.34	7.98
		Push/Pull Liquid	14.2	11.00	15.1
Dimension	in	14.5" × 9.9" × 11.7"			
Weight	lbs	24.3			

1-YEAR WARRANTY *

* For recovering only HVAC/R refrigerants from sealed HVAC/R systems. Warranty Voided if used for any other purposes.